INCH-POUND

KKK-T-728B
8 September 2025
SUPERSEDING
KKK-T-728A
2 February 1973

FEDERAL SPECIFICATION

Truck, Hand, Two-Wheeled (Light Duty) 300 Pound Capacity

The General Services Administration has authorized the use of this federal specification by all federal agencies.

1. Scope and Classification

1.1 Scope. This specification covers rigid frame and collapsible frame two-wheeled light duty hand trucks (see 6.1).

1.2 Classification.

1.2.1 Types and classes. Hand trucks covered by this specification may be of the following types and classes, as specified (see 6.2).

Type I - Rigid frame.
Class 1 - Light weight (aluminum or magnesium).
Class 2 - Medium weight (steel).
Type II - Collapsible frame.
Class 1 - Light weight (aluminum or magnesium).

2. APPLICABLE DOCUMENTS

2.1 Other publications. The following documents form a part of this specification to the extent specified herein. Unless an issue is identified, the issue in effect on the date of invitation for bids or request for proposal shall apply.

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support – Construction and Equipment (C&E) (ATTN: Code FCSB), 700 Robbins Avenue, Philadelphia, PA 19111-5098 or email to CE_Standardization@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 3920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at www.asq.org or the American Society for Quality, 611 East Wisconsin Avenue, Milwaukee, WI 53202.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the reference cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard Product. Hand trucks covered by this specification shall be the manufacturer's standard commercial product except for those modifications or changes required in order to comply with this specification.

3.2 Materials. The frame of types I and II, class 1 trucks shall be made of aluminum or magnesium and be of tubular construction. The frame of type I, class 2 trucks shall be made of steel and be of tubular construction. Materials used for the other components of the truck shall be suitable for the purpose intended. All materials shall be free from defects or imperfections which may affect the appearance or serviceability of the trucks.

3.3 Wheels. Each truck shall be equipped with two wheels which are fabricated of steel, hard rubber, or suitable high impact plastic. The rated load capacity of each pair of wheels shall not be less than the test load requirements for the truck as specified herein.

3.3.1 Steel wheels. Steel wheels shall be provided with solid rubber tires which have a Shore Durometer hardness of not less than 70 on the A scale. The rubber tires shall have a thickness (i.e., wall height) of .250 ± .010 inch and a width across the tread and at the point of attachment to the wheel of .875 ± .030 inch. The diameter of the wheel including the rubber tire shall be 5 ± .250 inches.

3.3.2 Rubber wheels. Rubber wheels shall consist of a hard rubber disc with a softer rubber tread molded into the disc. The wheel disc shall have a Shore Durometer hardness of not less than 70 nor more than 95 on the D scale. The wheel tread shall have a Shore Durometer hardness of not less than 70 nor more than 85 on the A scale. The width of the wheel at the hub and across the tread shall be 1.500 ± .055 inches. An oil impregnated powdered iron or powdered bronze bushing shall be molded into the center of the wheel. The diameter of the wheel, including both disc and tread, shall be 5 ± .250 inches.

3.4 Wheel bearings. Wheels shall be provided with either anti-friction or self-lubricating sleeve type bearings.

3.5 Handle. Each truck shall be provided with one or two handles. When provided with one handle, the handle shall be in the center of the truck. The handle shall be in the form of a suitable hand grip.

3.6 Vertical stability. The front end of the nose plates shall have a thin leveled loading edge to facilitate insertion under loads. The truck shall exhibit no tendency to tip over or tilt in a pronounced manner when examined in accordance with 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.7 Type I trucks. The type I truck frame shall be of the rigid (noncollapsible) type. The frame shall consist of two side members, three or more cross members, nose plate, one or two handles, and wheel mounting brackets. Component frame members shall be joined together by bolts, rivets, or welding. The overall dimensions of the truck shall be 46 ± 2.0 inches long by 14 ± 1.0 inches wide. The truck shall be equipped with a single nose plate which is a minimum of 10 inches front to back and a minimum of 14 inches wide.

3.7.1 Weights.

3.7.1.1 Class 1. The weight of type I, class 1 trucks shall not exceed 15 pounds.

3.7.1.2 Class 2. The weight of type I, class 2 trucks shall not exceed 25 pounds.

3.8 Type II truck. The type II truck frame shall be of the collapsible type. The frame shall consist of fixed and adjustable members to which shall be attached one or two handles, two functionally located nosepieces and two wheel mounting brackets. The two nosepieces, one on each side of the frame, shall be not less than 10 inches front to back when the truck is in the operation position. Component frame members shall be joined together by bolts, rivets, or welding. The frame shall be designed so that it can be extended or opened lengthwise and crosswise to its operation shape and can be folded or collapsed when not in use. A locking device shall be provided to secure and keep the frame rigid when in its extended or open position. The overall dimensions of the truck in its extended or open position shall not exceed 52 inches in length and not more than 13 inches in width at the widest position of the frame. The truck when folded or collapsed shall occupy a space not larger than 38 by 6 by 8 inches. Means shall be provided, such as straps, clamps, or latches, to secure the truck in its folded or collapsed position.

3.8.1 Weight. The weight of type II, class 1 trucks shall not exceed 15 pounds.

3.9 Truck capacity. The types I and II hand trucks shall have a working capacity of 300 pounds plus an overload factor of 100 pounds. Trucks shall show no evidence of damage or permanent deformation when tested in accordance with 4.3.2

3.10 Welding. Welding, when applicable, shall be in accordance with good commercial practice and shall be sound and not have burnt holes, cracks, fractures, or incomplete fusions. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter.

3.11 Rivets. Rivets, when applicable, shall have full concentric heads, shall be flush to the joining member, and shall not be cracked, fractured, or broken.

3.12 Threaded fasteners. Bolts or other threaded fasteners used to join the various parts of the truck together shall be adequate in design and fabrication for the intended purposes. Bolt holes shall be accurately punched or drilled and shall have burrs removed. Washers or lock washers shall be provided in accordance with good commercial practice.

3.13 Finish. Type I, Class 2 hand trucks shall be suitably finished to inhibit corrosion. Unless a specific finish is specified (see 6.2), these trucks shall be plated or painted at the manufacturer's option. Plating shall be in accordance with good commercial practice. When a painted finish is supplied, the trucks shall have one coat of primer applied prior to painting. A durable weatherproof paint shall be used. Unless otherwise specified in the contract or purchase order (see 6.2), any color normally furnished by the manufacturer on his commercial trucks will be acceptable.

3.14 Marking. Each hand truck shall be marked in a permanent manner with the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

3.15 Instructions. The manufacturer shall furnish with each type II hand truck a pamphlet or leaflet giving complete instructions for extending or opening the truck and placing it in service and for collapsing or folding and securing the truck.

3.16 Workmanship. Workmanship shall be first class in every respect. The hand trucks shall be free from sharp edges, slivers, and burrs that may be injurious to personnel and any other defects affecting appearance and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his/her own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with ASQ-Z1.4.

4.2.1 End product inspection.

4.2.1.1 Visual examination. The sample unit shall be one completely assembled end item. The inspection level shall be level II and the acceptance quality levels (AQL's) shall be 4.0 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units. Defects shall be classified as outlined in table I for recording of inspection results and corrective action. Results shall be kept available for review by Government inspectors.

4.2.1.2 Dimensional examination. Examination shall be made of the end item to determine compliance with dimensional requirements. Any dimension that exceeds the specified tolerance shall be classified a defect. The inspection level shall be S-2 with an acceptable quality level (AQL) of 6.5 defects, expressed in defects per hundred units.

4.2.1.3 Sampling for tests. A random sample of hand trucks shall be taken from each inspection lot in accordance with ASQ-Z1.4 at inspection level S-3 for tests of 4.3. If any truck fails any of the tests, the lot shall be rejected.

4.3 Tests.

4.3.1 Stability. The truck shall be placed in a position resting on its wheels and nose plate on a level surface. All outside support shall be removed from the truck and observation shall be made for conformance to 3.6.

4.3.2 Load bearing and transporting. The nose plate of the truck shall be inserted under a 400 pound load. The load shall be lifted from the floor by applying the necessary force on the handle (s) of the truck. The loaded truck shall be rolled in normal working position a distance of 100 feet three times. On each trip the trucks shall be rolled over three 0.5 by 3 inch wood strips which are secured in a flat position on the test surface. The strips shall be generally parallel and 3 inches apart. The truck is to be rolled at a minimum speed of 3 miles per hour (4.4 feet per second). Upon completion of the three runs, the truck shall be placed in a horizontal position on the floor and the 400 pound load shall be placed on the truck bed at the center. After a period of I minute, the truck shall be unloaded and visually examined for damage or deformation (see 3.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defects	Classification Major	Minor
Finish	Type of finish not as specified: blistered, peeled, chipped, or area of no film or thin film.	X	
Material	Component not fabricated of the specified material.	X	
Design	Any characteristic not in accordance with the specified requirements.	X	
Construction and workmanship	Part missing or not specified type or size.	X	
	Damage or defects affecting serviceability or durability.	X	
	Damage or defects not affecting serviceability or durability		X
	Sharp burr, sliver, or sharp edge that may be injurious to personnel or may affect serviceability.	X	
	Type II truck difficult to extend and collapse.		X
Welding (when applicable)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused.	X	
Bolts, nuts, screws, studs, and other types of thread fasteners (when applicable)	Missing, not type specified, broken, stripped, or fractured.	X	
	Not properly tightened..		X
Assembly	Component not properly assembled or secured but not affecting serviceability.		X
	Component not properly assembled or secured affecting serviceability.	X	
	Unit perceptibly out of square or alignment.	X	
Marking	Missing, incomplete, or not legible.		X

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of material is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that is helpful, but is not mandatory.)

6.1 Intended use. The hand trucks covered by this specification are intended for use in trucking boxes and other flat freight in such areas as offices, hospitals, stores, shops, and warehouses and are also intended for use on delivery trucks.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Type and class required (see 1.2.1).
c. If a specific finish is required (see 3.13).
d. If a specific color of paint is required (see 3.13).
e. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

Frame
Truck
Wheel bearing

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - YD
Air Force - 184
DLA - CQ

Preparing activity:
DLA - CQ

(Project 3920-2025-001)

Review activities:
Army - GL, SM
Navy - SH
DLA - GS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:45Z
Check the source to verify that this is the current version before use.