MIL-H-13514E
AMENDMENT-1
25 March 1985

MILITARY SPECIFICATION

HEATERS, SPACE, RADIANT TYPE, PORTABLE 45,000 BTU/HR

This amendment forms a part of Military Specification MIL-H-13514E dated 29 June 1983, and is approved for use by all Departments and Agencies of the Department of defense.

PAGE 1

2.1 under "SPECIFICATIONS FEDERAL": Delete "QQ-S-781-Steel Strapping, Flat" and "PPD-C-843 Cushioning Material, Cellulosic."

Under "SPECIFICATIONS FEDERAL": Add "PPP-B-601-Boxes, Wood, cleated-Plywood." and "PPP-B-636-Boxes, Shipping, Fiberboard."

PAGE 2

2.1 under "STANDARDS MILITARY": Add "MIL-STD-1186-Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Methods."

Under "Drawings": Delete" 5-13-1454-Heater, Space, Radiant Type, Portable, 45,000 BTU/HR.; Container for Domestic and level "A" Shipment.

PAGES 8, 9 and 10

Delete: Sect 5 and all Subparagraphs and Substitute the following:

" 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Preservative application.

5.1.1.1.1 Type I and type II heaters. All uncoated ferrous metal surfaces of each heater and components, except the pipe sections, shall be cleaned by method C-1, thoroughly dried and coated with type P-1 preservative in accordance with MIL-P-116. The pipe sections shall be coated with preservative in accordance with MIL-P-551. All components not otherwise specified shall be preserved in accordance with method III of MIL-P-116.

FSC 4520

Source: https://assist.dla.mil -- Downloaded: 202640-18T00:45Z
Check the source to verify that this is the currentversion before use.

5.1.1.2 Unit packing.

5.1.1.2.1 Pipe sections. Six sections of pipe, prepared as specified in 5.1.1.1.1, shall be unit packed in accordance with MIL-P-551, except that prior to wrapping the pipe sections for the type I heater, one poker, one shaker, and one damper, prepared as specified in 5.1.1.1.1, shall be placed in the center of the heated pipe sections. The size of the fiberboard box shall not exceed outside dimensions of 25 by 6 by 6 inches.

5.1.2 Commercial. The pipe sections, poker, shaker, and damper shall be preserved in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Type I heater. One complete type I heater shall be packed into a close-fitting cleated-plywood box conforming to style A or I of PPP-B-601. The inside dimensions of the shipping container shall be approximately 21 by 21 by 27 inches. The heater components shall be arranged in the shipping container with the heater base being placed first and moved to one corner of the 21 by 21 inch surface. The heater top with lid secured, shall be inverted and placed inside the heater base with some cushioning material placed between the two components and adequate enough to support the weight of the heater. The fiberboard box specified in 5.1.1.2.1, shall be slid into the opposing corner to which the heater base was positioned. The grate assembly shall be wrapped with cushioning material and placed with the concave side down inside the heater top. The adapter ring shall be placed on top of the heater top assembly. The remaining components of the type I heater shall be packed in the available space in the shipping container. All components shall be cushioned, blocked, braced, and rendered immobile within the shipping container, in accordance with MIL-STD-1186.

5.2.1.2 Type II heater. One complete type II heater shall be packed by the same requirements as specified in 5.2.1.1, except that the grate assembly, damper flue, poker, shaker, shovel, and spark arrester will not be included. The burner assembly shall be packed within the inverted heater top assembly. All components shall be cushioned, blocked, braced, and rendered immobile within the shipping container, in accordance with MIL-STD-1186.

Source: https://assist.dla.mil -- Downloaded: 202640-18T00:45Z
Check the source to verify that this is the currentversion before use.

PAGE 8, 9 and 10 (cont'd)

5.2.2 Level B packing.

5.2.2.1 Type I heater. One Complete type I heater shall be packed as specified in 5.2.1.1, except the shipping container shall conform to a grade V13c, class weather-resistant, corrugated fiberboard container in accordance with PPP-B-636. The container shall be closed and reinforced in accordance with the appendix of PPP-B-636.

5.2.2.2 Type II heater. One complete type II heater shall be packed as specified in 5.2.1.2, except the shipping container shall conform to a grade V13c, class weather-resistant, corrugated fiberboard container in accordance with PPP-B-636. The container shall be closed and reinforced in accordance with the appandix of PP-B-636.

5.2.3 Commercial packing. Type I and II complete heaters, preserved as specified in 5.1, shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any special markings required by the contract, interior packages and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D3951, as applicable."

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - ME
Air Force - 84

User activities:

Army - CE
Navy - MC

Preparing activity:

Army - GL

Project No. 4520-0296

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:45Z
Check the source to verify that this is the current version before use.