MILITARY SPECIFICATION

DROGUE, PARACHUTE STATIC LINE

This amendment forms a part of Military Specification MIL-D-38024B, dated 27 August 1965, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 1, paragraph 2.1, under listing of Federal Specifications, delete "V-T-295—Thread, Nylon,"and add "PP-B-601—Boxes, Wood, Cleated-Plywood.""

Under listing of Military Specifications, delete listing in its entirety and add "MIL-L-10547 Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Fesible."

Under listing of Federal Standards, delete "FED. STD. NO. 751-Stitches, Seams and Stitchings."

Page 3, add the following new paragraph:

"4.3.2 *In-process inspection*. Inspection shall be made at appropriate stages of fabrication to determine conformance to the requirements of this specification. The Government reserves the right to exclude from consideration for acceptance any material(s) for which in-process inspection has indicated non-conformance."

Page 6, paragraph 5.1.2, first sentence. After "against," insert "deterioration and physical."

Paragraph 5.2.1, delete in entirety and substitute:

"5.2.1 Level A. Seven hundred and fifty drogues, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, V2s of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a taped liner conforming to grade V3c of PPP-B-636. Alternatively, shipping containers shall conform to overseas type, style A, type 2 load of PPP-B-601. Level A packages shall be packed fiat, three in length, five in width, and five in depth within a shipping container. Inside dimensions of each shipping container shall approximate 25½ inches in length, 22½ inches in width and 18¾ inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each fiberboard shipping container shall be closed, waterproofed, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636. Each cleated plywood shipping container shall be provided with a sealed case liner conforming

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:50Z
Check the source to verify that this is the current version before use.

to type I or II, grade C of MIL-L-l0547, and flat steel strapped in accordance with the appendix of PPP-B-601."

Paragraph 5.2.2, last sentence, after "closed" delete "method II"; and after "with" insert "method II as specified in."

Add the following new paragraph:

"5.2.2.1 When specified (see 6.2), shipping containers shall be fabricated from grade V3C or V3S fiberboard.

Page 7, paragraph 5.3, lines 2 and 3, delete "intermediate" and substitute "interior".

Paragraph 6.2, add "e. When V-board shipping containers are required for level B shipments, (see 5.2.2.1) ."

Custodians:
Army-GL
Navy—MC
Air Force-11

Preparing activity:
Army-GL

Project No. 1670-0218

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:50Z
Check the source to verify that this is the current version before use.