MIL-I-38120A(USAF)
AMENDMENT 3

16 AUGUST 1982
SUPERSEDING
AMENDMENT 2
15 February 1982

MILITARY SPECIFICATION

INDICATOR, RATE OF FLOW AND TRANSFER EFU-20/A

This amendment forms a part of Military Specification MIL-I-38120A dated 8 March 1963, and is approved for use by all Departments and Agencies of the Department of Defense.

Add to bottom of Page 1:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 1

*Delete 1.1 and substitute:

"1.1 Scope. This specification covers one type of in-flight refueling rate of flow and fuel transfer indicator, designated EFU-20/A.

*Delete 2.1 and substitute:

"2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein."

SPECIFICATIONS:

FEDERAL:

Delete: "PPP-B-636, Box, Fiberboard."

Add: "PPP-B-1672, Box, Shipping, Reusable with Cushioning."

MILITARY:

Delete the following specifications in their entirety:

"MIL-P-7936 Parts and Equipment, Aeronautical, Preparation for Delivery.
MIL-T-9107 Test Reports, Preparation of.
MIL-I-26600 Interference Control Requirements, Aeronautical Equipment."

Delete "MIL-D-70327 Drawings, Engineering and Associated Lists" and substitute "DOD-D-1000 Drawing, Engineering and associated List."

FSC 6680

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:55Z
Check the source to verify that this is the currentversion before use.

PAGE 2

Under STANDARDS add:

"FEDERAL:

FED-STD-595 Color"

Under MILITARY:

Delete "MS33586 Metals, Definition of Dissimilar" and substitute "MIL-STD-889 Dissimilar Metals."

* Add: "MIL-STD-129 Marking For Shipment and Storage."
* "MIL-STD-147 Palletized Unit Loads."
"MIL-STD-701 Lists of Standards Semiconductor Devices."
"MIL-STD-794 Parts and Equipment, Procedures for Packaging and Packing of."
"MIL-STD-826 Electromagnetic Interference Test Requirements and Test Methods."
"MIL-STD-831 Test Reports, Preparation of."
* "MIL-STD-1188 Commercial Packaging of Supplies and Equipment."

*Delete parenthetical source paragraph and substitute the following:

"(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)"

*Delete 3.1 and substitute the following:

"3.1 First Article. The indicator furnished under this specification shall be a product which has been tested and passed the first article test specified herein."

PAGE 3

Paragraph 3.4.4, line 3: Delete "MS33586" and substitute "MIL-STD-889".

PAGE 6

Paragraph 3.5.6, line 3: Delete "MIL-STD-704" and substitute "MIL-STD-701".

PAGE 10

Paragraph 3.7, line 4: Delete "MIL-D-70327" and substitute "DOD-D-1000".

PAGE 11

Add the following new paragraph:

"3.11 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:55Z
Check the source to verify that this is the current version before use.

*Delete 4.1 and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

*Under 4.2, delete a. and b. and substitute:

"a. First Article Tests"
"b. Quality Conformance Tests"

PAGE 12

*Delete 4.4 and substitute: "4.4 First Article Testing".

*4.4.1, line 1, delete "qualification" and substitute "first article".

4.4.2, line 3: Delete "MIL-T-9107" and substitute "MIL-STD-831".

*4.4.3, delete and substitute:

"4.4.3 First Article Tests. The first article tests shall consist of all the tests described under 4.6."

*4.5, line 1, delete and substitute:

"4.5 Quality conformance. Quality conformance shall consist of:"

PAGE 17

*Add the following new paragraph:

"4.7 Inspection of packaging. The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of MIL-STD-794."

*Delete paragraph 5 through 5.2.3 in its entirety and substitute the following:

"5. PACKAGING.

5.1 Preservation. Preservation shall be level A, C, or Industrial as specified (see 6.2).

5.1.1 Cleaning. Indicators shall be cleaned in accordance with MIL-P-116, process C-1.

5.1.1.2 Drying. Indicators shall be dried in accordance with MIL-P-116.

5.1.1.3 Preservative applications. Preservatives shall not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:55Z
Check the source to verify that this is the current version before use.

5.1.1.4 Unit packs. Each indicator shall be individually packaged in accordance with MIL-P-116, Method III. Unit packs shall be individually packed in containers conforming to PPP-B-1672.

5.1.2 Level C. The level C preservation for indicators shall conform to the MIL-STD-794 requirements for this level. OR

5.1.2 Industrial. The industrial preservation of indicators shall be in accordance with the requirements of MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, C, or Industrial, as specified (see 6.2).

5.2.1 Level A. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level A protection.

5.2.2 Level B. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level B protection.

5.2.3 Level C. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level C protection. OR

5.2.3 Industrial. The packaged indicators shall be packed in accordance with the requirements of MIL-STD-1188.

5.2.4 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination equal 40 cubic feet or more. Quantities less than 40 cubic feet need not be unitized. Unitized loads shall be uniform in size and quantities to the greatest extent possible. Unitized loads shall be in conformance with MIL-STD-147.

5.3 Marking.

5.3.1 Level A, B, C. In addition to any special or other identification marking required by the contract (see 6.2), each unit pack exterior container and unitized load shall be marked in accordance with MIL-STD-129.

5.3.2 Industrial. Industrial marking shall be in accordance with the requirements of MIL-STD-1188.

5.4 General.

5.4.1 Exterior containers. Exterior container (see 5.2.1, 5.2.2, and 5.2.3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent possible.

PAGE 18

*Under 6.2 add the following new paragraph d.:

"d. Where the first article test samples should be sent and instructions concerning the submittal of the test reports."

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:55Z
Check the source to verify that this is the currentversion before use.

*Add the following new paragraph:

"6.2.1 Contracts or Orders should specify the following provisions for first article inspection:

"a. Whether first article tests are required. When a contractor is in continuous production of the indicator from contract to contract, consideration should be given to waive the first article tests."

"b. If first article test is required indicate:

1. Where the first article test is to be conducted (at the contractor's plant or Government or commercial laboratory).

2. That the approval of first article samples or the waiving of the first article tests shall not relieve the contractor of his obligation to fulfill all other requirements of the specifications."

*6.4, delete in its entirety.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Review activity:
DLA - GS

Preparing activity:
Air Force - 99

(Project 6680-F195)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:55Z
Check the source to verify that this is the current version before use.