MIL-P-38026A(USAF)
Amendment 4
16 May 1979
Superseding
Amendment 3
23 July 1971

MILITARY SPECIFICATION

POWER SUPPLY ECU-23 /A

This amendment forms a part of Military Specification MIL-P-38026A(USAF) dated 31 January 1968.

PAGE 1

2.1: Under Military Specifications delete "MIL-S-3151 and MIL-G-6099 and titles thereto."

*2.1: Under Military Specifications add "MIL-G-21480, Generator System 400 Hertz, Alternating Current, Aircraft, General Specification For."

PAGE 2

*2.1: Under Military Standards delete "MS33586 and title thereto."

*Delete Paragraph 3.3.1.1

Add "3.4.1.4 Reliability. The power supply shall have a minimum acceptable mean-time-between-failures (MTBF) of 450 hours demonstrated to a 90% confidence level."

PAGE 7

Figure 3: In the right-hand configuration, delete output terminal length ".510 MIN." and substitute ".750 MIN."

PAGE 8

Delete Paragraph 3.11.3 and substitute:

*"3.11.3 Cadmium plating. Parts which require corrosion protection in order to meet environmental and performance requirements contained herein shall be plated or otherwise suitably protected. Cadmium plating in accordance with QQ-P-416 shall be used where applicable only when no other protection process can reasonably provide the required protection. The use of cadmium plating shall require approval of the procuring activity."

FSC 6130

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:50Z
Check the source to verify that this is the currentversion before use.

PAGE 13

*4.6.7, line 31: Delete "MIL-G-6099" and substitute "MIL-G-21480."

PAGE 15

4.6.13: Delete and substitute:

"4.6.13 Acoustical noise. The acoustical noise of the power supply shall be measured in planes 1 foot from each of the six sides. In each plane, measurements shall be made over the entire surface to determine the maximum sound level. The distance between adjacent points of measurements shall not exceed 2 inches. The maximum sound level at any point shall not exceed 67 db when measured using the "B" scale of an integrating-type sound level meter having an overall (microphone, filter, amplifier) characteristic in accordance with figure 5. Microphone orientation shall be in accordance with the recommendations of the manufacturer of the sound level meter to obtain the required frequency response. The calibrating devices or standards used shall be directly traceable to the National Bureau of Standards. Measurements shall be made in an anechoic chamber with the power supply supported in a manner to minimize acoustic transmission and reflection by the support structure. Measurements shall be made with the power supply operating at full rated load after a warmup period of at least 30 minutes at full load."

Add:

"4.6.13.1 Acoustical noise retest. Acoustical noise tests of the power supply subsequent to initial acceptance by the Air Force shall be conducted in accordance with 4.6.13 except that:

a. The maximum sound level shall not exceed 75 db.

b. Alternate warmup conditions are permitted provided that the full load and overload ratings of the power supply are not exceeded."

PAGE 18

Add:

"4.6.28 Reliability. If the power supply passes the qualification tests without failure, it will be considered to have met the reliability requirements specified in 3.4.1.4."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:50Z
Check the source to verify that this is the current version before use.

*6.3, line 17: Delete "Aeronautical System Division, Attn: ENJPE-10, Wright-Patterson Air Force Base, Ohio 45433" and substitute "Sacramento ALC/MMIRE, McClellan AFB CA 95652."

Change paragraph 6.4 to Paragraph "6.5" and add:

*"6.4 Reclaimed materials shall be utilized to the maximum extent possible within the quality limits required by this document and to fulfill compliance with the Resource Conservation/Recovery Act of 1976. (Public Law 94-580 dated 21 October 1976)."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based upon the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Review Activity:
DLS - GS

Agent: SM-ALC/MMEDO

Project 6130-F190

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:50Z
Check the source to verify that this is the current version before use.