MIL-B-16755B
20 February 1967
SUPERSEDING
MIL-B-16755A (DM)
22 October 1964

MILITARY SPECIFICATION

BOTTLE, NURSING, WIDE MOUTH

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers wide mouth nursing bottles without caps, nipples, or closure disks.

1.2 Classification.

Size 1 - 4 ounces
Size 2 - 8 ounces

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

FSC 6530

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-626 Glassware, Methods for Sampling and Testing

Military

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 Marking for Shipment and Storage.

DRAWINGS

Defense Personnel Support Center (DPSC) Drawing

20157 Bottle, Nursing, Wide Mouth, Revised 21 December 1966

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First Article. Unless otherwise specified, prior to the start of production of the contract quantity, one sample of the bottle shall be tested by the contractor. The sample shall be submitted, together with the contractor's inspection and test reports, to the procuring contracting officer for examination and testing to determine compliance with the requirements of this specification. Written approval of the materials, construction, and performance of the sample shall be obtained from the procuring contracting officer, or his authorized representative, prior to the manufacture and assembly of the remaining quantity to be manufactured. Pending approval of the first article, acquisition of materials, components, or commencement of production is at the sole risk of the contractor. Accepted sample shall become the property of the procuring activity and shall be included in the quantity called for in the contract or order. In the event that the sample is not approved, the contractor shall submit a new sample for approval, or modify the existent sample so as to remove the deficiencies cited.

3.2 Material. Bottles shall be made from a good grade of heat-resistant, clear, colorless glass. The finished bottles shall meet the thermal shock test specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

3.3 Construction.

3.3.1 Design and dimensions. Design and dimensions of the bottle shall be in strict accordance with Defense Personnel Support Center (DPSC) Drawing 20157. The dimensions of the bottles shall be such that when the bottles are filled to their specified capacities, an inverted nipple will not be in contact with the contents.

3.4 Markings.

3.4.1 Graduation markings. Bottles shall be suitably marked with graduation markings in ounces with half-ounce divisions to at least 4-ounces for size 1 and 8-ounces for size 2.

3.4.2 Identification markings. Bottles shall be marked with the manufacturer's name or registered trademark. Marking shall be accomplished by molding with the letters sufficiently raised to be clear and distinct.

3.5 Weight. Weight of bottles shall be 4-3/4 ± 1/2 ounces for size 1 and 6-1/2 ± 1 ounces or size 2.

3.6 Workmanship. Workmanship shall be first class throughout. Bottles shall be symmetrically made, properly finished and annealed, (see 4.4), and reasonably free from seeds, blisters, and other imperfections.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier shall utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to insure that supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual and auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties).

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

4.2 Sampling. Sampling for examination shall be conducted in accordance with MIL-STD-105

For visual examination	Inspection level	AQL (defects per hundred units)
Major defects	II	1.0
Total (major and minor combined)	II	4.0
Dimensions	S-2	2.5

4.2.1 For tests. Sampling for tests shall be conducted in accordance with Inspection level S-3 of MIL-STD-105. The acceptance level shall be zero.

4.3 Examination. The bottles shall be examined to determine compliance with all the requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the following classification of defects.

Categories and defects *

Major

101	Bottles not of clear colorless glass.
102	Bottles not free from seeds, blisters, and other imperfections.
103	Inverted nipple makes contact with contents when bottle is filled to specified capacity.
104	Weight of bottle not as specified.
105	Bottles do not stand up easily, but tend to tip and fall.
106	Bottles not free from mold flash on the threads.

Minor

201	Identification marking not complete, permanent, or legible.
202	Bottles not free from dirt and extraneous matter.
203	Bottles not of acceptable shape as shown on the drawing.

* Examination shall not be restricted to the classified possible defects listed above.

4.3.2 Dimensional examination. The bottles shall be examined for defects in dimensions. Any dimension not within the tolerance specified herein shall be classified as a defect.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Strain. Bottles shall be tested for strain in accordance with the requirements of method 420 of FED-STD-626.

4.4.2 Shock. Bottles shall be tested for thermal shock (90° F. differential) in accordance with the requirements of method 402 of FED-STD-626.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One box (36 bottles), as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table I shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table I. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	NOT REQUIRED	4 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Unit package shall be a carton of appropriate size constructed in accordance with PPP-B-636, type CF, class domestic. Closure shall be adequate to prevent accidental opeing. Carton design shall include full height partitions, top and bottom pads constructed of the same material as the box, so arranged that each bottle is contained in a individual cell.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with 30.4 of PPP-B-636.

Source: http://www.everyspec.com Downloaded: 2006-10-27T09:51:09
Check the source to verify that this is the current version before use.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic and method I closure shall be utilized.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. In addition the following legend shall be shown:

"GLASS - HANDLE WITH CARE"

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packing (see 5.1 and 5.2).
(c) When first article is not required (see 3.1).
(d) Where first article shall be sent (see 3.1).

6.2 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Category N

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements .

SPECIFICATION

MIL-B-16755B

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64, WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:21Z
Check the source to verify that this is the current version before use.