MILITARY SPECIFICATION

COMPRESSORS, RECIPROCATING, ELECTRIC

MOTOR DRIVEN, NAVAL SHIPBOARD DIESEL

ENGINE AIR STARTING SERVICE

This amendment forms a part of Military Specification MIL-C- 16645A (SHIPS), 29 April 1955.

Page 3, paragraph 2, 1 continued: Under Navy Department Specifications delete reference to "General Specifications for Inspection of Material."

Page 3, paragraph 2. 1 continued: Under Publications add:

"BUREAU OF SHIPS

"NAVSHIPS 250-637-2 - Instructions for Torch Brazing of Ferrous and Non-Ferrous Piping.

"NAVSHIPS 250-648-8 - Inspection and Test of Silver-Brazed Piping Systems."

Page 4, paragraph 3. 1: Delete.

Page 6, paragraph 3.3, 12. 1: Delete "basis" and substitute "bases".

Page 8, paragraph 3.3. 17. 1; line 8: Insert "and in" before "technical manuals".

Page 8, paragraph 3. 3. 18: Add as last sentence "Silver brazed joints shall be in accordance with NAVSHIPS 250-637-2, For joints 1 / 2 inch and above, preinserted ring fittings shall be used. For sizes below 1/2 inch, face feed fittings may be used. "

Page 14, Table II: Under "A", second column: Delete "Valves, discharge, for all stages" and "Valves, inlet, for all stages".

Page 14, Table II: Add the following:

"E - 300 percent for all compressors: Valves, air cylinder, wearing parts only."

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:16Z
Check the source to verify that this is the current version before use.

Page 16, paragraph 4. 1 through 4. 1. 1: Delete and substitute:

“4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 17, paragraph 4.2, line 2: Delete “by the Government inspector".

Page 17, paragraph 4.3: Delete and substitute:

"4, 3 Acceptance tests. -"

Page 17, paragraph 4.3. 1, lines 1 and 2: Delete "at the place of manufacture”.

Page 17: Add the following paragraph as 4.3. 1. 1:

“4. 3. 1. 1 Inspection and test of joints in systems designated as hazardous in manual NAVSHIPS 250-648-8 shall be in accordance with the require ments of that manual. "

Page 19, paragraph 4.4.4, line 2: Delete “by the Government inspector”,

Page 19, paragraph 4$_0$405, line 2: Delete “by the Government inspector”=

Page 21, paragraph 4.5: Delete.

Pages 22 and 23, paragraph 6.1 (e): Delete “when” and substitute "What”.

Page 23, paragraph 6.2: Delete.

Preparing activity:
Navy - Ships
(Project 4310-N026Sh)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:16Z
Check the source to verify that this is the current version before use.