MIL-A-16749E(SHIPS)
AMENDMENT-2
17 June 1968
SUPERSEDING 1/
AMENDMENT-1
28 May 1965

MILITARY SPECIFICATION

AMPLIFIER, AUDIO FREQUENCY, SOUND POWERED TELEPHONE SYSTEM

This amendment forms a part of Military Specification MIL-A-16749E (SHIPS), 15 May 1963.

Page 3

3.4.1, delete and substitute:

"3.4.1 Under normal conditions, with the amplifier turned on, incoming signals from the remote sound powered telephone station shall be amplified and transmitted to the sound powered telephone headsets and the loudspeakers at the local station. The amplifier shall incorporate a sensitive switching means which shall operate to reduce the amplifier output to zero and to connect the headsets at the local station to the remote station when the talk switch of any of the local station headsets is operated. The sound powered telephone headsets will have d.c. blocking capacitors in their receiver circuits. The d.c. resistance of the microphone unit will be approximately 4.6 ohms, and the resistance of the line between the headset and the amplifier will be between 0 and 5 ohms. The sensitive switching circuit current, which flows through the microphone unit when the talk switch is operated, shall not exceed 3.5 milliamperes. The voltage of this switching circuit shall not exceed 4 volts d.c."

Page 4

3.5.5 through 3.5.8: Delete "of the loudspeaker" and substitute "for the loudspeaker".

3.5.10, line 2: Delete "ront" and substitute "front".

3.5.10.1, delete and substitute:

"3.5.10.1 Power switch. Operation of the power switch shall place the amplifier in a ready condition by connecting both sides of the available 115-volt, 60 cycle, single-phase power supply to the amplifier. In addition, another section of the switch shall connect the input signal direct to the telephone output terminals when the switch is in the "off" position."

3.5.10.3: Add "Volume attenuation shall be obtained by counter-clockwise rotation of the knob."

Page 5

3.6.1, line 2: Delete "major parts" and substitute "controls"; and add as last sentence, "The panel and chassis shall be removable as a subassembly."

3.6.2, line 3: Delete "20" and substitute "22".

Page 6

4.3.2, line 4: Delete "case" and substitute "cause".

1/ CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

FSC 5805

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:21Z
Check the source to verify that this is the current version before use.

4.4: Add "In all electrical tests, the sound powered telephone output terminals shall be loaded with a simulated load of 600 ohms resistance and 0.47 microfarad capacitance in series."

4.4.5, line 5: Delete "across a resistive load of 600 ohms" and substitute "loaded as specified in 4.4".

4.4.7, line 2: *Insert "speaker"* between "amplifier" and "output".

Preparing activity:
Navy - SH
(Project 5805-N123)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-510/A-752

Source: https://assist.dla.mil -- Downloaded: 202640-18T09:21Z
Check the source to verify that this is the current version before use.