MIL-D-16712C(GL)

25 March 1969
SUPERSEDING
MIL-D-16712B(GL)
28 December 1964

MILITARY SPECIFICATION

DRILLING MACHINES, PAPER, ELECTRIC MOTOR DRIVEN

1. SCOPE

* 1.1 Scope.- This specification covers cabinet type, electric motor driven, paper drilling machines (see 6.1).

* 1.2 Classification.- The machines shall be of the following styles, as specified (see 6.2).

Style 1 - Single spindle, non-automatic feed.
Style 2 - Three spindles, automatic feed.

* 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CC-M-636	-	Motors, Fractional Horsepower (Alternating-Current).
UU-P-271	-	Paper, Wrapping, Waterproofed, Kraft.
MMM-A-260	-	Adhesive, Water-Resistant, (For Sealing Water-proofed Paper).
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	-	Preservation, Methods Of.
MIL-B-121	-	Barrier Material, Greaseproofed, Water-Proofed, Flexible.
MIL-V-173	-	Varnish, Moisture and Fungus Resistant (For the Treatment of Communications, Electronic, and Associated Electrical Equipment.)
MIL-P-514	-	Plates; Identification, Instruction and Marking, Blank.
MIL-L-10547	-	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-130	-	Identification Marking of U. S. Military Property.
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement Of.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C., 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, Mass. 02110).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies).

* 3. REQUIREMENTS

3.1 First article.- When specified (see 6.2), before production is commenced, a sample of the required drilling machine conforming to this specification, shall be made available to the contracting officer or his authorized representative for approval in accordance with 4.2. Approval of the preproduction sample authorizes commencement of production but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product.- The paper drilling machines covered by this specification shall be the regular commercial product of the manufacturer, except for any changes necessary to comply with this specification. All machines of the same style furnished under any one contract or purchase order shall be identical throughout, including parts and assemblies thereof.

3.3 Materials and components.- Materials and components shall conform to the requirements specified herein, except materials and components not specifically defined shall be of the quality normally supplied by the manufacturer for drilling machines provided the completed item complies with all provisions of this specification.

3.4 Design and construction.- The drilling machines shall be for floor mounting and shall be designed for drilling holes in lifts of paper by means of removable hollow drill bits mounted in a single or 3 spindle drill head assembly, as applicable. The drill head assembly shall be electric motor driven, and shall operate over a table assembly. The drill head assembly and table assembly shall be mounted on, or made a part of, a metal cabinet-type base. The stroke or feed of the spindles shall be vertical and shall be actuated in response to foot pressure applied to a treadle at the cabinet base. All operating controls shall be accessible from the operator's normal working position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

3.4.1 Style 1 machine.- The style 1 machine shall have an electric motor driven, single spindle drill head assembly. The power required to feed the drill head spindle shall be developed by foot pressure applied by the operator to the treadle fixed at the base of the cabinet. The machine shall have capacities and dimensions conforming to table I. The machine shall be furnished completely wired. The wiring circuit shall originate in a grounding type attachment plug molded to not less than 7 nor more than 8 feet of flexible electrical cord extending beyond the cabinet base.

TABLE I.- Style 1 machine

Capacities and dimensions	Measurement (Inches)
Size of table, length by width (min.)	19 by 26
Height, table	36-1/2 ± 2
Height, overall (max.)	58
Floor space, overall (max.)	36 by 46
Drill sizes (1/32 increments)	1/8 thru 1/2
Capacity, round hole drilling depth, (1/4 thru 1/2 in. drills)	2
Min. hole spacing using indexing stops (not more than)	3/8
Min. distance to side guide	0
Max. distance to side guide (not less than)	18
Back margin adjustment	0-4 (min.)
Vertical adjustment, drill head assembly (min.)	1/2

3.4.2 Style 2 machine.- The style 2 machine shall have a belt driven, three spindle, drill head assembly, powered by an electric motor. The drill head spindles shall have a non-repeating, automatic power feed, actuated in response to foot pressure applied to the treadle fixed at the base of the cabinet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

Each cycle of the spindle feed shall require reapplication of pressure to the treadle. The machine shall have capacities and dimensions conforming to table II. The machine shall be furnished fully wired. The wiring circuit shall originate from marked terminals in an outlet box and shall be grounded.

TABLE II.- Style 2 machine

Capacities and dimensions	Measurement (Inches)
Size of table (min.)	19 by 26
Height, overall (max.)	58
Height of table	36-1/2 ± 2
Floor space, overall (max.)	36 by 46
Drill sizes (1/32 increments)	1/8 thru 1/2
Maximum size drill for:	
3-hole drilling	3/8 or 1/2
1 and 2-hole drilling	1/2
Capacity, round hold drilling depth (1/4 thru 1/2 in. drills)	2
Vertical adjustment, drill head assembly (min.)	1/2
Vertical adjustment, outside spindles (min.)	1/4
Center to center adjustment between 3-spindles (min.)	2-3/4 to 4-1/2
Center to center adjustment between 2-outside spindles (min.)	5-1/2 to 9
Min. hole spacing using indexing stops (not more than)	3/8
Side guide adjustment from left hand drill	0-14 (min.)
Back margin adjustment	0- 4 (min.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

3.4.3 Electrical.- Unless otherwise specified (see 6.2), the machines shall be designed to operate on a 120 volt, 60 hertz, single phase power source. Electric motors shall conform to CC-M-636. The motor shall be controlled by a starter of the nonautomatic type, and shall have overload protection provided by means of a thermal overload device compatible with the electric motor.

3.4.3.1 Fungus and moisture resistance.- When specified (see 6.2), the electrical circuitry, including all components and connections, shall be protected from the effects of moisture and fungus growth by an overall treatment with a varnish conforming to MIL-V-173 with the following exceptions:

(a) Components or circuit elements which are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.

(b) Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a minimum dry-film thickness of 0.001 inch to component or element surfaces previously cleaned and prepared.

3.4.3.2 Electromagnetic compatibility.- Unless otherwise specified (see 6.2), equipment procured under this specification shall conform to class IIB requirements of MIL-STD-461 (see 4.4.1).

3.4.3.3 Wiring.- All wiring shall conform to the applicable requirements of the National Electrical Code (NFPA No. 70). All wiring shall be neat, sturdy, and as short as practicable, except that sufficient slack shall be provided to prevent stress on wires and connections. Wires shall be protected against abrasion where necessary and shall not be bent sharply around corners or edges that might cut or abrade the insulation. Where wires run through holes in metal, the insulation shall be protected with approved grommets or bushings. All conductors shall be continuous between outlets and there shall be no splice or tap within a raceway. Electrical connections shall be mechanically secured.

3.4.3.4 Worklight.- The machine shall be equipped with a permanently attached worklight to illuminate the table. The light shall be provided with its own switch, so that the table may be illuminated regardless of the motor control setting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

3.4.4 Spindle adjustment.- Manually operated adjusting devices shall be incorporated in the drill head assembly for setting the feed depth of the spindle (see tables I and II), to insure drilling the bottom sheet of each lift of paper, and to compensate for any variability in length of drills. In addition, on 3-spindle drills, manually operated devices shall be provided for individual lateral adjustment of the outside spindles (see table II).

3.4.5 Paper clamp.- An automatic clamping device shall be provided for each spindle to automatically retain the lift of paper throughout the entire drilling cycle.

3.4.6 Table assembly.- The table assembly shall include guides, scales, and indexing stops for use in positioning lifts of paper in relation to the drill spindles, Scales graduated in inches and sixteenths shall be provided for use in setting the back guide and indexing stops. Provisions shall be made for automatic or semiautomatic indexing between drilling strokes, for not less than 6 successive drilling positions. The table area directly below the drill bits shall be recessed to receive replaceable flush mounted, wood or plastic blocks for the drills to cut against.

3.4.7 Cabinet base.- The cabinet base shall have a means for fastening to the floor. A removable container for drill chips shall be provided. The drill chips shall be ejected through the hollow drills and drill head to the chip receptacle.

3.4.8 Screw threads.- All screw-threads shall conform to Handbook H-28.

3.4.9 Lubrication.- All parts requiring lubrication shall be lubricated. Where parts require periodic lubrication, the parts shall be provided with accessible and appropriate fittings to facilitate lubrication. All fittings shall be tagged to indicate the recommended commercial lubricant.

3.5 Finish.- The machine shall be given the manufacturer's regular finish normally provided on his standard commerical machines.

3.6 Marking for identification.- The machines shall be marked for identification in accordance with MIL-STD-130 on an identification plate conforming to MIL-P-514.

3.7 Performance characteristics.- When tested as specified in 4.4.2 through 4.4.3.2, the machines shall drill clean, accurately sized and located holes in lifts of paper of the pile height indicated in table III for the drill diameters indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

TABLE III.- Drilling capacity, inches

Drill diameter	Pile height
1/8	5/8
5/32	1-1/8
3/16	1-1/2
7/32	1-1/2
1/4 thru 1/2	2

The holes drilled in the top and bottom sheets of each lift of paper shall register with each other and with the scale readings, of indexing stops, and back gage within 1/64 inch.

3.8 Accessories.- The following accessories shall be provided with each machine:

(a) One each 1/4, 3/8, and 1/2 inch hollow drills for each spindle.
(b) One dozen replacement cutting blocks.
(c) One self-aligning drill sharpener.

3.9 Technical publications, repair parts, and tools.- Such technical publications, repair parts, and tools as are specified (see 6.2) shall be furnished with each machine.

3.10 Workmanship.- The end item shall be clean and free of sharp and rough edges, projections, cracks, and breaks. All components and assemblies shall be in proper alignment, with all fastening devices drawn tight. All functioning components, and adjusting devices, shall operate without binding. Welded and soldered connections, when used, shall show complete fusion and shall be free of undercut, burn-through, and breaks in and adjacent to the welded and soldered areas. All painted and plated surfaces shall be uniformly coated and free from runs, teardrops, sags, foreign inclusions, blisters, peeling, and any other defects indicative of faulty surface preparation or application of finishes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

* 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.- When a preproduction sample is required it shall be examined for defects in table IV, specified dimensions and capacities, and tested as specified in 4.4.1 through 4.4.3.2, as applicable.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified,or qualified in this specification or applicable purchase document.

4.3.2 Process inspection.- An examination shall be made during the manufacturing process to determine compliance with the fungus and moisture treatment requirements of electrical circuitry in 3.4.3.1, when applicable. Whenever a deviation is noted correction shall be made to affected items and process.

4.3.3 End item inspection.- The lot shall be all machines of the same style offered for inspection at one time. The sample unit shall be one complete end item.

4.3.3.1 Visual examination.- The end item shall be examined for defects classified in table IV. The inspection level shall be II. The acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

TABLE IV.- Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not as regularly furnished by manufacturer		X
Plated finish, when applicable	Blister, nodule, or peeling of plated finishes	X	
Painted finish	Run, teardrop, sag, grit, foreign inclusion, peeling, not uniformly coated		X
	Evidence of rust	X	
Construction and workmanship	Any part fractured, split, punctured, dented, malformed, or otherwise impaired	X	
	Any burr, sliver, or splinter	X	
	Misalignment of components	X	
	Weld defective (when applicable)	X	
	Fastening device missing		X
	More than one fastening device missing	X	
	Fastening device not drawn tight		X
	More than one fastening device not drawn tight	X	
	Not manufacturer's standard product except as otherwise required herein	X	
	Machines of same style not identical throughout	X	
	Not specified style of machine	X	
	Not designed for floor mounting	X	
	Stroke or feed of spindle not vertical	X	
Electrical assembly	Wiring cut, abraded, not properly joined, loose at terminal, grommets or bushings omitted, wiring bent sharply around corners or edges that might cut or abrade the insulation	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

TABLE IV.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Electrical assembly (cont'd)	Conductor not continuous in raceway	X	
	Inadequate slack for wiring to relieve strain or excessive insulation stripped from wiring	X	
	Connections not mechanically secured	X	
	Wiring incomplete	X	
	Terminal ends of wires not marked, (Style 2)		X
	Thermal overload missing	X	
	Worklight not provided with independent switch		X
Operating controls	Any mechanical or electrical control or adjusting device inoperative or missing	X	
	Improperly located		X
	Not specified type		X
Lubrication fittings	Missing (when applicable)		X
	Not accessible	X	
Lubrication	Not lubricated		X
	Not tagged to identify recommended lubricant		X
Scales	Any scale missing or not graduated as specified	X	
Guides and indexing stops	Not specified type		X
	Less than 6 indexing stops provided	X	
	Indexing operation not automatic or semi-automatic		X
Cutting blocks	Not provided or improperly located	X	
	Not removable	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

TABLE IV.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Cabinet base	Floor mounting holes not provided		X
	Chip container missing or not removable	X	
Accessories	Missing, incorrect quantity, size, or type		X
Technical publication (when applicable)	Incorrect, missing, or illegible		X
Repair parts and tools, when applicable	Missing, incorrect quantity or variety		X
Identification marking	Missing, illegible, incorrect, or improperly applied		X

4.3.3.2 Dimensional and capacity examination.- The end item shall be examined for compliance with requirements in tables I and II, as applicable. Any evidence of non-compliance shall be classified a defect. The inspection level shall be S-2. The AQL shall be 4.0 expressed in terms of defects per hundred units.

4.3.3.3 End item testing.- When a preproduction sample is not required, the initial production unit shall be tested in accordance with 4.4.1 when electromagnetic compatibility is required. In addition, production units shall be tested in accordance with 4.4.2 through 4.4.3.2, as applicable, using inspection level S-1, with no evidence of failure.

4.3.3.4 Code and standards compliance.- Proof of compliance with NFPA No. 70 (see 3.4.3.3) shall be made available to the Government representative.

4.3.4 Examination of preparation for delivery.- An examination shall be made to determine that preservation, packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table V. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be all of the containers offered for inspection at one time. The inspection level shall be S-2 and the acceptable quality level shall be 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

TABLE V.- Examination of preparation for delivery

Examination	Defect
Markings, exterior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Preservation	Preservative improperly applied or missing.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as blocking and bracing inadequate or improperly affixed, case liner not sealed.

4.3.4.1 Examination of shipping containers.- Examination for defects in closure and strapping or shipping containers shall be in accordance with the appendix of the applicable container specification.

4.4 Tests.

4.4.1 Electromagnetic compatibility.- When applicable, the preproduction sample or initial unit of production, equipped for the reduction of radio interference in accordance with 3.4.3.2, shall be tested by the supplier in accordance with Test Methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish the contracting officer for approval, the Interference Control Plan, EMI/EMC Test Plan and the Electromagnetic Compatibility Test Report required in MIL-STD-461. The report shall include all the required information. Upon approval of the report by the contracting officer and provided all other requirements of the specification are met, the preproduction sample or initial unit of production, as applicable, shall be used as a model for all production units.

4.4.2 Controls and adjusting devices.- All operating controls and adjusting devices shall be operated throughout their normal range of operation to determine that the required function can be performed. Measurements shall be taken to determine that the adjusting devices afford the range of adjustment specified in tables I and II, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

4.4.3 Performance tests.- Tests shall be performed in accordance with 4.4.3.1 and 4.4.3.2, as applicable. The paper required shall be 14 by 20 inch onion skin or manifold paper, having a substance weight not exceeding 10 pounds (500 sheets - 17 by 22 inches).

4.4.3.1 Style 1 machines.- The table shall be loaded with a 5/8 inch lift of paper. A 1/8 inch drill shall be mounted in the spindle. The back guide shall be set for drilling a minimum distance from the back edge of the paper. The indexing stops shall be set for drilling and indexing of six holes equally spaced, center to center, along the 20 inch dimension, with the end holes equal distance, but not more than one inch, from each end of the paper. After drilling, the top or bottom sheet of the drilled pile shall be turned over, end for end, and the holes of the top and bottom sheets overlayed. Inspection shall then be made to determine compliance with the dimensional, quality, and registration requirements in 3.7. Then, with the back guide set for a 1/4 inch margin between the edges of the sheet and holes, the foregoing test and inspection shall be repeated using 5/32, 3/16, 3/8, and 1/2-inch drills with paper pile heights as indicated in table III, for each drill size.

4.4.3.2 Style 2 machines.- Style 2 machines shall be tested in accordance with 4.4.3.1, except for drill sizes through 3/8 inch, a drill shall be mounted in each spindle. For 1/2 inch drill size, drills shall be mounted in 2 of the 3 spindles.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Disassembly.- Detachable components shall be detached from the drilling machine in order to reduce cube and prevent damage while in transit. Disassembly shall be limited so as not to require special tools or skills at reassembly.

5.1.1.2 Preservation.-

5.1.1.2.1 Cleaning and drying.- All exposed, uncoated, ferrous metal surfaces of each drilling machine, including detached components, tools, and accessories, shall be cleaned process C-1 of MIL-P-116 and thoroughly dried.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

5.1.1.2.2 Application of preservation.- Surfaces, cleaned and dried as specified, shall be coated with type P-2 preservative of MIL-P-116.

* 5.1.1.2.3 Protection of preservative.- Surfaces, from which preservative might be removed by contact with packaging and packing materials, shall be covered, wrapped, or bagged with greaseproof barrier material conforming to type I or II, grade A of MIL-B-121. Barrier material shall be secured with twine made of jute, sisal, manila, or cotton, or with tape conforming to type III, grade A of PPP-T-45, or heat sealed when heat-sealable barrier material is used.

5.1.1.3 Packaging.-

5.1.1.3.1 Securing of components.- Components of each drilling machine that are free to move, shall be secured in such a manner as to prevent movement while in transit.

5.1.1.3.2 Detached components, tools and accessories.- Detached components, tools, and accessories shall be cushioned and packaged in a snug-fitting paperboard, fiberboard, or nailed wood box or boxes. Each paperboard or fiberboard box shall be secured to the machine.

5.1.1.3.3 Equipment manual.- Each equipment manual shall be prepared method IC-1 of MIL-P-116 and secured to the machine or packaged in the same box as the detached components, tools, and accessories.

* 5.1.2 Level C.- Drilling machines shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A.- Each drilling machine, preserved and packaged as specified in 5.1, shall be packed in a cleated plywood or nailed wood shipping container conforming to overseas type, type 3 load of PPP-B-601, or class 2, style 2 or 4, type 3 load of PPP-B-621. Each shipping container shall be provided with skids in accordance with the applicable container specification. The machine shall be secured by bolting to the base of the container with bolts engaging skids. Additional lumber blocking and bracing shall be used as necessary, to immobilize the drilling machine within the shipping container. The blocking

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

and bracing shall not depend on end-grain nailing alone, but supplemental supporting cleats shall be provided to reinforce and prevent splitting of the blocking and bracing. Nailed wood containers for detached components, tools, and accessories, when used (see 5.1.1.3.2), shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547 and secured in an unused portion of the shipping container. The drilling machine shall be covered with a full-height shroud made of waterproof barrier material conforming to class E-2, H-1, H-5, or M of UU-P-271. All seams of the shroud shall be sealed with a 3/4-inch minimum width continuous seam of water-resistant adhesive, conforming to MMM-A-260. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

* 5.2.2 Level B.- Each drilling machine, preserved and packaged as specified in 5.1, shall be packed as specified in 5.2.1, except that shipping containers shall conform to domestic type, style A or B of PPP-B-601, or class 1, style 2 or 4, type 3 load of PPP-B-621, and case liner and shroud shall not be required.

5.2.3 Level C.- Drilling machines, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The machines are intended for use in print shops and binderies for drilling holes in lifts of printed materials for subsequent retention in ring binders.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Style machine required (see 1.2).
(c) First article.- When a preproduction sample is required (see 3.1).
(d) Power source characteristics, if other than specified (see 3.4.3).
(e) When fungus resistance treatment is required (see 3.4.3.1).
(f) When electromagnetic compatibility is not required (see 3.4.3.2).
(g) Technical publications, repair parts, and tools required (see 3.9).
(h) Applicable levels of preservation, packaging, and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

6.3 Electromagnetic compatibility.- When applicable, the contracting officer should submit a copy of the Interference Control Plan, the EMI/EMC Test Plan, and the test report required (see 4.4.1) to the Commanding General, U. S. Army Electronics Command, ATTN: AMSEL-RD-GF, Fort Monmouth, New Jersey 07703, for approval.

* 6.4 Supersession.- The style 1 drilling machine covered herein is identical to the item formerly covered by MIL-D-16712B(GL).

6.5 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 3610-A152

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
Drilling Machines, Paper, Electric Motor Driven MIL-D-16712C(GL)

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:19Z
Check the source to verify that this is the current version before use.