MILITARY SPECIFICATION SHEET

BEARING, PLAIN, ROD END, SELF-ALIGNING, SELF-LUBRICATING, NARROW, EXTERNALLY THREADED, -65°F to +325°F

This amendment forms a part of MIL-B-81935/4A, dated 24 June 1983 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Under the heading "Part number," delete and substitute the following:

"Part number: The part number consists of the letter M, the basic number of this specification sheet, followed by a two digit dash number from table I, followed by an alpha code letter 'K' for a keyway (no code when a keyway is not desired) and an alpha code letter 'L' to designate a left handed thread (no 'L' code would designate right handed threads)

Example:

M81935/4-04KL

- L — Left handed Thread direction designator
- K — Keyway designator
- 04 — Dash number citing the bore nominal diameter code
- M81935/4 — Military specification number

Custodians:
Navy - AS
Air Force - 11
Army - AV

Reviewer activities:
Navy - SH
Air Force - 99
Army - AR, AT, MI
DLA - IS

User activity:
Navy - SH

Preparing Activity:
Navy - AS
(Project 3120-0711-03)

AMSC N/A

FSC 3120

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.