MILITARY SPECIFICATION

CARTRIDGE, 105MM, HE, ROCKET ASSISTED, XM548, BODY, MOTOR FOR

This amendment forms a part of Military Specification MIL-C-60457 (MU), dated 27 October 1967, and is approved for use by the U.S. Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and agencies of the Department of Defense."

Delete "XM548" and substitute "XM548E1" wherever referenced in the specification.

PAGE 3

3.3.2, Line 6: Delete "The rotating band shall make contact with the side walls of the band seat for a full 360 degrees and a minimum of 50 percent of the side wall area." and substitute "Voids in the area of the band seat projections will be permitted as specified on dwg. 9212398."

3.3.3: Delete in its entirety.

PAGE 5

3.8: Delete in its entirety.

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

PAGE 8

4.3.1, Last line: Delete "and not more than one lot of rotating band blanks." and substitute "and rotating band blanks from not more than one interfix lot from one manufacturer."

PAGE 14

4.3.3.1.1, Line 3: Delete "If either of the sample motor bodies fail to meet the requirements of 3.3.2...." and substitute "If either of the sample motor bodies fail to meet the tightness requirements specified on dwg. 9212398...."

4.3.3.1.2, Line 4: Delete "If the density of either specimen exceeds the requirement of 3.3.3...." and substitute "If the density of either specimen exceeds the density requirement specified on dwg. 9212398...."

PAGE 15

4.3.3.2.1.1, Line 2 and 4: Delete "serialized" and substitute "identified."

PAGE 17

4.4.1.1: Delete in its entirety and substitute the following:

"4.4.1.1 Band tightness (see 3.3.2 and dwg. 9212398) - Four 90 degree segments shall be cut from the open end of the motor body. A specimen approximately 1 1/4 inch long shall be cut from each segment and examined for band tightness. Each specimen shall be brush cleaned and examined using approved optical test equipment."

4.4.3.1: Delete in its entirety and substitute the following:

"4.4.3.1 Security - The motor bodies supplied in accordance with 4.3.3.2.4.1 shall be inert loaded and assembled to an inert warhead and an inert fuze. The paint shall be removed from the outside diameter and measurements taken in two locations; one measurement 90 degrees from the other. The locations of the measurements shall be marked

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

prior to firing for identification upon recovery of the projectile. The inert loaded projectile shall be fired in an M103 or M137 cannon using a propellant adjusted to produce 40,000 psi chamber pressure. The motor bodies shall be recovered and remeasured in the same locations as the initial measurement. Any change in either dimension exceeding 0.003 inch will be considered as deformation."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1315-A443

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.