METRIC


MIL-DTL-55302/159D
8 July 2004
SUPERSEDING
MIL-C-55302/159C(CR)
17 March 1995

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, 17, 29, 33, 41, 53, AND 65 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS, 2.54 MM X 1.27 MM OFFSET GRID, METRIC

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.



NOTE: Dimensions are in millimeters.

FIGURE 1. Connector receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

RECEPTACLE TERMINAL STYLES




FIGURE 2. Connector termination styles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

RECEPTACLE TERMINAL STYLES
















REF	MALE CONTACTS	REF	FEMALE CONTACTS
A	STRAIGHT DIP SOLDER 	D	STRAIGHT DIP SOLDER 
T	STRAIGHT DIP SOLDER  1.6 (.064 IN.) P.C. BOARD	U	STRAIGHT DIP SOLDER  1.6 (.064 IN.) P.C. BOARD
N	STRAIGHT DIP SOLDER  2.4 (.094 IN.) P.C. BOARD	Z	STRAIGHT DIP SOLDER  2.4 (.094 IN.) P.C. BOARD
V	STRAIGHT DIP SOLDER  3.2 (.125 IN.) P.C. BOARD	W	STRAIGHT DIP SOLDER  3.2 (.125 IN.) P.C. BOARD

FIGURE 2. Connector termination styles – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

RECEPTACLE TERMINAL STYLES


REF MALE CONTACTS	REF FEMALE CONTACTS
S SOLDER CUP  FOR UP TO 22 AWG.	L SOLDER CUP  FOR UP TO 22 AWG.
M DOUBLE CRIMP  FOR 22,24 AND 26 AWG.	H DOUBLE CRIMP  FOR 22,24 AND 26 AWG.
R CRIMP  FOR 22,24 AND 26 AWG.	K CRIMP  FOR 22,24 AND 26 AWG.
	Y WRAP POST 

NOTE: Dimensions are in millimeters.

FIGURE 2. Connector termination styles – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

RECEPTACLE MOUNTING STYLES



NOTE: Dimensions are in millimeters.

FIGURE 3. Mounting styles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

RECEPTACLE LOCKING HARDWARE




FIGURE 4. Locking hardware.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in millimeters.
2. This is a metric design.
3. Unless otherwise specified, tolerance is ± 0.10 millimeter.
4. These connectors mate with MIL-DTL-55302/162.
5. See table II for mating.
6. Contact identification may be located adjacent to cavity on face or side and may be rotated 180°.
7. Crimp contacts are shipped not inserted into insulator.
8. Use crimp tool M22520/2-01 for R and K terminal styles with Daniels manufacturing positioner K547.
9. Use crimp tool M22520/2-01 for M and H terminal styles with Daniels manufacturing positioner K547 and K640.

FIGURE 4. Locking hardware – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.




FIGURE 5. Mounting dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.





FIGURE 5. Mounting dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in millimeters.
2. Tolerances are noncumulative.

FIGURE 5. Mounting dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

TABLE I. Number of contacts.

Number of contacts	Dimension (in millimeters)	
	A	B
17	30.50	38.50
29	45.70	53.70
33	50.80	58.80
41	60.90	58.90
53	76.20	84.20
65	91.40	99.40

TABLE II. Mating references.

Type	Will only mate with (see note)	Locking method
B	P, U, W	None
F	J, K	Push 1/4 turn
G	J, K	Push 1/4 turn
J	F, G	Push 1/4 turn
P	B, T, V	None
T	P, U, W	None
U	B, T, V	None
V	P, U, W	None
W	B, T, V	None
X	Z	Screw
Z	X, Y	Screw

NOTE: These connectors mate with MIL-DTL-55302/162.

TABLE III. Mounting references.

Number of contacts	A
17	30.50
29	45.70
33	50.80
41	60.90
53	76.20
65	91.40

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction:

Dimensions and configuration: See figures 1 through 5 and tables I, II and III.

Material:

Insulators: Diallyl phthalate in accordance with ASTM D5948.

Guides and hardware: Brass in accordance with ASTM B36, B16, B124, B453, or B455; nickel plated in accordance with SAE-AMS-QQ-N-290 or AISI 300 series stainless steel or equivalent in accordance with ASTM A582, passivated in accordance with SAE-AMS-QQ-P-35.

Plating: Plating in accordance with MIL-DTL-55302 or as noted.

Mating surface (pin and wire): Gold in accordance with ASTM B488, class 1.27, type II, code C over nickel in accordance with SAE-AMS-QQ-N-290, 30-150 microinches.

Terminations: Solderable areas (including crimp barrels and wire wrap terminations) shall be gold in accordance with ASTM B488, type III, code A, class 0.254 minimum thickness or gold in accordance with ASTM B488, type II, code C, class 0.51 over nickel in accordance with SAE-AMS-QQ-N-290, 30 to 150 microinches thick. Solderable areas must meet the requirements of MIL-STD-202, method 208.

All other surfaces: Gold in accordance with ASTM B488, type II, code C, class 0.127 minimum over nickel in accordance with SAE-AMS-QQ-N-290, 30-150 microinches.

Contact identification: See figure 1.

Contact separation forces:

Minimum force: 0.14 newton (0.50 ounce) with a 0.5800 millimeter (.0228 inch) +0.005, -0.00 diameter pin after being cycled 3 times.

Note: Steel pin test surface roughness to be 0.025 – 0.25 micron rms.

Unmating: The maximum force of a connector assembly shall not exceed 0.53 newton (1.90 ounces) multiplied by the number of contact positions.

Mating: The maximum force of a connector assembly shall not exceed 0.70 newton (2.5 ounces) multiplied by the number of contact positions.

Contact retention minimum: Functional value 22.2 newtons (5 pounds); destructive test 35.3 newtons (8 pounds) maximum design and qualification value.

Contact rating: 5 amperes per line.

Durability: 2,000 cycles minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage:

Sea level: 1,400 V ac rms test.

High altitude: 300 V ac rms test.

Keying: Rotation of guides, 6 positions each, 36 possible combinations.

Connector Part or Identifying Number (PIN):

Example: D55302/ 159 D 65 B

Specification number

Specification sheet number

Type of contact and termination
(see figures 1 and 2)

Number of contacts
(see table I)

Guide hardware number
(see figures 3, 4, 5 and tables II and III)

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/162	ASTM B36	ASTM B488
MIL-STD-202	ASTM B124	ASTM D5948
ASTM A582	ASTM B453	SAE-AMS-QQ-N-290
ASTM B16	ASTM B455	SAE-AMS-QQ-P-35

CONCLUDING MATERIAL

Custodians:
Army - CR
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4605-001)

Review activities:
Army - AR, AT, AV, CR4, MI

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsible can change, you should verify the currency of the information above using the ASSIST Online database at http://www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.