
MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, 120, 150, 160, AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-55302.



Ⓒ STYLE I (INTERNAL KEYING)

FIGURE 1. Connectors, receptacle, (.075 spacing).

Ⓒ denotes changes

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Dash 1/ number	No. of contacts	Type	A	B	C	D	E	Contact identification numbers
01 02 03 04	120	I II III IV	5.380 (136.65)	5.090 (129.29)	59	4.425 (112.40)	4.690 (119.13)	1 - 60 61 - 120
05 06 07 08	150	I II III IV	6.505 (165.23)	6.215 (157.86)	74	5.550 (140.97)	5.815 (147.70)	1 - 75 76 - 150
09 10 11 12	160	I II III IV	6.880 (174.75)	6.590 (167.39)	79	5.925 (150.50)	6.190 (157.23)	1 - 80 81 - 160
13 14 15 16	180	I II III IV	7.630 (193.80)	7.340 (186.44)	89	6.675 (169.55)	6.940 (176.28)	1 - 90 91 - 180

1/ Dash numbers 01 thru 16 are for style 1 (internal keying) connectors.

FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.



© FIGURE 1. Connectors, receptacle (.075 spacing). - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

©

Dash 1/ number	No. of contacts	Type	A	B	C	D	E	Contact identification numbers
17 18 19 20	120	I II III IV	5.380 (136.65)	5.090 (129.29)	59	4.425 (112.40)	4.690 (119.13)	1 - 60 61 - 120
21 22 23 24	150	I II III IV	6.505 (165.23)	6.215 (157.86)	74	5.550 (140.97)	5.815 (147.70)	1 - 75 76 - 150
25 26 27 28	160	I II III IV	6.880 (174.75)	6.590 (167.39)	79	5.925 (150.50)	6.190 (157.23)	1 - 80 81 - 160
29 30 31 32	180	I II III IV	7.630 (193.80)	7.340 (186.44)	89	6.675 (169.55)	6.940 (176.28)	1 - 90 91 - 180

1/ Dash numbers 17 thru 32 are for style 2 (external keying) connectors.

© FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

INCHES	MM	INCHES	MM
.003	.08	.087	2.21
.004	.10	.096	2.44
.005	.13	.101	2.57
.006	.15	.108	2.74
.010	.25	.109	2.77
.012	.30	.113	2.87
.014	.36	.125	3.18
.015	.38	.130	3.30
.018	.46	.135	3.43
.019	.48	.136	3.45
.020	.51	.140	3.56
.022	.56	.171	4.34
.025	.64	.175	4.44
.027	.69	.176	4.47
.028	.71	.180	4.57 ©
.030	.76	.185	4.70
.031	.79	.200	5.08
.032	.81	.235	5.97
.040	1.02	.242	6.15
.045	1.14	.248	6.30
.050	1.27	.250	6.35
.0625	1.588	.255	6.48
.063	1.60	.260	6.60
.065	1.65	.298	7.57
.067	1.70	.300	7.62
.073	1.85	.305	7.75
.075	1.90	.315	8.00
.080	2.03	.330	8.38
.081	2.06	.332	8.43
.083	2.11	.340	8.64
.085	2.16	.400	10.16

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.005 (.13 mm) on decimals and ±2° on angles.
4. These connectors mate with connectors specified in MIL-C-55302/23.
5. Use printed circuit boards with the Type III receptacle.
6. Minimum pad length on printed circuit board.
7. Termination layout on .025 (.64 mm) modular grid.
8. Numbers indicating, every five cavities stamped on side. Numbers indicating end cavities and lines indicating every five cavities stamped on mating face.
© 9. Location indicators embossed on surface.

FIGURE 1. Connectors, receptacle, (.075 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Material:
Plating: The contact plating shall be gold per MIL-G-45204, type II, grade C, class 1, over nickel per QQ-N-290, class 2, 30 to 150 microinches.

Contact identification: See figure 1.

Contact rating: 3.0 amperes maximum per contact, 2.25 amperes continuous per connector at room ambient.

Keying: See MIL-C-55302/31.

Oversized pin exclusion (sockets only): .0465 diameter pin.

Contact separation force: The connector shall meet the requirements of MIL-C-55302/29.

Wire size: No. 26 AWG maximum with type II, solder eyelet contact for wire termination.

Resistance to test probe damage: The connector shall meet the requirements of MIL-C-55302/30.

Mating and unmating: The maximum mating force in pounds shall be the number of contacts multiplied by .25 and the withdrawal force in pounds shall be a minimum of .025 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: The average contact resistance of all contacts measured shall not exceed .015 ohm, and no individual contact pair shall have a resistance exceeding .020 ohm.

Contact retention: 3 pounds minimum.

Dielectric withstanding voltage:
Sea level: 900 volts rms.
High altitude: 200 volts rms.

Replacement contacts: See MIL-C-55302/32.

Contact removal tool: See MIL-C-55302/28.

Part number: M55302/25- (dash number from figure 1).

Patent number 3,404,367. The Government has a royalty free license under this patent for the benefit of manufacturers of the item either for the Government or for use in equipment to be delivered to the Government.

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - CR, AR, MI
Navy - SH, AS, OS
Air Force - 11, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3115-6)

☆U.S. GOVERNMENT PRINTING OFFICE: 1980 — 603-121/1949

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-55302/25C

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

HQ, USA CORADCOM
ATTN: DRDCO-CM-DM
Fort Monmouth, NJ 07703

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

FOLD

HQ, USA CORADCOM
ATTN: DRDCO-CM-DM
Fort Monmouth, NJ 07703

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID



HQ, USA CORADCOM
ATTN: DRDCO-CM-DM
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.