INCH-POUND

MIL-G-70464 (AR)
AMENDMENT 1
21 August 1991

MILITARY SPECIFICATION

GRENADE (GP), LINER FOR

This amendment forms a part of Military Specification MIL-G-70464(AR), dated 21 November 1985, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1 Military Specifications, Add:

"MIL-A-70625 - Automated Acceptance Inspection Equipment for Non-Electronic Components, Design, Testing and approval of"

PAGE 6

4.4.2.1 Delete table in its entirety and substitute new table (see included table).

PAGE 9

4.4.3.2 Add new paragraph.

"4.4.3.2 Dimensional control of parts - In place of normal sampling associated with the classification of defects, a qualification sample of at least ten parts shall be inspected for verification of dimensional conformance in order to qualify each machine prior to production and after each production stoppage of more than one hour. Upon qualification, one process sample shall be selected per 600 parts produced and at the end of a shift.

4.4.3.2.1 Qualification of machine - If any defective parts are found during qualification of the machine, the machine producing the defective part shall not be used in production.

4.4.3.2.2 Process sample - If any defective part is found when inspection is performed on the process sample, the machine that produced the defective part shall be removed from production. Further, that portion of production since the last process sample shall be rejected.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

4.4.3.2.3 Adjustment or rework of production machines - All machines removed from production because of some fault may, after adjustment or rework, be returned to production provided they pass the qualification test above.

4.4.3.2.4 Statistical Process Control (SPC) Plan - The alternate sampling plan shall be used only with the implementation of a procuring agency approved Statistical Process Control (SPC) Plan. See 6.5. The SPC plan shall record and monitor variable data. The data that are gathered from the acceptance sample may be used in the SPC data base."

4.4.4 Insert as the next to last sentence: "When Automated Acceptance Inspection Equipment is to be used, the provisions of MIL-A-70625 shall apply."

4.5.1, line 5 , after "equivalent equipment. "Add: "Equipment used shall provide a hardcopy trace of the profile."

Add new paragraph 4.5.2 and 4.5.3

"4.5.2 Wall thickness. The samples selected for this test shall be inspected:

a. Along one continuous longitudinal element between datums A and B.

b. Along one continuous circumferential element (360^{c}) at a random location between datums A and B.

c. Along one continuous circumferential element (360^{c}) at a random location between datums A and C.

d. At one location through the apex.

e. At one location through the skirt.

4.5.3 Wall thickness variation. The samples selected for this test shall be inspected along one continuous circumferential element (360^{c}) at random location between datums A and B and along another continuous circumferential element (360^{c}) at a random location between datums A and C. These inspections will be performed at the same locations where the wall thickness is inspected per paragraph 4.5.2b-c."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Grenade Liner				9345266
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter	(b)	0.40%	3.2	Gage
102	Length to smaller basic diameter	(b)	0.40%	3.2	Gage
103	Distance between basic diameters	(b)	0.40%	3.2	Gage
104	Length to largest basic diameter	(b)	0.40%	3.2	Gage
105	Total length	(b)	0.40%	3.2	Gage
106	Wall thickness.	(b)	0.40%	3.2	4.5.2
107	Wall thickness variation	(b)	0.40%	3.2	4.5.3
108	Runout skirt diameter	(b)	0.40%	3.2	Gage
109	Part cracked or dented	(b)	0.40%	3.2	Visual
110	Outside surface profile, surface variation and protuberances	(a)		3.2	4.5.1
111	Skirt straightness	(c)		3.2	Gage
Minor					
201	Radius between outside diameter and junction with conical surface	(b)	0.65%	3.2	Gage
202	Finish improper (stain or unusual discoloration)	(b)	0.65%	3.2	Visual
203	Evidence of poor workmanship	(b)	0.65%	3.4	Visual

NOTES:
(a) Sampling per para 4.4.3.1
(b) In lieu of sampling by MIL-STD-105, alternative sampling per 4.4.3.2 may be used.
(c) One per machine per hour.

(9) 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

6.3 line 3-4, Change: "Armament Research and Development Center (ARDC), ATTN: DRSMC-QAR-I(D), Dover, NJ 07801"

To: "Armament Research, Development and Engineering Center (ARDEC), ATTN: AMSMC-QAR-I(D), Picatinny Arsenal, NJ 07806-5000."

6.4 lines 2-3, Change: "Armament Research and Development Center (ARDC)"

To: "Armament Research, Development and Engineering Center (ARDEC)"

line 6, Change" "ARDC" to: "ARDEC"

Add new paragraphs: 6.5 and 6.6

"6.5 Submission of SPC plan. The SPC plan should be submitted to the procuring agency for review. Guidance for preparing the SPC plan is outlined in Statistical Process Control Plans, Preparation and Evaluations, ARDEC, dated 4 April 1986. Copies may be obtained through the procuring agency.

"6.6 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract.

Reference Paragraph	DID Number
4.4.3.2	DI-NDTI-80809A

DID Title	Suggested Tailoring
Test/Inspection Reports	Tailoring as appropriate"

Custodian
Army - AR

Preparing activity:
Army - AR

(Project 1330-A366)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.