INCH-POUND

MIL-W-64044 (AR)
AMENDMENT 6
16 February 1990
SUPERSEDING
AMENDMENT 5
10 OCTOBER 1985

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, M261 AND M267, PARTS FOR

This amendment forms a part of Military Specification MIL-W-64044 (AR), dated 7 October 1983, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Add to Product Drawings, "9334152 Obturator Support Assy".

3.2, Add to list of drawing "9334152".

PAGE 4

4.3.1, Add to Table:

	"O-ring	9334139	10
	O-ring	9334114	10
	Obturator Support, Split	9334154	15 or 5/cavity whichever is greater
	Obturator Support Assy	9334152	25
*	Ring, Retaining, Auto Jettison #9 Grenade (M261 only)	12561495	15
*	Ring, Retaining, Auto Jettison (M261 only)	12561496	15
*	O-ring, Cargo Retaining M261 only)	12561497	15"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:12Z
Check the source to verify that this is the current version before use.

PAGE 7

Table I: Add:

"Obturator Support, Split (Dwg. 9334154) Examination for defects	15(a)	3.2	4.4.2.14
Obturator Support Assy (Dwg. 9334152) Examination for defects	25	3.2	4.4.2.15
O-ring (Dwg. 9334139) Examination for defects	10	3.2	Gage
O-ring (Dwg. 9334114) Examination for defects	10	3.2	Gage"

PAGE 10

* 4.4.2.2, Major 101: Change "largest outside diameter" to "second largest diameter".

Major 103, Delete "Center" and substitute "blow-through".

Minor 202, Delete "in its entirety.

* Add Minor 206: "206 Largest Outside Diameter .65% 3.2 Gage"

PAGE 17

4.4.2.9, Minor 201: Delete in its entirety.

Minor 202: Delete in its entirety.

PAGE 20

4.4.2.12, Add Major 111 and Minor 210 respectively:

"111	Surface finish (Note 8)	0.40%	3.2	Gage/Visual
* 210	Stake height	0.65%	3.2	Gage"

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

PAGE 21

4.4.2.13, Add Major 102:

"102 Continuity (cable) 100% 3.2 milliohmeter"

Minor 201, Delete in its entirety.

Minor 202, Delete in its entirety.

Add 4.4.2.14, included PAGE (21a).

Add 4.4.2.15, included PAGE (21b).

Add 4.4.2.16, included PAGE (21c).

Add 4.4.2.17, included PAGE (21d).

* Add 4.4.2.18, included PAGE (21e).

* Add 4.4.2.19, included PAGE (21f).

* Add 4.4.2.20, included PAGE (21g).

PAGE 23

6.3, Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: AMSMC-QAF-I(D)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Obturator Support, Split	6 of 1	9334154
			NEXT HIGHER ASSEMBLY 9334152

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Smaller inside diameter		0.40%	3.2	Gage
103	Larger inside diameter		0.40%	3.2	Gage
104	Depth		0.40%	3.2	Gage
105	Split width, max.		0.40%	3.2	Gage
106	Mold inspection	5/cavity			
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

REMARKS

Source: https://assist.dla.mil -- Downloaded: 2026-03-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Obturator Support Assembly		9334152
			NEXT HIGHER ASSEMBLY 9334122

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Tape missing or improperly located		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

5 (21b)

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9334139
4.4.2.16	O-ring				NEXT HIGHER ASSEMBLY 9334148 or 9334097
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Cross section diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.17	O-ring				9334114
					NEXT HIGHER ASSEMBLY
					9334123 or 9334122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Cross section diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z. Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Ring, Retaining, Auto Jettison-#9 Grenade				12561495
					NEXT HIGHER ASSEMBLY 9334122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Thickness-top surface		0.40%	3.2	SMI*/Gage
102	Color code		0.40%	3.2	Visual
Minor					
201	Largest inside diameter		0.65%	3.2	SMI*/Gage
202	Thickness-side		0.65%	3.2	SMI*/Gage
203	Center of hole to largest inside diameter		0.65%	3.2	SMI*/Gage
204	Spring tab height		0.65%	3.2	SMI*/Gage
205	Width of notch		0.65%	3.2	SMI*/Gage
206	Location of notch		0.65%	3.2	SMI*/Optical Comparator
207	Dimple height		0.65%	3.2	SMI*/Gage
208	Evidence of poor workmanship		0.65%	3.4	Visual

REMARKS:
* Standard Measuring Instrument

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Ring, Retaining, Auto Jettison	SHEET 1 OF 1	12561496
			NEXT HIGHER ASSEMBLY 9334122

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Thickness-top surface		0.40%	3.2	SMI*/Gage
Minor					
201	Largest inside diameter		0.65%	3.2	SMI*/Gage
202	Thickness-side		0.65%	3.2	SMI*/Gage
203	Center of hole to largest inside diameter		0.65%	3.2	SMI*/Gage
204	Spring tab height		0.65%	3.2	SMI*/Gage
205	Width of notch		0.65%	3.2	SMI*/Gage
206	Location of notch		0.65%	3.2	SMI*/Optical Comparator
207	Evidence of poor workmanship		0.65%	3.4	Visual

REMARKS

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12561497
4.4.2.20	O-ring, Cargo Retaining				NEXT HIGHER ASSEMBLY 9334122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
Major					
101	Inside diameter		0.40%	3.2	SMI*/Gage
102	Cross section diameter		0.40%	3.2	SMI*/Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

REMARKS

* Standard Measurement Instrument

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A773)

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.