

TABLE I. DASH NUMBERS.

DASH NO	A NOMINAL SIZE INCHES	B NOMINAL SIZE INCHES	C NOMINAL SIZE FEET	HEAT TREATMENT	FORMING 1/ PROCESS	ADDITIONAL 2/ REQUIREMENTS
001	.0150	48	12	ANNEALED	C	do
003	.0160	24	8	ANNEALED	C	do
005	.0200	24	8	ANNEALED	C	do
007	.0250	24	8	ANNEALED	C	do
009	.0320	24	8	ANNEALED	C	do
011	.0320	36	10	ANNEALED	C	do
013	.0360	24	8	ANNEALED	C	do
015	.0380	36	8	ANNEALED	H	
017	.0500	24	8	ANNEALED	C	do
019	.0500	36	10	ANNEALED	C	do
021	.0630	24	8	ANNEALED	C	do
023	.0630	36	10	ANNEALED	C	do
025	.0900	24	8	ANNEALED	C	do
027	.0907	48	12	ANNEALED	H	
029	.1000	36	8	ANNEALED	H	
031	.1090	48	12	ANNEALED	H	
033	.1250	24	8	ANNEALED	C	do
035	.1250	36	10	ANNEALED	C	do
037	.1406	36	8	ANNEALED	H	

1/ SEE REQUIREMENT 2
2/ SEE REQUIREMENT 3

APPROVED 28 FEB 1985 REVISED

USER ACTIVITIES:
REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
AS Other Cust MR 99		SHEET, METAL, CORROSION RESISTANT, TYPE 410	MS14464
PROCUREMENT SPECIFICATION QQ-S-766	SUPERSEDES:		PAGE 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:44Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL. STEEL, CORROSION RESISTANT, TYPE 410 (UNS S41000) AS SPECIFIED IN PROCUREMENT DOCUMENT.

2. FORMING PROCESS. COLD FINISHED - CODE "C"
HOT FINISHED - CODE "H"

3. ADDITIONAL REQUIREMENTS.

POLISHED	OVERALL - CODE	"p"
POLISHED	ONE SIDE - CODE	"p (1)"
DULL	OVERALL - CODE	"do"
BRIGHT	OVERALL - CODE	"bo"
DESCALED	OVERALL - CODE	"ds"
PICKLED	OVERALL - CODE	"po"

4. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14464C001

- (SEE TABLE I)
- COLD FINISHED (SEE REQUIREMENT 2)
- BASIC MS NUMBER

5. MARKING. IRON AND STEEL PRODUCTS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

2. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 28 FEB 1985 REVISED

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
AS		SHEET, METAL, CORROSION RESISTANT, TYPE 410	MS14464
Other Cust MR 99			
PROCUREMENT SPECIFICATION QQ-S-766	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:44Z
Check the source to verify that this is the current version before use.