FEDERAL SPECIFICATION

CLOTH, DUCK, COTTON, UNBLEACHED, PLIED-YARNS

ARMY AND NUMBERED

This amendment, which forms part of Federal Specification CCC-C-419E, dated April 27, 1977, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGES 3 and 4

Tables 1 and 2: Delete and substitute

Source: https://assist.dla.mil -- Downloaded: 2026-10-27 12:27
Check the source to verify that this is the current version before use.

"TABLE I. Physical and mechanical requirements for type I, numbered ducks

Number of duck, commercial designation	Weight				Breaking strength				Air permeability	
	Oz/Yd^2		G/M^2		Warp		Filling			
	(Min)	(Max)	(Min)	(Max)	Pounds (Min)	Newton (Min)	Pounds (Min)	Newton (Min)	$Ft^3/min/Ft^2$) (Max)	$Cm^3/Sec/C$. (Max)
1 1/	28.7	31.6	973	1071	440	1958	370	1647	2.0	1.02
2 1/	27.1	29.8	919	1010	420	1869	345	1535	2.0	1.02
4 1/	23.9	26.3	811	892	375	1669	300	1335	2.0	1.02
6 1/	20.7	22.8	703	773	335	1491	250	1113	2.0	1.02
8 1/	17.6	19.4	595	658	285	1268	210	935	2.0	1.02
10 2/	14.4	15.8	486	536	245	1090	160	712	4.0	2.03
12 2/	11.2	13.0	378	441	195	868	120	534	4.0	2.03

1/ Plied yarns shall be used for both warp and filling.

2/ Warp yarns shall be plied; filling yarns shall be singles or plied.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T12:29Z
Check the source to verify that this is the current version before use.

Table II. Physical and mechanical requirements for type III, army duck 1/

Weight				Breaking strength				Tearing strength				Air permeability	
				Warp		Filling		Warp		Filling			
Oz/Yd^2		G/M^2		Pounds	Newton	Pounds	Newton	Pounds	Newton	Pounds	Newton	$Ft^3/(Min\text{-}Ft^2)$	$Cm^3/Sec/Cm^2$
(Min)	(Max)	(Min)	(Max)	(Min)	(Min)	(Min)	(Min)	(Min)	(Min)	(Min)	(Min)	(Max)	(Max)
8.25	9.25	280	314	125	556	120	534	4.0	18	3.0	13	4.0	2.03
9.85	11.0	334	373	160	712	110	490	-	-	-	-	4.0	2.03
12.30	13.50	417	458	210	935	130	579	-	-	-	-	4.0	2.03
14.80	16.30	501	553	235	1046	175	779	-	-	-	-	-	-
18.50	20.40	626	692	315	1402	200	890	-	-	-	-	-	-

1/ The warp yarns shall be plied and the filling yarns shall be singles or plied."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:29Z
Check the source to verify that this is the current version before use.

3.2.1 Delete first sentence and substitute: "The width of the cloth shall be as specified (see 6.2). The minimum acceptable width shall be inclusive of the woven selvage when fly-shuttle looms are used or when a tuck-in selvage is used on shuttleless looms and exclusive of the lock-in fringed selvage when a shuttleless lino lock-in fringed selvage is used. Cut raw edges shall not be permitted."

3.2.2 Add new sentence: "The use of a fly-shuttle or a shuttleless loom is permitted."

MILITARY INTERESTS:

Custodians

Army - GL
Navy - NU
Air Force - 11

Review Activities

Army - MD, MI, AR, EA, CR
Navy - MC
Air Force - 99
DLA-CT

User Activities

Army - AT, ME
Navy - YD

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 8305-0651

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:29Z
Check the source to verify that this is the current version before use.