AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, RIGHT ANGLE

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, D.C. 20406, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification W-F-001316(GSA-FSS), dated March 25, 1968.

PAGE 3

Paragraph 3.2.3.3, first sentence, delete the wording "magenta No. 17142". and replace with "black and the lens cap, end cap and any exposed plastic switch parts shall be yellow obtained without the use of paint, enamel, or any other post molding application".

Paragraph 3.2.4, first sentence delete the small "c" in the wording "style B and c" and replace with a capital "C" so that wording becomes "style B and C".

Paragraph 3.3.2.1, delete paragraph in its entirety and replace with the following:

"3.3.2.1 Storage compartment. The class 3 flashlight shall have a storage compartment provided in the end caps or other accessible area of the flashlight for storage of a lens and spare lamp. The storage compartment shall be so designed that lens and lamp are readily accessible, fit securely in the compartment, and will not become broken or displaced when the flashlight is subjected to the tests specified in section 4."

Paragraph 3.3.3, first and second sentences. In the first sentence delete the wording "25 inch pounds" and replace with "30 pound inches". In the second sentence delete the wording "75 inch pounds" and replace with "50 pound inches".

PAGE 4

Paragraph 3.3.7, fifth sentence, delete the number "35,000" and replace with "25,000". Also, delete the wording "15 cycles" and replace with "15 to 20 cycles".

Paragraph 3.3.9, first and third sentences. In the first sentence delete the words "can not" and replace with "cannot". Also, delete the third sentence in its entirety and replace with the following: "The suspension ring shall be capable of supporting, without distortion, a weight of 25 pounds".

PAGE 5

Paragraphs 4.1.1, 4.2, 4.2.1, 4.2.2 and 4.3, delete in entirety and replace with the following:

"4.1.1 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction or beginning of contractual year inspection (see 4.2).

(b) Quality conformance inspection (see 4.3).

(c) Inspecition of preparation for delivery (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

"4.2 Preproduction or beginning of contractual year inspection. This inspection shall be accomplished before production of flashlights is commenced or at the beginning of each contractual year and shall consist of an examination as specified in 4.2.1 and tests as specified in 4.2.2.

4.2.1 Examination. Five sample flashlights of each type, style, and class to be supplied under this specification shall be examined to determine compliance with all requirements of section 3 above that do not require a specific section 4 test. Presence of one or more defects shall be cause for rejection.

4.2.2 Tests. Following successful completion of the examination specified in 4.2.1 above, the five samples shall be subjected to all applicable tests specified in 4.4. Failure of any test shall be cause for rejection. Unless otherwise specified, all tests shall be conducted at room temperature, pressure, and humidity.

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105. For purposes of inspection the test lot shall consist of all flashlights of a particular type, style and class presented for inspection at one time. The sample unit shall be one flashlight.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as cited in 4.2.1 above. The inspection level shall be level S-4 and the Acceptable Quality Level (AQL) shall be 2.5, expressed in terms of percent defective.

4.3.3 Tests. Samples selected in accordance with 4.3.1 shall be subjected to all applicable tests specified in 4.4.1, 4.4.3, 4.4.4, 4.4.5, 4.4.6, 4.4.7, 4.4.8, 4.4.9, 4.4.10, 4.4.12 and 4.4.13. The inspection level shall be level S-3 and the AQL shall be 2.5, expressed in terms of percent defective. Unless otherwise specified, tests shall be conducted at room temperature, pressure, and humidity."

Paragraph 4.4.2, second sentence, delete the wording "90 percent" and replace with "85 percent $\pm$ 5 percent".

Paragraph 4.4.3, first and second sentences. Revise the first sentence to read as follows: "Flashlights shall be subjected to a temperature of minus 40°F $\pm$ 5°F." Also, delete the second sentence in its entirety.

Paragraph 4.4.4, third sentence, delete in its entirety and replace with the following:

"Each flashlight shall be dropped so that it strikes 10 times in a horizontal position, 10 times in a vertical position upon the head of the flashlight and 10 times in a vertical position upon the base of the flashlight. Tightening of threaded parts shall not be made once testing has started."

Paragraph 4.4.5, first sentence, delete the word "Two" and start sentence with the word "Samples".

Paragraph 4.4.6, delete paragraph in its entirety and replace with the following:

"4.4.6 Gasket and thread test (applicable to style B and C flashlights only). Flashlights shall be completely assembled including batteries. All component parts that are threaded shall be backed off a minimum of two (2) complete threads and retightened using the manufacturers recommended torque for tightening to a watertight condition, a torque not exceeding 30 pound inches. This shall be considered as one test cycle. There shall be a minimum of 100 test cycles all of which shall use the same torque used in the first test cycle, a torque not exceeding 30 pound inches. The parts shall remain tightened for at least two minutes during each cycle. Upon completion of the last test cycle, the flashlights shall be assembled using a torque of 50 pound inches $\pm$ 2 pound inches, whereupon compliance with 3.3.3 shall be determined. Subsequently, the style B and C flashlights shall be assembled using the manufacturer's recommended torque for watertightness, a torque not exceeding 30 pound inches, whereupon flashlights shall be subjected to the watertightness test specified in 4.4.7 below."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

PAGE 6 (con.)

Paragraph 4.4.8, delete in its entirety and replace with following:

"4.4.8 Thread test (applicable to Style A flashlights only). Flashlights shall be completely assembled including batteries. All component parts that are threaded shall be backed off a minimum of two (2) complete threads and retightened using the manufacturer's recommended torque for tightening parts, a torque not to exceed 30 pound inches. This shall be considered one test cycle. There shall be a minimum of 100 test cycles all of which shall use the same torque used in the first cycle, a torque not exceeding 30 pound inches. The parts shall remain tightened for at least two minutes during each cycle. Upon completion of the last test cycle, the flashlight shall be assembled using a torque of 50 pound inches $\pm$ 2 pound inches, whereupon compliance with 3.3.3 shall be determined."

PAGE 7

Paragraph 4.4.11, delete paragraph in its entirety and replace with the following:

"4.4.11 Switch. The switch mechanism of the flashlight shall be tested by operating the switch contacts for 25,000 continuous cycles at a rate of 15 to 20 cycles per minute. A cycles shall consist of movements from "OFF" position to full "ON" position and back to "OFF" position. The switch shall be operated under normal electrical load conditions. The lamp and batteries shall be renewed as often as required to assure that the switch mechanism is operating under normal load throughout the 25,000 cycles (see 3.3.7). Failure of switch to complete 25,000 cycles of operation without malfunction shall be cause for rejection.

Paragraph 4.4.13, first sentence, delete in its entirety and replace with the following:

"The suspension ring shall be tested by suspending a weight of 25 pounds from the ring for one minute with the flashlight in a vertical position, base down, to determine compliance with 3.3.9."

Section 5, delete in its entirety and replace with the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A. Each flashlight shall be individually packaged in accordance with submethod IC-2 of MIL-P-116.

5.1.1.1 Intermediate packaging. Twelve flashlights of one stock number, as specified in 5.1.1, shall be intermediate packaged in a close-fitting box conforming to PPP-B-636, W6c.

5.1.2 Level B. Each flashlight shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The box shall be closed and secured to prevent accidental opening.

5.1.2.1 Intermediate packaging. Twelve flashlights of one stock number packaged, as specified in 5.1.2, shall be intermediate packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be closed and secured to prevent accidental opening.

5.1.3 Level C. Flashlights shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Intermediate packages of like description, in quantities, as specified (see 6.2), shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, or PPP-B-621, class 2. The box shall be closed, waterproofed and strapped in accordance with the appendix to the applicable box specification. When the gross weight exceeds 250 pounds, skids shall be provided in accordance with the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:34Z
Check the source to verify that this is the current version before use.

"5.2.2 Level B. Six intermediate packages (72 flashlights) shall be packed in a close fitting box conforming to PPP-B-636, class domestic. The box shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The flashlights, packaged, as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable."

PAGE 8

Paragraph 6.2, part f, delete in its entirety and replace with the following:

"(f) Quantity of intermediate packages required in the shipping container (see 5.2.1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.