MILITARY SPECIFICATION

CASE, SHIPPING, REUSABLE: 11727512

1. SCOPE

1.1 Scope.- This specification covers the performance requirements and quality assurance provisions for a multipurpose shipping case for Computer Gun Direction: M18 and Radar Chronograph M36, recoverable repair components (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-108	Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-129	Marking for Shipment and Storage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. Army, Frankford Arsenal

F11727512 Case, Reusable, Shipping

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from procuring activity or as indicated by contracting officer.)

3. REQUIREMENTS

3.1 Materials.- The materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

3.2 Fabrication.- The case shall be manufactured in accordance with Drawing F11727512 and all drawings pertaining thereto.

3.2.1 Shell forming process.- The upper and lower case shells shall be thermo-formed by any proven method normally associated with the plastic industry. Finished formed parts shall be entirely free of blisters, blemishes, or thermo shock stress marks.

3.3 General specification.- The contractor shall be responsible for adherence to the following requirements of MIL-F-13926:

(a) Dimensions and tolerances
(b) Inorganic protective surface finishes
(c) Part identification and marking
(d) Workmanship

3.4 Environmental.

3.4.1 Storage.- The case assembly shall be capable of maintaining dimensional and structural integrity when subjected to temperature extremes of 150°F to -80°F. The case shall show no evidence of distortion, cracks, or delamination and shall remain watertight.

3.4.2 Standard ambient temperature.- Subsequent to the requirements of 3.4.1, the case shall meet all performance requirements of this specification at a standard ambient temperature between +60° and +90°F.

3.4.3 Impact resistance (ambient temperatures).- The latched case assembly, fitted with a dummy load, weighting 14 pounds, shall sustain two drops, once on the top and once on the bottom, from a height of 30 inches. Subsequent to the two drops, the case shall show no evidence of damage which will affect its intended function. The impacts shall not unlatch the cover from the body, and the case shall then meet the requirements of 3.4.5 and 3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

3.4.4 Impact resistance (low temperature).- The latched case assembly, fitted with dummy load, weighing 14 pounds, shall sustain two drops, once on the top and once on the bottom, from a height of 30 inches after being subjected to low temperature conditioning at -40°F. Subsequent to the two drops, the case shall show no evidence of damage which will affect its intended function. The impact shall not unlatch the cover from the body, and there shall be no evidence of cracks or fractures. The case assembly shall then meet the requirements of 3.4.5 and 3.5, after the case has returned to ambient temperature.

3.4.5 Watertight.- The interior of the case shall show no evidence of leakage or moisture after the locked case is submerged in 3 feet of water in accordance with the watertight test specified in Table III of MIL-STD-108.

3.4.6 Extreme operating temperatures.- The case shall meet the performance requirements of this specification while exposed to, and thermally stabilized at ambient temperatures of -65°F and 150°F.

3.5 Performance.

3.5.1 Fasteners, handles and hinges.- Fasteners, handles and hinges shall function without interference. The fasteners when engaged shall secure the cover to the body and shall displace a uniform compression on gasketed seal.

3.5.2 Cover.- The cover and body shall mate freely and shall open and close easily, without restriction or interference.

3.5.3 Cushion inserts.- Cushion inserts shall be securely fastened to the cover and body and shall show no evidence of damage or shifting.

3.6 Workmanship.- Cases fabricated to the requirements of this specification, shall be in accordance with proven forming techniques and shall be free of defects that might affect strength, serviceability and protection of contents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of two (2) case assemblies manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.- Components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105, and the sampling plan specified in Table I. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

TABLE I - CLASSIFICATION OF DEFECTS

CLASS CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
CRITICAL: NONE		
MAJOR: AQL 1.0% Defective		
101. Fasteners, handles and hinges	3.5.1	4.6.2.1
102. Cover	3.5.2	4.6.2.2
103. Cushion inserts	3.5.3	4.6.2.3
MINOR: NONE		

4.3.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General.- Two sample cases shall be selected at random as a special sampling from each lot produced. The samples shall have successfully met all other acceptance tests specified herein, and shall then meet the following requirements and tests.

TEST	REQUIREMENT	TEST PROCEDURE
301. Fabrication	3.2	F11727512
302. General specification	3.3	MIL-F-13926, Visual

4.4.2 Environmental and functional.- Two sample cases shall be selected at random as sample from each lot produced. The samples shall have successfully met all other acceptance tests specified herein, and shall then meet the following requirements and tests:

TEST	REQUIREMENT	TEST PROCEDURE
303. Storage	3.4.1	4.6.1.1
304. Impact resistance (ambient temperatures)	3.4.3	4.6.1.2
305. Impact resistance (low temperature)	3.4.4	4.6.1.3
306. Watertight	3.4.5	4.6.1.4
307. Extreme operating temperatures	3.4.6	4.6.1.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents (IEL), when provided with the Technical Data Package (TDP).

4.5.2.2 Contractor design.- The contractor shall make available inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.2.2.1 Preparation for tests.- The case assembly shall be fitted with a dummy load having a mass of 13-1/2 x 6-3/4 x 4 and a weight of 14 pounds. The pressure relief valve shall be removed and aperture sealed with a gasketed fitting when performing the watertight tests.

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Storage.- The case assembly with dummy load shall be tested as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

(a) Elevated temperature.- The case assembly shall be placed in test chamber and the temperature elevated gradually to 150°F and allowed to remain at this temperature until thermo-stabilization is reached within the case. The test sample shall remain at the thermo-stabilized temperature of 150°F for a period of 4 hours, after which the temperature shall be gradually reduced to ambient. There shall be no evidence of cracks, delamination or distortion as a result of the test. There shall be no leakage when the case is tested in accordance with 4.6.1.4.

(b) Low temperature.- The case assembly shall be placed in test chamber and the temperature lowered gradually to -80°F and allowed to remain at this temperature until thermo-stabilization is reached within the case. The test sample shall remain at the thermo-stabilized temperature of -80°F for a period of 4 hours, after which the temperature shall be gradually raised to ambient. There shall be no evidence of cracks, delamination or distortion as a result of the test. There shall be no leakage when the case is tested in accordance with 4.6.1.4.

4.6.1.2 Impact resistance (ambient temperature).- The sample case fitted with dummy load shall be subjected to a 30 inch free fall, flat drop, once on the top and once on the bottom onto a steel or concrete surface. Following the test, the case shall be subjected to a watertight test specified in 4.6.1.4.

4.6.1.2.1 Results of test.- The case assembly shall be examined and there shall be no evidence of chipping, cracking, delamination or water penetration.

4.6.1.3 Impact resistance (low temperature).- The sample case shall be placed in a test chamber and the temperature lowered gradually to -40°F and allowed to remain at this temperature until thermo-stabilization is reached within the container. The test sample shall remain at the thermo-stabilized temperature of -40°F for a period of 4 hours. The sample shall be immediately subjected to impact test described in 4.6.1.2. The case shall be subjected to watertight test specified in 4.6.1.4 after container has been stabilized at ambient temperatures.

4.6.1.3.1 Results of test.- The case assembly shall be examined and there shall be no evidence of chipping, cracking, delamination or water penetration.

4.6.1.4 Watertight.- The watertight test shall be performed in accordance with Table III of MIL-STD-108.

4.6.1.5 Extreme operating temperatures.- The operating temperature test consists of exposing the case to the temperatures indicated in 3.4.6 by means of equipment complying with the requirements of 4.5.2.2. The test shall be conducted in accordance with Procedure II of MIL-F-13926, and the temperature conditions of 3.4.6 shall apply. While exposed to

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

these temperatures, the case shall meet the requirements specified in 3.5.1, 3.5.2 and 3.5.3.

4.6.2 Performance.

4.6.2.1 Fasteners, handles and hinges.- Operability of these devices shall be checked by a functional and visual examination. The fasteners shall be operated five times to determine compliance with the requirements specified in 3.5.1.

4.6.2.2 Cover.- The cover shall be operable as specified in 3.5.2 when subjected to a functional examination by opening and closing the case at least five times and subsequently visually examining the components for defects or poor workmanship.

4.6.2.3 Cushion inserts.- A visual and tactile examination shall be performed to determine that the cushions are securely bonded in position. Visual examination shall reveal no evidence of damage or shifting of cushions.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing.- Unless otherwise specified, the cases shall be prepared for shipment using normal commercial methods, or materials to assure acceptance by common or other carrier for safe transportation at the lowest rate to point of destination.

5.2 Marking.- Marking for shipment shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The case assembly defined herein is intended to accommodate, but not limited to the following items:

Keyboard	-	Part No. 10526191
Matrix	-	Part No. 10526190
Indicator, Digital display	-	Part No. 8215501
Power supply	-	Part No. 10512499
Control, electrical Frequency	-	Part No. 10525510
Amplifier Audio frequency	-	Part No. 10512508
Amplifier detector	-	Part No. 10525674

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification
(b) Applicable stock number
(c) Order of document precedence

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A227

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.