MIL-C-14866(MU)
AMENDMENT 1
30 July 1973

MILITARY SPECIFICATION

CONTROL, POWER SUPPLY: 10559261

This amendment forms a part of Military Specification MIL-C-14866(MU), dated 2 March 1970.

Page 4, paragraph 3.3.2.5: Delete and substitute as follows:

"3.3.2.5 Sealing.- With the power supply control initially pressurized with nitrogen or air to 5 ± 1 pounds per square inch gage (psig), the loss of pressure shall not exceed 0.2 psig in 2 hours."

Page 7, Table IV, Item 307: Delete "Immersion" and substitute "Sealing".

Page 8: Add paragraph 4.5.2.2.1 as follows:

"4.5.2.2.1 Pressure tester.- Special test equipment (STE) in accordance with Drawing 8565556, or equivalent, shall be provided to check the sealing of the power supply control."

Page 9, paragraph 4.6.5: Delete "and the tolerance requirements for vibration frequency measuring instruments shall not apply."

Page 9, paragraph 4.6.5.1, NOTE: Delete "less than 7°F" and substitute "no greater than 3°F".

Page 10, paragraph 4.6.5.2 (a): Delete and substitute as follows:

"(a) Test in accordance with Method 514.1, Procedure I of MIL-STD-810 for category (f) equipment, except that resonance search and dwell on resonance shall not be required and the acceleration shall not exceed ± 4g and the maximum excursion (double amplitude) shall be 0.5 inch."

Page 11, paragraph 4.6.5.4: Delete and substitute as follows:

"4.6.5.4 Sealing.- Perform this test utilizing the STE specified in 4.5.2.2.1. Pressurize the power supply control as specified in 3.3.2.5. Measure the pressure loss over a minimum period of 120 minutes. Verify that the requirement of 3.3.2.5 is met."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A522

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:58Z
Check the source to verify that this is the current version before use.