MIL-C-14858A (AR)
30 April 1985
SUPERSEDING
MIL-C-14858(MU)
23 November 1963

MILITARY SPECIFICATION

CARTRIDGE, CALIBER .50: REFERENCE

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a Cartridge, Caliber .50, Reference to be used for calibrating acceptance testing equipment.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspections of Attributes
MIL-STD-109	-	Quality Assurance Terms and Definitions

FSC 1305

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

MIL-STD-636	-	Visual Inspection Standards for Small Arms Ammunition Through Caliber .50
MIL-STD-644	-	Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition
MIL-STD-1168	-	Lot Numbering of Ammunition

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWING

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

7643674	-	Classification of Cartridge Case Defects
10521041	-	Cartridge, Caliber .50, Reference
10542647	-	Packing and Marking, Cartridge, Cal. .50, Reference; Cartons; Box, Ammunition, M2A1; Box, Wirebound
10542648	-	Packing and Marking, Cartridge, Cal. .50, Reference; Cartons; Box, Ammunition, M2A1
LI-10521041	-	Index of Inspection Equipment Lists for Cartridge, Cal. .50, Reference

PUBLICATIONS

SCATP-7.62	-	Ammunition Ballistic Acceptance Test Methods, Test Procedures for 7.62mm Cartridges
TECP 700-700 Vol. 3	-	Manual of Test Methods for Small Arms Ammunition

(Copies of specification, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The cartridge shall comply with the requirements specified on Drawing 10521041 referenced specifications and the following:

3.2 Bullet extraction. The force required to extract the bullet from the cartridge case shall be not less than 200 pounds.

3.3 Residual stress. The cartridge case shall not split or crack when subjected to a 1% mercurous nitrate solution for 15 minutes.

3.4 Waterproof. The cartridge shall not release more than one bubble of air when subjected to a pressure differential of 7 1/2 pounds per square inch (psi) for 30 seconds.

3.5 Action time. The action time (overall primer ignition, propellant burning and bullet-barrel time) of the cartridge shall not exceed 4 milliseconds.

3.6 Velocity. The grand average of the velocities of all the sample cartridges conditioned at 70° Fahrenheit (F), shall be 2910 feet per second (ft/sec), plus or minus 20 ft/sec, at 78 feet from the muzzle of the weapon. The average of standard deviations of velocities for fifteen 20-round series shall not exceed 20 ft sec.

3.7 Chamber pressure. The average chamber pressure of the sample cartridges, conditioned at 70°, shall not exceed 55,000 psi. The average of the standard deviations of chamber pressure for fifteen 20-round series shall not exceed 2000 psi.

3.8 Function and casualty. The cartridge shall function without casualty.

3.9 Workmanship. The metal parts of the cartridge shall be free of cracks, splits, perforations, burrs and foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by any cleaning agent. All parts and assemblies shall be fabricated, loaded and assembled in a thorough and workmanlike manner. In addition, the cartridge shall comply with the standards specified in the .50 Caliber section of MIL-STD-636. Extreme care should be exercised to avoid contamination of primers or propellant by oil, grease or other foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Quality Conformance Inspection (see 4.3)

4.3 Quality Conformance Inspection

4.3.1 Lot formation. In accordance with MIL-A-48078.

4.3.1.1 Lot submission. The product shall be submitted in accordance with MIL-STD-105. The entire lot of reference cartridges shall be assembled and charged on a single loading machine. (See 6.7)

4.3.1.2 Component parts. Unless otherwise specified, component lots shall be homogeneous and of a size convenient to the contractor and inspected, tested and accepted by the contractor. The cartridge lot shall not contain:

a. Cartridge cases from more than one lot interfix number from one manufacturer.

b. Primers from more than one lot and more than one manufacturer.

c. Bullets from more than one interfix number from one manufacturer.

d. Propellant from more than one lot and more than one manufacturer.

4.3.1.3 Lot identification. Each lot of ammunition shall be identified as to type, caliber and model, as well as a lot number in accordance with MIL-STD-1168 and the suppliers identification as assigned by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

4.3.2 Examination for defects.

a. Major and minor defects. Examination for major and minor defects shall be performed on a class basis in accordance with classification of defects using applicable sampling plans and acceptance criteria of MIL-STD-105. All non-conforming cartridges shall be rejected.

b. Critical defects. Unless otherwise specified, one hundred percent examination shall be performed for all critical defects. If a visual critical defect is found in a sample either just prior to a firing test or after a firing test (and the defect is not due to the firing), the lot shall be rejected. The lot shall then be rescreened and resubmitted for visual inspection of critical defects. If a critical defect is found during packing, the portion of the lot that has been packed or is in the process of being packed shall be rejected. In addition, the portion of the lot remaining to be packed shall be rejected. The lot shall then be rescreened and resubmitted for visual inspection of critical defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.1	Cartridge, Caliber .50 Reference	1 OF 4	10521041
			NEXT HIGHER ASSEMBLY: Not applicable

CATEGORY	EXAMINATION OR TEST 1/	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE 2/ /INSPECTION METHOD
Critical					
1.	Case split in K, L or M location (6)		100%	3.1	Visual
2.	Case split in I, S or J location with loss of powder (6)		100%	3.1	Visual
3.	Perforated Case (7)		100%	3.1	Visual
4.	Primer missing (32)		100%	3.1	Visual
5.	Primer cocked (33)		100%	3.1	Visual
6.	Primer inverted (34)		100%	3.1	Visual
7.	Weight, under min 3/		100%	3.1	Balance
Major	(Class AQL - .25%) (except for Major 101.)				
101.	Case split in I, S, or J location with no loss of powder (6)		100%	3.1	Visual
102.	Corroded or stained (if etched) case (2)			3.1	Visual
103.	Round head, case (4)			3.1	Visual
104.	Dented case (5)			3.1	Visual
105.	Draw scratch in case (8)			3.1	Visual

NOTES: 1/ Numbers after defect descriptions refer to visual defect standards in MIL-STD-636 (Caliber .50 Section).
2/ Refer to MIL-STD-636 (Caliber .50 Section) for visual defect standards. In the event of conflict between paragraph 4.3.2.1 of this specification and MIL-STD-636 as to defect classification the classification specified in paragraph 4.3.2.1 shall apply.
3/ Each lightweight cartridge shall be disassembled and the propellant weighed. Any cartridge containing less than 100 grains of propellant shall be classed as a critical defect. Any cartridge containing 100 grains or more of propellant shall be classed as a major defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-14858A (AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER 10521041
4.3.2.1	Cartridge, Caliber .50 Reference				NEXT HIGHER ASSEMBLY Not applicable
CATEGORY	EXAMINATION OR TEST 1/	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
106.	Beveled underside of head (10)			3.1	Visual
107.	Case mouth not crimped in cannelure (11)			3.1	Visual
108.	Scaly metal on case (12)			3.1	Visual
109.	No chamfer on head (rim) (13)			3.1	Visual
110.	No visible evidence of mouth anneal (21)			3.1	Visual
111.	Split bullet jacket (24)			3.1	Visual
112.	Loose bullet (25)			3.1	Visual/Manual
113.	Missing cannelure (26)			3.1	Visual
114.	Scaly metal on bullet (27)			3.1	Visual
115.	Loose primer (35)			3.1	Visual/Manual
116.	Total length			3.1	Gage
117.	Cartridge profile failure (requiring more than 80 lbs dead weight to insert in profile and alignment gage)			3.1	Gage
118.	Diameter of extractor groove, max			3.1	Gage
119.	Diameter of head			3.1	Gage
120.	Thickness of head			3.1	Gage
121.	Length to shoulder datum			3.1	Gage
122.	Depth of primer			3.1	Gage

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.1	Cartridge, Caliber .50 Reference	3 OF 4	10521041
			NEXT HIGHER ASSEMBLY: Not applicable

CATEGORY	EXAMINATION OR TEST 1/	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor	(Class AQL - 1.5%)				
201.	Discolored, dirty, oily, or smeared (waterproofing) (1)			3.1	Visual
202.	Dented case (5)			3.1	Visual
203.	Draw scratch in case (8)			3.1	Visual
204.	Scratch in case (9)			3.1	Visual
205.	Scaly metal on case (12)			3.1	Visual
206.	Fold, wrinkle, buckle or bulge in case (14, 15, 16, 17)			3.1	Visual
				3.1	Visual
207.	Head stamp missing or illegible (18)			3.1	Visual
208.	Defective head (19)			3.1	Visual
209.	Defective mouth (20)			3.1	Visual
210.	Dented bullet (22)			3.1	Visual
211.	Bullet scratched (23)			3.1	Visual
212.	Scaly metal on bullet (27)			3.1	Visual
213.	Upset (crooked) point (28)			3.1	Visual
214.	Exposed steel (clad jacket) (29)			3.1	Visual

NOTES:

8 Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-14858A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.1	Cartridge, Caliber .50 Reference	4 OF 4	10521041
			NEXT HIGHER ASSEMBLY: Not applicable

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
215.	Blunt point (30)			3.1	Visual
216.	Defective cannelure (31)			3.1	Visual
217.	Nicked or dented primer (36)			3.1	Visual
218.	No waterproofing material (primer pocket joint) (37)			3.1	Visual
219.	Defective crimp (38)			3.1	Visual
220.	Diameter of extractor groove, min			3.1	Gage
221.	Evidence of poor workmanship 4/			3.9	Visual

NOTES:

4/ Defects other than those listed in MIL-STD-636 (Caliber .50 Section).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. Testing is described in the Quality Conformance Inspection tables (4.3.3.1). Testing shall be conducted in accordance with the methods and procedures specified in 4.3.

a. Test samples. The quantities for the various tests shall be as specified in paragraph 4.3.3.1. Only cartridges having met the visual and dimensional requirements shall be used in the ballistic tests, and shall have been selected in such a manner that the sample is representative of the entire lot. Sufficient cartridges shall be selected such that all testing (including testing of second samples where applicable) can be performed. The cartridges shall be thoroughly mixed before being divided into samples for the various tests.

b. Firing defects. Firing defects and associated acceptance-rejection criteria are specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-14858A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.3.3.1	Cartridge, Caliber .50, Reference				10521041
					NEXT HIGHER ASSEMBLY
					Not applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Test				
	Bullet extraction	25	1/	3.2	4.4.1
	Residual stress (mercurous nitrate)	20	1/	3.3	4.4.2
	Waterproof	50	2/	3.4	4.4.3
	Action time	50	1/	3.5	4.4.4
	Velocity	300	3/	3.6	4.4.5
	Chamber pressure	300	3/	3.7	4.4.6
	Function and casualty	650	4/	3.8	4.4.7

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be us

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-14858A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.3.1	Cartridge, Caliber .50, Reference	2 OF 2	10521041
			NEXT HIGHER ASSEMBLY: Not applicable

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	1/ Failure of 2 or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample, the lot shall be rejected. 2/ Failure of 10 or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than 3 but less than 10 cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if, in the combined first and second sample, 10 or more cartridges fail to comply with the applicable requirement. 3/ Failure of the cartridges to comply with the applicable requirements shall be cause for rejection of the lot (See 6.7.2) 4/ Examination for firing defects shall be made during the firing of all ballistic tests. A lot shall be rejected when firing defects exceed the acceptance number in Table I.				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

TABLE I

Firing defect classification and accept-reject criteria

Defect Class	Defect Description	ACC	REJ
	CARTRIDGE FAILURES		
Critical	a. Bullet in bore	0	1
Critical	b. Misfire - Vent hole missing or blocked 1/	0	1
Major	c. Misfire - (excluding b. above)	1	2
	PRIMER FAILURES		
Major	a. Perforation of firing pin ident in primer cup	2	3
Major	b. Escape of gas through primer cup (excluding a above)	1	2
Major	c. Loose primer 2/	3	4
Major	d. Blown primer 2/	0	1
Major	e. Dropped primer 2/	0	1
	f. Escape of gas around primer cup		
Major	(1) 50% or more than 50% of periphery	7	8
Minor	(2) Less than 50% of periphery	12	13
	CASE CASUALTIES 3/		
I. Longitudinal split			
Major	a. Body (J)	2	3
Major	b. Body (K)	0	1
Major	c. to head (L)	0	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

Major	d. Through head (M)	0	1
Minor	e. Neck and shoulder (I or S)	13	14

II. Circumferential Rupture

Major	a. Partial, shoulder or body (J & S)	1	3
Major	b. Partial, body (K)	0	1
Major	c. Partial, head (L)	0	1
Major	d. Complete	0	1

Note 1/ Each cartridge that misfires shall be disassembled and examined for a blocked or absent vent hole. If the vent hole is blocked or missing the lot shall be rejected.

Note 2/ Primer Defect Description:

a. Loose primer. The fired primer shall be called loose when it protrudes above the case head or movement of the primer can be observed by applying pressure on the primer by means of a probe, thumbnail or fingertip.

b. Blown primer. A primer which, when the cartridge is fired, is separated completely from the head of the cartridge case, and both the head of the case and the primer pocket are grossly distorted and deformed. The severity of this condition is such that it is readily detectable by visual examination.

c. Dropped primer. A primer which falls from the primer pocket after the cartridge is fired.

Note 3/ For location of defects indicated by letters in parenthesis, see Drawing 7643674.

4.3.4 Packaging, packing, and marking. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644. During or immediately prior to the packaging operation, 100 percent examination of the cartridges shall be performed to ascertain that the cartridge type conforms to the drawing. Occurrence of a high pressure test cartridge shall be classed as a critical defect. Occurrence of any incorrect type other than high pressure test shall be classed as a major defect. All non-conforming cartridges shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

4.3.5 Inspection equipment. The inspection equipment required to perform the examination and test prescribed herein is described in the Paragraph Reference/Inspection method column in the tables starting with Paragraph 4.3.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.3.5.1 Inspection equipment list. The examination and tests shall be made using equipment listed on LI-10521041, except as specified in 4.3.

4.4 Methods of inspection.

4.4.1 Bullet extraction. The cartridges shall be tested in an approved bullet extractor machine. The rate of travel of the test head shall be not less than 3 nor more than 6 inches per minute. The test shall be conducted in accordance with TECP 700-700, Vol. 3.

4.4.2 Residual stress (Mercurous nitrate). Tests shall be conducted in accordance with TECP 700-700, Vol. 3.

4.4.3 Waterproof. The ammunition to be tested (not to exceed five cartridges at one time) shall be placed horizontally on a perforated tray. The tray shall be placed in a desiccator containing sufficient quantity of freshly boiled water to maintain a head of 2 to 2 1/2 inches. The desiccator shall be evacuated to a pressure of 7 1/2 pounds per square inch (15 inches of mercury below atmospheric pressure and held at that pressure for 30 seconds. The number of bubbles liberated from the mouth or primer of each cartridge shall be observed.

4.4.4 Action time. The test shall be conducted in accordance with SCATP-7.62.

4.4.5 Velocity. Prior to this test, cartridges shall be conditioned at $70^{\circ} \pm 2^{\circ}F$ for a minimum of two hours. The test shall be conducted in accordance with TECP 700-700 Vol. 3, and the following: The five velocity barrel assemblies for the velocity test shall be selected from a quantity of eight chamber pressure barrels using the long piston. Selection of the five barrel assemblies shall be made by firing 30 reference cartridges in each barrel. The five test barrel assemblies that have the lowest standard deviation for velocity shall be selected for the test. Prior to firing of the 30 reference cartridges, each barrel assembly shall be "broken in" by firing 100 standard cartridges. Once broken in, the breaking in process shall not be repeated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

Twenty cartridges shall be fired in each of five velocity barrel assemblies. The average velocity and standard deviation of velocities for each velocity barrel assembly and the average velocity for the five assemblies shall be computed. If the average velocity for any velocity barrel assembly varies from the average for the five assemblies by more than plus or minus 14 feet/second on the first day of firing, then that assembly shall be discarded and another selected and firing conducted therein until the aforementioned condition is met by all five assemblies; thereafter, on the two succeeding days, the same five assemblies shall be used. An additional 20 cartridges shall be fired in the same manner in the same velocity barrel assemblies on each of two succeeding days. The average velocity and standard deviation of velocities for each 20-round test, the daily average velocity (20-rounds in each of five assemblies), and the grand average for the entire 15 velocity series (five assemblies on each of three days) shall be computed.

4.4.6 Chamber pressure. Prior to this test, cartridges shall be conditioned at $70^{\circ} \pm 2^{\circ}F$ for a minimum of two hours. The test shall be conducted in accordance with TECP 700-700, Vol. 3 and the following: The five chamber pressure barrel assemblies specified in paragraph O.P.M 7-12, 2.1.(2)(b) of the TECP shall be selected from a quantity of eight barrel assemblies. Selection of the five barrel assemblies shall be made by firing 30 reference cartridges in each barrel. The five test barrel assemblies that have the lowest standard deviation for chamber pressure shall be selected for the test. Prior to firing of the 30 reference cartridges, each barrel assembly shall be "broken in" by firing 100 standard cartridges. Once broken-in, the breaking in process shall not be repeated. Twenty cartridges shall be fired in each of five pressure barrel assemblies on each of three days. The average chamber pressure and standard deviation of pressures for each 20-round test, the daily average chamber pressure (20 rounds in each of five assemblies) and the grand average chamber pressure for the entire 15 pressure series (five assemblies on each of three days) and the average of the standard deviations for the 15 pressure series shall be computed.

4.4.7 Function and casualty. This test shall be conducted simultaneously with the velocity and pressure tests.

4.4.8 Defect penalty. In any ballistic test in which the occurrence of a firing defect prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the acceptance sample shall be penalized for such defects in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging - level A (worldwide shipment). The cartridges shall be packaged in accordance with Drawing 10542648.

5.2 Packing - level A (worldwide shipment). Packing shall be in accordance with Drawing 10542647.

5.3 Marking and labeling. Marking and labeling of the packed cartridges shall be in accordance with Drawing 10542647.

6. NOTES

6.1 Intended use. The cartridges covered by this specification are intended for use as reference cartridges for calibration purposes in Cal. .50 cartridge acceptance testing.

6.2 Ordering data. Ordering data should include:

a. Title, number and date of this specification.

b. Type and level of packing for the cartridges.

c. Provisions for the submission of Inspection Equipment Designs (DI-R-10054) (see 6.3).

d. Provisions for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government (see 6.7).

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit inspection equipment designs as required to Commander, ARDC, ATTN: AMSMC-QAF-I (D), Dover, NJ 07801-5001.

6.4 Hazard notice. The cartridge described herein and some of its components are flammable and explosive and consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to prevent fire, explosion, adverse environment, rough handling, corrosive atmosphere, and electrically induced incidents. Such measures shall include the employment of an effective safety program that addresses the inherent hazards associated with the cartridge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawing prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, US Army Armament Research and Development Command (ARRADCOM) or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.6 Submission of test data. In addition to the normal distribution of records, when the cartridge is procured by the US ARDC, one (1) copy of all ballistic data and the ammunition data card for each lot shall be forwarded to: Commander, ARDC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001.

6.7 In-process controls.

6.7.1 Uniformity of charge. A machine shall be chosen which is known to drop charges with better than average uniformity and which gives constant results in the daily production tests. If relative machine performacne is unknown, special tests should be fired to assure selection of a good machine.

6.7.2 Loading control. A quantity of 20 rounds shall be fired for pressure and velocity for each four hours of an eight hour shift to establish velocity and pressure values, and check charge weight and uniformity of charge weight every hour. Once established, the charge weight shall remain constant throughout loading.

6.8 Changes from previous issues. Asterisks are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AB30)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:57Z
Check the source to verify that this is the current version before use.