MIL-F-14847B (AR)
AMENDMENT 8
10 July 1979
SUPERSEDING
MIL-F-14847B (MU)
AMENDMENT 7
30 May 1979

MILITARY SPECIFICATION

FUZE, MTSQ, M564 ASSEMBLY

LESS BOOSTER PELLET AND LEAD CHARGE

This amendment forms a part of Military Specification MIL-F-14847B (MU) dated 17 June 1975.

PAGE 1

In the title, delete "CLOSING, CUP" and change "(LEAD)" TO "LEAD".

Paragraph 2.1 under "Standards" add, "MIL-STD-1168 Ammunition Lot Numbering".

Paragraph 2.1, delete the words "Munitions Command" and substitute "Armament Command".

PAGE 3

Paragraph 3.4.5 Delete "(Ambient temperature)" and substitute "($+70^{O} \pm 5^{O}F$).

PAGE 4

Paragraph 3.4.9 Delete in its entirety.

Paragraph 4.1.2 Add, "Lot numbering, as required, shall be in accordance with MIL-STD-1168."

PAGE 5

Paragraph 4.2 Delete the number "425" and substitute "450".

Paragraph 4.2 Line 3, delete in its entirety and add "340 or 360 (aggregate) (as applicable See 4.2.2.3) component parts as delineated in 4.2.2".

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:54Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.1 Delete the number "425" and substitute "450".

Paragraph 4.2.1 Delete the second sentence in its entirety and substitute "three hundred forty (340) or 360 component parts (as applicable), 450 sub-assemblies and 22 fuze subassemblies shall be inspected, as provided herein, at a government laboratory or other facility as specified in the contract."

Add paragraph 4.2.3.3 as follows:

"4.2.2.3 Twenty (20) of each component (1) if applicable shall be tested as in 4.3.3.15 (Force)."

Paragraph 4.2.3.1 Delete the number "(15)" and substitute "(16)".

PAGE 6

Paragraph 4.2.6 Delete "(Ambient Temperature)" next to "Time-to-burst" and substitute, "($+70^{O} \pm 5^{O}F$)."

PAGE 7

Paragraph 4.2.6.1.e Delete "ambient"

PAGE 12

Paragraph 4.3.2.17 Delete Critical 1 in its entirety and substitute "1. Letter "S" not over its proper line Visual". Delete Major "106" in its entirety.

PAGE 13

Paragraph 4.3.2.18 Delete Critical 2 in its entirety and substitute "2. Internal thread not full to undercut Gage".

PAGE 14

* Paragraph 4.3.2.22 Delete the paragraph in its entirety.

PAGE 16

Paragraph 4.3.2.27 Delete the heading in its entirety and substitute, "Rotor Assembly, Drawing D10551356 or Drawing D11744013 covering a detail of Drawing F10534285".

Paragraph 4.3.2.29 Delete the number "1.0%" and substitute "0.40%".

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:54Z
Check the source to verify that this is the currentversion before use.

PAGE 20

Paragraph 4.3.2.38 Delete Major 102 in its entirety.

* Paragraph 4.3.2.40 Delete Critical 1 in its entirety.

Paragraph 4.3.3.5.1 Under "Closing Plug Assembly" add"**D.A.M. Assembly (Push on Setback Mechanism Assembly) F10520702". Add footnote, "**Only Setback Mechanism Assembly D10550357 need to be assembled into D.A.M. Body F10520703 for the static load test. The methods and equipment used to assemble these samples shall be the same ones used in production of the D.A.M. Assembly".

PAGE 26

Paragraph 4.3.3.12.1 Delete "requirement of drawing F11738601" and substitute "requirement of body and cap assembly, drawing F10520720".

Paragraph 4.3.3.14 Delete "(ambient temperature)".

PAGE 27

Paragraph 4.3.3.14 Delete "(ambient temperature)".

Paragraph 4.3.3.14.1.e Delete "Ambient".

Add Paragraph 4.3.3.15

> "Force-Sintered Rotor (Destructive) - Twenty samples from each lot of sintered rotors shall be subject to the force specified on drawing F11744012. Failure of any sintered rotor to comply with the requirement shall be cause for rejection of the lot of rotors."

PAGE 30

Paragraph 4.4.13.1.1b Delete the words "welsh plugs" and substitute "expansion plugs".

Paragraph 4.4.13.1.1c Delete the words "check for detent assembly, primer and firing pin" and substitute "check detent assembly, primer and firing pin".

* Paragraph 4.4.13.1.1e Delete "reinforcing ring and".

PAGE 31

Paragraph 4.4.13.3 Delete line "a" in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

Paragraph 4.4.13.5.1b Delete the words "Welsh plugs" and substitute "expansion plugs".

Paragraph 4.4.13.5.1c Delete the words "check for detent assembly primer and firing pin" and substitute"check detent assembly, primer and firing pin".

PAGE 32

Paragraph 4.4.14.4 To the end of the paragraph add, "Chamber pressures shall also be measured and recorded on the first and last rounds of each phase."

PAGE 33

Add Paragraph 4.4.15

"Force-Sintered Rotor - The test shall be performed using the value and direction specified on drawing F11744012. Rotors which have been subject to the applied force test shall be scrapped."

Paragraph 4.4.14.6.1 Delete in its entirety and substitute the following:

"4.4.14.6.1 Temperature Conditioning. For test phases which require specific temperatures, the fuze and the complete test-round, shall be temperature conditioned. The elapsed time from the conditioning chamber to the firing in the weapon shall not exceed five (5) minutes. Reconditioning is not permitted. The test chamber, with test items, shall be brought to within the conditioning temperature range and maintained until stabilization of the fuze temperature is reached (see 6.4). After stabilization, the test item shall be saturated at that temperature for 24 hours, minimum."

* The margins of this amendment are marked with an Asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1390-A231

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.