MIL-F-14854A (AR)
Amendment 3
12 May 1978
SUPERSEDING
Amendment 2
17 April 1978

MILITARY SPECIFICATION

FUZE, MTSQ, M564, ASSEMBLY
LOADING AND PACKING

This amendment forms a part of Military Specification MIL-F-14854A (MU), dated 16 April 1973.

PAGE 1

* Para. 2.1 Under "Standards" add, "MIL-STD-1168 Ammunition Lot Numbering". Under "Specification" add, "MIL-F-14847 Fuze, MTSQ, M564 Assembly less Booster Pellet and Closing Cup (Lead) Charge".

PAGE 2

* Add paragraph 3.4 as follows:

"3.4 Ballistics.-The fuze shall initiate detonation of the round upon impact when fired in the 105MM Howitzer, Charge 7 (1550 fps) with the fuze set "S" on a target 400-5 feet from the muzzle of the weapon."

Para. 4.1.2 Add "Lot numbering, as required, shall be in accordance with MIL-STD-1168".

PAGE 3

Para. 4.3.2.1 and 4.3.3.1 a, delete F10534649" and substitute "F11738601".

Para. 4.3.2.3, delete "B8595510" and substitute "C11738593".

PAGE 4

* Para. 4.3.2.4, add defect 104 as follows:

"104. Hole in booster cup not filled with sealant Visual"

Para. 4.3.3.1.b (2). delete "...on the booster pellets."

Para. 4.3.3.1 b (3), delete "safety adapter" and substitute "D.A.M assembly".

PAGE 5

*Add paragraph 4.3.3.3 as follows:

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:56Z
Check the source to verify that this is the current version before use.

"4.3.3.3 Ballistics.

4.3.3.3.1 Starting with the first lot produced and continuing until three consecutively produced lots have consecutively met the acceptance criteria, twenty (20) fuzes shall be selected from each lot and tested as specified in 4.4.2. The occurrence of three or more failures shall be cause for rejection of the lot.

4.3.3.3.2 After three lots have been accepted as specified in 4.3.3.3.1, ten (10) fuzes shall be selected from each lot and tested as specified in 4.4.2. The occurrence of two or more failures shall be cause for rejection of the lot. If any lot is rejected, sampling and acceptance criteria shall revert to 4.3.3.3.1 until three lots are again accepted as specified in that paragraph.

4.3.3.3.3 In the event the rate of failure in the metal parts lots exceed the allowable rate stated in the above paragraphs, the maximum failure rate encountered in the ballistic acceptance tests for the applicable metal parts lots will be used as an acceptance criteria. The rate will be determined by the results of the Target Impact Function Distance Phase and the Ground or Water Impact Function Phase of MIL-F-14847. The failure rate will be multiplied by the applicable sample size above, and the results will be rounded to the next highest integer. This figure will become the accept number for the test, and any failure which causes this number to be exceeded, will also cause the lot to be rejected."

* Add paragraph 4.4.2 as follows:

"4.4.2 Ballistics.-The sample fuzes shall be fired as specified in 3.4 against a suitably supported one inch plywood screen of adequate size under the conditions delineated in 4.3.3.3".

* The margins of this amendment are marked with an Asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1390-A-185

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:56Z
Check the source to verify that this is the current version before use.