INCH-POUND

MIL-C-22442/1B(AS)
AMENDMENT 1
24 MAY 1991

MILITARY SPECIFICATON

CABLE ASSEMBLIES, RADIO FREQUENCY (AIRCRAFT AUDIO), SWITCH ASSEMBLY

This amendment forms a part of MIL-C-22442/1B(AS), dated 2 September 1988, and is approved for use by the Naval Air Systems Command, Department or the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 12

Requirement 14: Change 30 milliamperes to 18 milliamperes in last sentence.

Requirement 19: Add: the following sentence after the first sentence "Unless otherwise specified, the DC bias shall be set to 27.5 $\pm$ .5 volts as measured across the DC bias supply terminals when placed in the circuit."

Page 13

Requirement 19c: Delete: Add new requirement: " The power supply shall be adjusted so that 27.5 volts DC appears across the output terminals of the DC bias supply when placed in the test circuit. The frequency generator shall be set to 1000 Hz. The input current shall be checked with a DC current meter."

PAGE 14

Requirement 19e line 4: Change "10 to 22 volts" to "10 to 30 volts".

Preparing Activity
Navy AS
Project No. 5995-N135

AMSC N/A FSC 5995

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:21Z
Check the source to verify that this is the current version before use.