RR-H-40B
May 4, 1973
SUPERSEDING
Fed. Spec. RR-H-40A
July 28, 1966

FEDERAL SPECIFICATION

HANDCART, GROCERY, (NESTING)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers metal grocery type handcarts (shopping carts).

1.2 Classification.

1.2.1 Types. Handcarts covered by this specification shall be furnished in the following types, as specified (see 6.2).

II - With baby seat and lower tray.
IV - With lower tray.
V - With baby seat.
VI - Without baby seat, or tray.

1.2.2 Sizes. Handcarts covered by this specification shall be furnished in the following large, upper basket sizes, as specified (see 6.2).

5000 cubic inches	8000 cubic inches
6000 cubic inches	9000 cubic inches
7000 cubic inches	10,000 cubic inches

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

Federal Specifications:

FF-C-77 - Casters, Institutional Duty.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-650 - Box, Fiberboard Special Purpose (Records Retiring).

Federal Standards:

Fed. Std. No. 66 - Steel: Chemical Composition and Hardenability.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC, 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from Buiness Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 7290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street NW Washington, DC 20036.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Carbon steel. Steel wire, strip and tubing shall conform to C1010 to C1020 of Fed. Std. No. 66.

3.1.2 Plastic. Plastic for handle, seat, and other components shall be acetal, acrylic, cellulose acetate butyrate, nylon, polypropylene, butadiene styrene, polystyrene, or polyethylene at the manufacturer's option.

3.2 Construction.

3.2.1 Basket. The upper basket shall be rectangular in shape, have a hinged rear gate, closely welded wire mesh sides and bottom, with reinforcements conforming to 3.1.1. When specified (see 6.2), baskets shall be furnished with plastic, rubber, or metal bumpers.

3.2.2 Supporting structure. The supporting structure shall be tubular steel, steel strip or a combination thereof conforming to 3.1.1.

3.2.3 Seat. The baby seat shall be of the folding variety to permit nesting or increasing capacity. A leg-hole closure device shall be provided and may be of plastic as specified in 3.1.2. The device shall operate in such a way as to prevent moisture from running back into the basket when leg-holes are closed.

3.2.4 Casters.

3.2.4.1 Front casters. Except when specified (see 6.2), front casters shall conform to Type II, Class C, Wheel diameter-5 inches, Style C, of Federal Specification FF-C-77.

3.2.4.2 Rear casters. Rear casters shall conform to Type I, Class C, Wheel diameter-5 inches, Style C, of Federal Specification FF-C-77.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

3.2.4.3 Mounting. Mounting of casters shall be in accordance with standard commercial practice. Casters shall not shimmy or flutter when operating in a lightly or fully loaded condition in accordance with 4.4.2.

3.2.5 Welding. All spots welds shall be sound and free of porosity, expulsion, or surface burning and shall show good penetration in each welded part. Fusion welding or brazing shall be in accordance with established welding procedures to insure welds of full strength. Welds shall be smooth, free from flux and cracks, surface porosity, and undercutting.

3.2.6 Tolerance. The tolerance on the sizes specified in 1.2.2 shall be plus or minus 5 percent when tested in accordance with 4.4.3.

3.3 Finish. The entire basket and supporting structure shall be nickel chrome plated in accordance with commercial practice.

3.4 Performance. Handcarts shall not overturn or deform when tested in accordance with 4.4.2.

3.5 Identification marking. Handcarts shall be marked in a plain and permanent manner with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

3.6 Personalized marking. When required (see 6.2), personalized markings shall be in accordance with standard commercial practice.

3.7 Workmanship. Handcarts shall be free from sharp edges, projections, and defects which might affect its serviceability, appearance, or endanger the health or safety of users.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of each type and size of handcart offered for delivery at the same time.

4.2.2 Visual and workmanship of end item. Handcarts shall be examined for these characteristics in accordance with level S-4 in MIL-STD-105.

4.2.3 Sampling for tests. Samples for tests shall be in accordance with level S-2 in MIL-STD-105.

4.3 Inspection.

4.3.1 End item. Handcarts shall be examined for defects listed in table I. The acceptable quality levels (AQL's) for defects listed in table I shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

TABLE I. Classification of defects, end item

Defects	Major	Minor
Type and size not as specified.	X	
Sharp edges or projections.	X	
Parts disengaged.	X	
Surface not plated.	X	
Casters fail to swivel.	X	
Wheel and casters fail to bear evenly on a flat surface.	X	
Weld missing, fractured, or incomplete fusion.	X	
Porosity or undercut in welds.		X
Burn holes or pils.		X

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:08Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect, illegible, improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate staping, or distortion of container.
Contents	Number per container is more or less than required. Net weight exceeds requirements of the box specification.

4.4 Tests.

4.4.1 Acceptance. The AQL shall be 1 (one) percent in accordance with MIL-STD-105.

4.4.2 Stability. Handcarts shall be tested for stability and operation by loading it four times its actual weight. The loaded handcart shall be wheeled about in all directions on a smooth level floor by gradually applying a force in a horizontal direction against the handle and then the upper basket in compliance with 3.2.4.3.

4.4.3 Capacity. The size shall be determined by the grain measure level full method to determine compliance with the size in 1.2.2 and 3.2.7. The basket shall be lined with a thin material to hold grain. The basket shall then be filled with grain level full with the top edge of the basket. The capacity in cubic inches shall be determined by measuring the grain into a container of known cubic dimension.

4.4.3.1 Unless otherwise specified (see 6.2), the test for copacity (4.4.3) shall be required in the initial delivery and therafter only when the manufacturer's basic design has been changed.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Handcarts shall be packaged in accordance with MIL-P-116, method III.

5.1.2 Level C. The handcarts shall be packaged to insure protection for the handcart during shipment and provides for safe delivery to its destination.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Handcarts packaged as specified in 5.1 shall be individually packed in close-fitting boxes conforming to PPP-B-636, class weather-resistant or to PPP-B-640, class 2. Close, waterproof seal and secure all boxes in accordance with the appendix to the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:08Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Handcarts packaged as specified in 5.1 shall be individually packed in close-fitting boxes conforming to PPP-B-636, grade 200 minimum. Closure of boxes shall be in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. The handcarts packaged as specified in 5.1 shall be packed to comply with the National Motor Freight Classification rules or the Uniform Freight Classification rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or purchase order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. All marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Handcarts are intended for use in self-service establishments, for conveying food, and small household and similar items.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of handcart (see 1.2.1).
(c) Size of handcart.
(d) Bumpers, when required and type of material.
(e) Personalized marking when required (see 3.6).
(f) If rear casters are to be swivel type (see 3.2.5).
(g) Size of lot, if different from 4.2.1.

6.3 Cross reference data. Cross reference of classification changes between this specification and the preceding Federal specification, RR-H-40A dated July 28, 1966 are as follows:

RR-H-40A	RR-H-40B
Type I	Deleted
Type II	None
Type III	Deleted
Type IV	None
Type V	None
Type VI	None

MILITARY INTERESTS:

DOD has waived coordinating on revisions and amendments to this Federal Specification until further notice.

User interest:

Army - GL

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.