MILITARY SPECIFICATION SHEET

CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, FLANGE AND MOUNTED)

This amendment forms a part of Military Specification Sheet MIL-C-83517/11, dated 20 September 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE: Delete and substitute new title as printed in this amendment.

PAGE 8

ENGINEERING PARAMETERS, Voltage rating. Delete "600 Vrms maximum at sea level" and substitute "335 Vrms maximum at sea level".

PAGE 10

Voltage standing wave ratio (VSWR), Step 4: Delete "(1.05+.005f)" and substitute "1.35 +.01 F (F in GHz)".

RF transmission loss: Delete "(0.15 dB MAX @ 6 GHz)" and substitute ".07 $\sqrt{F}$ (tested from 2-18 GHz, F in GHz)".

RF high potential withstanding voltage, RF voltage: Delete "1,000 Vrms" and substitute "670 Vrms".

PAGE 11

Add the following before concluding material:

"Patent Notice The Government has been offered a royalty free license under the U.S. Patent listed below for the benefit of manufacturers of the items disclosed and described herein, either for the Government or for use in equipment delivered to the Government.

Patent number 4175308 expires November 1995 "

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities
Army - AR, AT, MI
Navy - AS, SH
Air Force - 11, 99
DLA - ES

User activities
Navy - MC
Air Force - 19

Agent.
DLA - ES

Preparing activity:
Air Force - 85

(Project 5935-3446-11)

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:33Z
Check the source to verify that this is the current version before use.