INCH-POUND

MIL-DTL-83517/13
w/AMENDMENT 1
21 April 2015
SUPERSEDING
MIL-DTL-83517/13
2 September 2005

DETAIL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA, (SOCKET CONTACT) FEEDTHROUGH, HERMETIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83517.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parenthesis
4. All undimensioned pictorial configurations are for reference purposes only.
5. Unless otherwise specified, all tolerances shall be ±.005 inch (± 0.13mm).

FIGURE 1. Series SMA, Feedthrough, Hermetic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:33Z
Check the source to verify that this is the current version before use.

ENGINEERING PARAMETERS:

Nominal impedance: 50 ohms.

Voltage rating: 600 V rms maximum at sea level.
150 V rms maximum at 70,000 feet.

Frequency range: 0 to 18.0 GHz.

Temperature rating: -65° to +105°C.

REQUIREMENTS:

Design and construction: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: Not applicable.
Torque: 2 inch pounds, maximum.

Coupling proof torque: Not applicable.

Permeability: Not Applicable.

Hermetic seal: Leakage shall not exceed 1×10^{-5} cubic centimeters per second of tracer gas at atmospheric pressure when mounted in mounting hole.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: 5,000 megohms minimum, in accordance with test procedure EIA/ECA-364-21.

Center contact retention:

Axial force: 6 pounds minimum.

Torque: Not applicable.

Dielectric withstanding voltage: In accordance with test procedure EIA 364-20, test condition I.

Test voltage 1,000 V rms.

Vibration, high frequency: MIL-STD-202, method 204, condition D.

Corona level:

Altitude: 70,000 feet, 375 volts, minimum.

Shock: MIL-STD-202, method 213. The acceleration shall be 200'Gs.

Corrosion: In accordance with test procedure EIA/ECA-364-26, test condition B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:33Z
Check the source to verify that this is the current version before use.

Voltage standing wave ratio (VSWR):

1.05 +.01 F (F in GHz), maximum. From .5 to 18.0 GHz.

RF transmission loss: $.07 \sqrt{F \text{ (F in GHz)}}$, tested 2-18 GHz.

RF leakage: Not applicable.

Connector durability: 500 cycles minimum, at 12 cycles per minute maximum. The connector shall meet the mating characteristics arid force to engage and disengage requirements

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact:	10.0	10.0
Outer contact:	2.0	Not applicable

Thermal shock: Applicable, MIL-STD-202, method 107, test condition A.

Moisture resistance: Method 106 of MIL-STD-202.

No measurements at high humidity. Insulation resistance, except step 7b shall be omitted.

RF high potential withstanding voltage:

500 Volts at 5 MHz.

Leakage current: Not applicable.

RF leakage: -90 dB from 0 to 8 GHz.

RF insertion loss: 0.10 dB maximum at 6 GHz.

Barometric pressure (reduced): MIL-STD-202, method 105, test condition C. The connector shall not exhibit breakdown (corona) when the applied voltage is 250 volts rms at 70,000 feet.

Coupling mechanism retention force: Not applicable.

Part or Identifying Number (PIN): M83517/13-30001

Supersession: This document will supersede DSCC drawing 87036 once a qualified source in obtained.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:33Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-83517, this document references to the following:

MIL-STD-202
MIL-STD-348
EIA 364-20
EIA/ECA-364-21
EIA/ECA-364-26

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA – CC

(Project 5935-2015-143)

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:33Z
Check the source to verify that this is the current version before use.