MILITARY SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY,
STRIP OR MICROSTRIP TRANSMISSION LINE,
SERIES SMA (PIN CONTACT, FLANGE MOUNTED TAB TERMINAL)

This amendment forms a part of Military Specification Sheet MIL-C-83517/2, dated 20 September 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE: Delete and substitute new title as printed in this amendment.

PAGE 4

ENGINEERING PARAMETERS, Voltage rating: Delete "600 Vrms maximum at sea level" and substitute "335 Vrms maximum at sea level".

PAGE 5

Voltage standing wave ratio (VWSR), Step 4: Delete "(to be determined)" and substitute "1.35 +.01 F (F in GHz)".

RF transmission loss: Delete "(to be determined)" and substitute ".07$\sqrt{F}$ (tested from 2-18 GHz, F in GHz)".

RF high potential withstanding voltage, RF voltage: Delete "1,000 Vrms" and substitute "670 Vrms".

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, MI
Navy - AS, SH
Air Force - 11, 99
DLA - ES

User activities:
Navy - MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5935-3446-02)

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:31Z
Check the source to verify that this is the current version before use.