INCH-POUND


MIL-DTL-83517/6A
31 May 2005
SUPERSEDING
MIL-C-83517/6
20 September 1982

DETAIL SPECIFICATION SHEET

CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, 8 HOLE SURFACE LAUNCH)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-C-83517.



Part of Identifying Number (PIN)	"A" dim.	Transmission line thickness
M83517/6-31001	.060 ± .003	.125
M83517/6-31002	.120 ± .003	.250

Inches	mm	Inches	mm
.001	.03	.072	1.83
.002	.05	.085	2.16
.003	.08	.086	2.18
.004	.10	.120	3.05
.005	.13	.125	3.18
.010	.25	250	6.35
.050	1.27	.375	9.53
.060	1.52	.438	11.13
		.570	14.48

FIGURE 1. Series SMA, socket contact, surface launch, receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. All undimensioned pictorial configurations are for reference purposes only.
4. Number two screws are suggested for mounting.

FIGURE 1. Series SMA, socket contact, surface launch, receptacle – Continued.

ENGINEERING PARAMETERS

Nominal impedance: 50 ohms.

Voltage rating: 335 Vrms maximum at sea level.
150 Vrms maximum at 70,000 feet.

Frequency range: 0 to 12.4 GHz.

Temperature rating: -65º to 105ºC.

REQUIREMENTS:

Design and construction: See figure 1, table I and MIL-STD-348.

Force to engage and disengage:

Torque – 2 inch-pounds maximum.
Longitudinal force – Not applicable.

Coupling proof torque: Not applicable.

Inspection note: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Contact gaging: See figure 2.

Contacts with spring members:

Center contact (socket):

Oversize test pin - .0375 +.0001.
Test pin finish – 16 microinches.
Insertion depth - .030/.045.
Number of insertions – 3.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Insertion force test: Steel test pin diameter .0370 + .0001.

Insertion depth - .050/.075.
Test pin finish – 16 microinches.
Insertion force – 3 pounds maximum.

Withdrawal force test: Steel test pin diameter .0355 - .0001.

Insertion depth - .050/.075.
Withdrawal force – 1 ounce minimum.
Test pin finish – 16 microinches.



Inches	mm
.015	0.38

FIGURE 2. Test pin data.

TABLE I. PIN and characteristics.

PIN M83517/6-	Connector figure no.	Characteristics
31001	1	Strip transmission line surface launch, receptacle for .125 inch (3.18 mm) strip transmission line
31002	1	Strip transmission line surface launch, receptacle for .250 inch (6.35 mm) strip transmission line.

Permeability of nonmagnetic materials: Applicable.

Seal:

Hermetic sealed connectors: Not applicable.
Pressurized and weatherproof connectors: Not applicable.

Insulation resistance: 5,000 megohms minimum in accordance with test procedure EIA-364-21.

Center contact retention:

Axial force: Not applicable.
Torque: Not applicable.

Dielectric withstanding voltage: In accordance with test procedure EIA-364-20, test condition I.

Test voltage 1,000 V rms.

Corrosion: In accordance with test procedure EIA-364-26, test condition B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Voltage standing wave ratio (VSWR): 1.35 +.01F (F in GHz), maximum.

Test frequency range: From .5 to 18.0 GHz. (Using a test method approved by the qualifying activity.)

RF transmission loss: $.07\sqrt{F \text{ (F in GHz)}}$ tested from 2-18 GHz.

RF leakage: Not applicable.

Connector durability:

Interface:

500 cycles minimum at 12 cycles/minute maximum rate.
Connector shall meet contact gaging and force to engage and disengage requirements.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact:	3.0	4.0
Outer contact:	2.0	Not applicable

Thermal shock: Applicable, test condition A.

Moisture resistance: Method 106 of MIL-STD-202.

No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

RF high potential withstanding voltage:

At a frequency between 5 to 7.5 MHz.
Leakage current – Not applicable.
RF voltage – 670 V rms.

Coupling mechanism retention force: Not applicable.

PIN: M83517/6-(dash number from table I.)

Group qualification: See table II.

TABLE II. Group qualification.

Group	Submission and qualification of any of the following connectors 1/2/ M83517/6-	Qualifies the following connectors M83517/6-
1	3+001	3+001 3+002

1/ Individual connectors other than listed are self qualifying only.
2/ Qualification of connectors, qualifies connectors of the same material only.
+ Denotes finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-C-83517, this document references the following:

MIL-STD-202
MIL-STD-348
EIA-364-20
EIA-364-21
EIA-364-26

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA – CC

(Project 5935-4608-006)

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.