INCH-POUND


MIL-DTL-83517/7A
31 May 2005
SUPERSEDING
MIL-C-83517/7
20 September 1982

DETAIL SPECIFICATION SHEET

# CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (PIN CONTACT, 8 HOLE SURFACE LAUNCH)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-C-83517.




| Part or Identifying Number (PIN) | "A" dim. | Transmission line thickness |
|---|---|---|
| M83517/7-31001 | .060±.003 | .125 |
| M83517/7-31002 | .120±.003 | .250 |

FIGURE 1. Series SMA, pin contact, surface launch, receptacle.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. All undimensioned pictorial configurations are for reference purposes only.

| INCHES | MM | INCHES | MM |
|---|---|---|---|
| .001 | .03 | .085 | 2.16 |
| .002 | .05 | .120 | 3.05 |
| .003 | .08 | .125 | 3.18 |
| .004 | .10 | .250 | 6.35 |
| .005 | .13 | .390 | 9.91 |
| .010 | .25 | .4375 | 11.11 |
| .050 | 1.27 | .438 | 11.13 |
| .068 | 1.73 | .528 | 13.41 |
| .072 | 1.83 | .570 | 14.48 |

FIGURE 1. Series SMA, pin contact, surface launch, receptacle – Continued.

ENGINEERING PARAMETERS

Nominal impedance: 50 ohms.

Voltage rating: 335 V rms maximum at sea level.
150 V rms maximum at 70,000 feet.

Frequency range: 0 to 12.4 GHz.

Temperature rating: -65º to 105ºC.

REQUIREMENTS

Design and construction: See figure 1, table I and MIL-STD-348.

Force to engage and disengage:

Torque – 2 inch-pounds maximum.
Longitudinal force – Not applicable.

Coupling proof torque: 15 inch-pounds minimum.

Inspection note: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

TABLE I. PIN and characteristics.

| PIN M83517/7- | Connector figure no. | Characteristics |
|---|---|---|
| 31001 | 1 | Strip transmission line surface launch, receptacle for .125 inch (3.18 mm) strip transmission line. |
| 31002 | 1 | Strip transmission line surface launch, receptacle for .250 inch (6.35 mm) strip transmission line. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Permeability of nonmagnetic materials: Applicable.

Seal:

Hermetic sealed connectors: Not applicable.
Pressurized and weatherproof connectors: Not applicable.

Insulation resistance: 5,000 megohms minimum in accordance with test procedure EIA-364-21.

Center contact retention:

Axial force: Not applicable.
Torque: Not applicable.

Dielectric withstanding voltage: In accordance with test procedure EIA-364-20, test condition I.

Test voltage 1,000 V rms.

Corrosion: In accordance with test procedure EIA-364-26, test condition B.

Voltage standing wave ratio (VSWR): 1.35 +.01F (F in GHz), maximum.

Test frequency range: From .5 to 18.0 GHz. (Using a test method approved by the qualifying activity.)

RF transmission loss: $.07\sqrt{F \text{ (F in GHz)}}$ tested from 2-18 GHz.

RF leakage: Not applicable.

Connector durability:

Interface:

500 cycles minimum at 12 cycles/minute maximum rate.
Connector shall meet contact gaging and force to engage and disengage requirements.

Contact resistance: In milliohms maximum.

| | Initial | After environment |
|---|---|---|
| Center contact: | 3.0 | 4.0 |
| Outer contact: | 2.0 | Not applicable |

Thermal shock: Applicable, test condition A.

Moisture resistance: Method 106 of MIL-STD-202.

No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

RF high potential withstanding voltage:

At a frequency between 5 to 7.5 MHz.
Leakage current – Not applicable.
RF voltage – 670 V rms.

Coupling mechanism retention force: 60 pounds minimum.

PIN: M83517/7-(dash number from table I.)

Group qualification: See table II.

TABLE II. Group qualification.

| Group | Submission and qualification of any of the following connectors 1/ 2/ M83517/7- | Qualifies the following connectors M83517/7- |
|---|---|---|
| 1 | 3+001 | 3+001<br>3+002 |

1/ Individual connectors other than listed are self qualifying only.
2/ Qualification of connectors, qualifies connectors of the same material only.
+ Denotes finish.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-C-83517, this document references the following:

MIL-STD-202
MIL-STD-348
EIA-364-20
EIA-364-21
EIA-364-26

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA – CC

(Project 5935-4608-007)

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.