MIL-C-39022/4A(USAF)
AMENDMENT 3
3 June 1983
SUPERSEDING
AMENDMENT 2
5 November 1979

MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED, PAPER-PLASTIC FILM
DIELECTRIC, DIRECT CURRENT,
(HERMETICALLY SEALED IN METAL CASES),
ESTABLISHED RELIABILITY,
STYLE CHR29 (INSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39022/4A(USAF), dated 4 November 1970, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under the procurement note, insert the following:

" THIS SPECIFICATION INACTIVE FOR NEW DESIGN AFTER 12 JUNE 1978. USE MIL-C-83421/1. "

* FIGURE 1, NOTE 1: Delete and substitute:

"1. Number 22 AWG wire (.025 inch ±.002) for case diameters of .360 (9.14 mm) and under.
Number 20 AWG wire (.032 inch ±.002) for case diameters over .360 (9.14 mm)."

FIGURE 1, NOTES, after note 6, add the following:

"7. Lead length may be a minimum of 1-inch long for use in tape and reel packaging when specified in the ordering data."

PAGE 3

Temperature cycling, delete in its entirety and substitute "Thermal shock: Method 107 of MIL-STD-202, condition A."

NOTE: The margin of this amendment is marked with an asterisk to indicate where the change (addition) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:
Air Force - 17

Review activities:
Air Force - 11, 99

Agent:
DLA - ES

Preparing activity:
Air Force - 11

(Project 5910-F390-1)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:14Z
Check the source to verify that this is the current version before use.