MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC FILM DIELECTRIC, DIRECT AND ALTERNATING CURRENT, (HERMETICALLY SEALED IN METAL CASES), ESTABLISHED RELIABILITY
STYLES CHR01A, CHR01B, CHR01C, CHR01D, CHR01E, CHR01F, CHR01G, CHR01H, CHR01J, CHR01K, CHR01L, CHR01M, CHR01N, CHR01P, AND CHR01R (INSULATED)

This amendment forms a part of MIL-C-39022/9C(USAF), dated 31 October 1973, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Note 1, delete and substitute:

"1. Number 22 AWG wire (.025 inch ±.002) for case diameters of .312 (7.92 mm) and less.
Number 20 AWG wire (.032 inch ±.002) for case diameters of .400 (10.16 mm) and .500 (12.70 mm).
Number 18 AWG wire (.040 inch ±.002) for case diameters of .562 (14.27 mm) and over."

FIGURE 1, NOTES, add new note 8 as follows:

"8. Lead length may be a minimum of one inch long for use in tape and reel packaging, when specified in the ordering data."

REQUIREMENTS, Leads and Operating temperature range, delete in their entirety and substitute the following:

"Leads:

.500 inch and smaller case diameters: Solder-coated copper clad steel. Type N2 of MIL-STD-1276 may be furnished when specified in the contract or purchase order (see MIL-C-39022 ordering data).
.562 inch and larger case diameters: Type C of MIL-STD-1276."

"Operating temperature range: -55°C to +100°C; linearly derate to 50 percent of rated voltage for +125°C operating."

PAGE 6

* TABLE II, Cap. change with temp. (max):, delete and substitute:

"

Measurement Cap. change with temp. (max):	CHR01A, CHR01B, CHR01D, CHR01E, CHR01G, CHR01H, CHR01K, CHR01L, CHR01N, and CHR01P	CHR01C, CHR01F, CHR01J, CHR01M, and CHR01R
At -55°C	-2.5 percent to 0 percent	-2.5 percent to 0 percent
At +25°C (retrace)	±.25 percent	±.25 percent
At +125°C	-1.0 percent to +1.2 percent	±2.0 percent

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:15Z
Check the source to verify that this is the current version before use.

PAGE 7

Seal, delete and substitute:

"Seal: Method 112 of MIL-STD-202, test condition C, procedure IIIA; no evidence of leakage with the exception of the following:

Styles	lbf/in^2	Exposure time hours	Maximum dwell hours	R1 Reject limit (atm cm^3/s)
CHR01A, CHR01B, CHR01D, CHR01E, CHR01G, CHR01H, CHR01K, CHR01L, CHR01N, and CHR01P	45 ±5	1 +1-0	1	1 x 10^{-6}
CHR01C, CHR01F, CHR01J, CHR01M, and CHR01R	45 ±5	1 +1-0	1	1 x 10^{-5}

Failure rate level "L": At 25°C, immerse in isopropyl alcohol; check for continuous bubble stream."

PAGE 9

EXAMPLE OF MARKING, line 1: Delete "M39022/09-" and substitute "M39022/9-".

Following marking add:

"Packaging: Capacitors shall be furnished in tape and reel packaging when so specified in the ordering data."

NOTE: The margins of this amendment are marked with an asterisk to indicate where the changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-F430)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:15Z
Check the source to verify that this is the current version before use.