MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED, PAPER-PLASTIC FILM
DIELECTRIC, DIRECT CURRENT,
(HERMETICALLY SEALED IN METAL CASES),
ESTABLISHED RELIABILITY,
STYLE CHR19 (INSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39022/2C, dated 12 October 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Following title, insert: "|FAILURE RATE LEVEL 'L' IS INACTIVE|
|FOR DESIGN AFTER 20 July 1983 .|"

* NOTE 1, delete and substitute:

"1. Number 22 AWG wire (.025 inch ±.002) for case diameters of .312 (7.92 mm). Number 20 AWG wire (.032 inch ±.002) for case diameters over .312 (7.92 mm)."

FIGURE NOTES, after note 7, add the following:

"8. Lead length may be a minimum of 1-inch long for use in tape and reel packaging when specified in the ordering data."

NOTE: The margin of this amendment is marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC, OS, SH, CG
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1536-1)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:13Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.