MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, PLASTIC DIELECTRIC (METALLIZED PLASTIC FILM), ALTERNATING CURRENT (RMS) (HERMETICALLY SEALED IN METAL CASES) ESTABLISHED RELIABILITY, STYLE CHR49 (UNINSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39022/7C, dated 19 July 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, column 4, line 10, delete "1.355" and substitute "1.375".
TABLE I, column 4, line 11, delete "1.355" and substitute "1.375".
TABLE I, column 6, line 11, delete "1195" and substitute "1196".
TABLE I, column 7, line 11, delete "1215" and substitute "1216".
TABLE I, column 8, line 12, delete "1336" and substitute "1335".

PAGE 6

TABLE IV, column 1, line 25, delete "1304" and substitute "1340".

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC, OS, SH, CG
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1521)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:14Z
Check the source to verify that this is the current version before use.