MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED, PAPER-PLASTIC FILM
DIELECTRIC, DIRECT CURRENT,
(HERMETICALLY SEALED IN METAL CASES),
ESTABLISHED RELIABILITY,
STYLE CHR12 (UNINSULATED)

This amendment forms a part of MIL-C-39022/8B, dated 14 February 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following title, add: "FAILURE RATE LEVEL 'L' IS INACTIVE FOR DESIGN AFTER 20 July 1983 ."

NOTE 1, delete and substitute:

"1. Number 22 AWG wire (.025 inch ±.002) for case diameters of .312 (7.92 mm). Number 20 AWG wire (.032 inch ±.002) for case diameters over .312 (7.92 mm)."

*Add the following note:

"6. The centerline of the mounting clamp shall be within .050 inch (1.27 mm) of the centerline of the length (L dimension) of the capacitor."

PAGES 3 THROUGH 9

TABLE I, dimensions, nominal (inches) 1/, add: "±" to the tolerances.

PAGE 4

TABLE I, entries "14 through 21", delete and substitute (for 1.5 and 1.8 Capacitance values):

Data for entries 14 through 21.

DC rated voltage	Capacitance value	Circuit diagram	Capacitance tolerance	Dimensions, nominal (inches) 1/						Dash number Failure rate level for (%/1,000 hr)				
				L ±.062	D ±.031	H ±.062	G ±.062	E ±.031	F ±.005	L (5.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
Volts	µF		Percent (±)											
50	1.5	1	5	1.125	0.500	0.438	0.500	0.250	0.156	2049	2149	2249	2349	2449
50	1.5	1	10	1.125	0.500	0.438	0.500	0.250	0.156	2050	2150	2250	2350	2450
50	1.5	3	5	1.062	0.500	0.438	0.500	0.250	0.156	2051	2151	2251	2351	2451
50	1.5	3	10	1.062	0.500	0.438	0.500	0.250	0.156	2052	2152	2252	2352	2452
50	1.8	1	5	1.375	0.500	0.438	0.500	0.250	0.156	2053	2153	2253	2353	2453
50	1.8	1	10	1.375	0.500	0.438	0.500	0.250	0.156	2054	2154	2254	2354	2454
50	1.8	3	5	1.312	0.500	0.438	0.500	0.250	0.156	2055	2155	2255	2355	2455
50	1.8	3	10	1.312	0.500	0.438	0.500	0.250	0.156	2056	2156	2256	2356	2456

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:15Z
Check the source to verify that this is the current version before use.

PAGE 8

TABLE I, entries "25 through 28", delete and substitute (for 0.10 Capacitance value):

Data for entries 25 through 28.

DC rated voltage	Capacitance value	Circuit diagram	Capacitance tolerance	Dimensions, nominal (inches) 1/ L ±.062	D ±.031	H ±.062	G ±.062	E ±.031	F ±.005	Dash number Failure rate level for (%/1,000 hr) L (5.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
Volts	µF		Percent (±)											
600	0.10	1	10	1.125	0.500	0.438	0.500	0.250	0.156	1085	1205	1325	1445	1565
600	0.10	1	20	1.125	0.500	0.438	0.500	0.250	0.156	1086	1206	1326	1446	1566
600	0.10	3	10	1.062	0.500	0.438	0.500	0.250	0.156	1087	1207	1327	1447	1567
600	0.10	3	20	1.062	0.500	0.438	0.500	0.250	0.156	1088	1208	1328	1448	1568

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC, OS, SH, CG
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1660)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:15Z
Check the source to verify that this is the current version before use.