INCH-POUND
MIL-PRF-39023B
AMENDMENT 2
24 November, 2000
SUPERSEDING
AMENDMENT 1
24 March, 2000

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND, PRECISION
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-39023B, dated 1 February 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 10

* 3.31, delete and substitute:

"3.31 Salt spray (corrosion). When resistors are tested as specified in 4.7.27, the units shall be disassembled and inspected. There shall be no appreciable corrosion."

PAGE 16

* TABLE XI, delete and substitute:

"TABLE XI. Group A inspection.

Inspection	Requirement paragraph	Method paragraph	Sampling plan
Dimensions	3.1	4.7.1	
Lateral runout	3.7	4.7.3	
Shaft runout	3.8	4.7.4	
Pilot diameter runout	3.9	4.7.5	
Shaft radial play	3.10	4.7.6	
Shaft end play	3.11	4.7.7	
Torque	3.13	4.7.9	
Marking	3.33	4.7.1	
Workmanship	3.35	4.7.1	See 4.6.2.1
DC resistance	3.6	4.7.2	
Taps (when applicable)	3.14	4.7.10	
Dielectric withstanding voltage	3.15	4.7.11	
Insulation resistance	3.16	4.7.12	
Functional conformity tolerance	3.17	4.7.13	
Mechanical backlash	3.18	4.7.14	
End voltage	3.20	4.7.16	
Output smoothness	3.21	4.7.17	
Terminal strength	3.22	4.7.18	

"

4.6.2.1, line 2, delete "table XI" and substitute "table XII".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:17Z
Check the source to verify that this is the current version before use.

TABLE XIII, Sampling plan, delete "4.6.1.3.1" and substitute "4.6.3.1".

* 4.6.4.1, delete and substitute:

"4.6.4.1 Disposition of sample units. Sample units which have passed all the Group B inspection may be delivered on the contract or order."

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5905-1603)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19, 80

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:17Z
Check the source to verify that this is the current version before use.