NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/37B
30 September 1996
SUPERSEDING
MIL-R-41819/37A
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, DISTINGUISHED MARKSMAN, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Gilding Metal

DIMENSIONS:
HEIGHT: 1/4 inch (0.64 cm) (REF)
WIDTH: 1/4 inch (0.64 cm) (REF)
THICKNESS (At Thickest Point): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)

FINISH: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled color shall be black as indicated. The enamel color shall conform to TIOH chip number 26 or the standard sample.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:58Z
Check the source to verify that this is the current version before use.

4. The attaching device shall be a staple type prong. The prong shall be centered on the reverse side of the ribbon attachment.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:58Z
Check the source to verify that this is the current version before use.