A-A-53322
26 February 1988

COMMERCIAL ITEM DESCRIPTION

SLING, HEAD

The General Services Administration has authorized the use of this Commercial Item Description.

This Commercial Item Description covers a disposable head sling suitable for use with a spreader bar and appropriate weights to provide cervical traction for patients in transit.

Salient characteristics:

The head sling shall be a universal size, readily adjustable to fit the patient. The sling shall consist of two foam pads covered with white flannel, mounted on two closed loops of rope.

A foam strip, 2-1/2 inches ± 1/8 inch wide by 11-3/8 inches ± 1/4 inch long with a nominal thickness of 1/4 inch shall be used to form each pad. The unfolded dimensions of the unfolded flannel used to cover the foam shall be 12-1/2 inches ± 1/2 inch long by 6-1/4 inches ± 1/2 inch wide.

All sides of the flannel piece shall be folded back 1/4 inch ± 1/16 inch, then wrapped around the foam pad and sealed by means of an adhesive or stitching. The ends of the flannel shall then be folded over the ends of the pad and stitched to the pad. The flannel covered pad shall then be folded back, approximately 1-1/2 inches at each end, and stitched to form a double thickness of flannel covered pad in that area. The dimensions of the finished head sling pad shall be 2-1/2 inches ± 1/8 inch wide and 7-3/4 inches ± 1/4 inch long.

Two braided closed loops of rope, a nominal 9/64 inch in rope diameter and 23 inches ± 1/2 inch in loop circumference, shall be threaded through each end loop of the head sling pad. The braided rope shall be multifilament 2520/420 denier with a minimum 340 pound breaking strength, or equal. The ends of the rope shall be closed by a plastic seal, heat seal or other suitable method.

AMSC N/A FSC 6530

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

Head sling stitching shall be lock stitch, type 301, with 6 to 10 stitches per inch. Thread breaks shall be backstitched not less than 1/2 inch. The thread for stitching shall be nylon number 50, or equal. Stitching shall be uniform. The sling shall have no raw edges. Thread ends shall be trimmed throughout.

The head sling shall support a minimum weight of 75 pounds, spread uniformly over the area between the stitching of the pad, without any visible evidence of damage.

The design of the head sling shall prevent pressure on the neck, carotid artery, or nerves.

The sling shall have no mend, patch, burn, or needle chew. The sling shall be clean.

Workmanship. The head sling shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Each (EA). One head sling, as specified, constitutes one unit.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, with an AQL of 1.0 (percent defective) and an inspection level of II. The unit of product for examination purposes shall be one complete head sling as specified in this description.

Defects.

Any component missing, misplaced, or not as specified.

Any operation omitted or not properly performed.

Color not as specified.

Closed loops damaged.

Any mend, patch, burn, or needle chew.

Wrong seam or stitch type.

Open seam, more than 1/4 inch.

Raw edge, more than 1/2 inch.

Incorrect number or stitches per inch.

Head sling not clean.

Abrasion marks on head sling pad or ropes.

Stitching not uniformly gauged.

Thread breaks backstitched less than 1/2 inch.

Thread ends not trimmed throughout.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

Sampling for tests. Sampling for tests including dimensional test, shall be conducted in accordance with MIL-STD-105, with an AQL of 2.5 (percent defective) and inspection level of S-1. The unit of product for test purposes shall be one head sling.

Tests.

Test for fit

One head sling shall be placed on an individual's head. The head sling shall be examined for fit and compliance with the requirement to accept an orthopedic style spreader bar on the two closed loops of rope.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580, as amended, and as implemented by Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document:

6530-00-117-9012

Note: The head sling shall be compatible with a 12 inch spreader bar, NSN, 6530-00-926-9066, and a 9 inch spreader bar, NSN 6530-00-926-9067.

Ordering data. Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and/or order.

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

PREPARING ACTIVITY:

DoD - MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
PHS
FDA-MPQAS

Project No. 6530-1974

PGC 50012

Location: CID/SLING/H13-29

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-ATTS
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2 DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:18Z
Check the source to verify that this is the current version before use.