INCH-POUND

MIL-C-28876/27C
AMENDMENT 1
04 MAY 1995

MILITARY SPECIFICATION SHEET

CONNECTORS, FIBER OPTIC, CIRCULAR, PLUG AND RECEPTACLE STYLE,
MULTIPLE REMOVABLE TERMINI, SCREW THREADS,
STRAIGHT BACKSHELL, STRAIN RELIEF, ENVIRONMENT RESISTING

This amendment forms a part of MIL-C-28876/27C, dated 9 July 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "STRAIN RELIEF".

FIGURE 1: Delete "STRAIN RELIEF BACKNUT" and substitute "BACKSHELL BACKNUT".

FIGURE 1: Delete "BACKSHELL COUPLING NUT" and substitute "BACKSHELL COUPLING RING".

FIGURE 1, title: Delete "Backshell with strain relief" and substitute "Straight backshell".

PAGE 2

FIGURE 1, table, dimension B maximum: Delete "1.03 (26.2)" (two places) and substitute "30.5 (1.20)" (two places).

FIGURE 1, table, dimension B maximum: Delete "1.15 (29.2)" (two places) and substitute "30.5 (1.20)" (two places).

FIGURE 1, table: Add the following row to the table:

"

23	F	1, 2, 3	165.10 (6.500)	57.15 (2.250)	See table I	See table I

"

FIGURE 1: Add the following Note:

"7. Backshell internal configuration not shown. The backshell interface dimensions shall be in accordance with figure 10 of MIL-C-28876."

REQUIREMENTS, temperature: Delete in its entirety.

REQUIREMENTS, fiber optic cable, cable diameter: Delete and substitute:

"Cable diameter: 8.00 ± 0.50 mm (0.315 ± 0.020 inch), 11.80 ± 1.10 mm (0.425 ± 0.043 inch), or 20.75 ± 1.25 mm (.817 ± .049 inch) (see MIL-C-85045/13, MIL-C-85045/15, MIL-C-85045/17, and MIL-C-85045/18)."

REQUIREMENTS, cleaning procedures: Delete and substitute:

"Cleaning procedures: Each shipment of backshells shall include recommended cleaning procedures. The following wording or equivalent is recommended "To clean, use wipe dampened with alcohol and blow dry with air"."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T20:36Z
Check the source to verify that this is the current version before use.

PAGE 3

REQUIREMENTS, marking: Delete "coupling nut" and substitute "coupling ring".

TABLE I: Delete and substitute the following:

"TABLE I. Pin designators.

Shell size	Designator	Backshell dash number	Dimension C cable range	Dimension D maximum
11	A	1L, 1	6.09 - 6.35 (.240 - .250)	20.32 (.800)
		2L, 2	7.11 - 8.00 (.280 - .315)	23.50 (.925)
		3L, 3	7.75 - 8.80 (.305 - .346)	23.50 (.925)
13	B	1L, 1	7.11 - 8.00 (.280 - .315)	23.50 (.925)
		2L, 2	7.75 - 8.80 (.305 - .346)	23.50 (.925)
15	C	1L, 1	12.57 - 13.08 (.495 - .515)	27.94 (1.10)
		2L, 2	9.65 - 10.74 (.380 - .423)	23.50 (.925)
		3L, 3	10.75 - 11.81 (.423 - .465)	27.94 (1.10)
		4L, 4	7.75 - 8.80 (.305 - .346)	23.50 (.925)
23	F	1	19.50 - 22.00 (.768 - .866)	38.10 (1.500)
		2	22.86 - 25.40 (.900 - 1.000)	38.10 (1.500)

"

PAGE 4

Delete "CONCLUDING MATERIAL" and substitute as printed herein.

"CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - SH
Air Force - 85
NASA - NA

Review activities:
Army - MI
Navy - AS, MC, OS, YD
Air Force - 13, 14, 17, 19, 80, 90, 99
DLA - ES"

Preparing activity:
Navy - SH

Agent:
DLA - ES

(Project 6060-0115-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:36Z
Check the source to verify that this is the current version before use.