MILITARY SPECIFICATION

RELAYS, HYBRID OR SOLID STATE,
SENSORS, ESTABLISHED RELIABILITY

GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification
MIL-R-28894, dated 10 April 1986.

SPECIFICATION SHEETS

MIL-R-28894/1	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Vertical Mount
MIL-R-28894/2	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Horizontal Mount
MIL-R-28894/3	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Inverted Mount
MIL-R-28894/4	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Horizontal Mount With Connector Termination
MIL-R-28894/5	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 3PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Vertical Mount
MIL-R-28894/6	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 3PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Horizontal Mount
MIL-R-28894/7	-	Relays, Hybrid, Sensors, Established Reliability, Type I, Class B, (Hybrid AC Power Monitoring Sensor), 3PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted), Inverted Mount
MIL-R-28894/8	-	Relays, Hybrid, Sensors, Established Reliability, Type II, Class B, (Hybrid DC Voltage Sensor), 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)
MIL-R-28894/9	-	Relays, Hybrid, Sensors, Established Reliability, Type II, Class B, (Hybrid DC Voltage Sensor), 4PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)
MIL-R-28894/10	-	Relays, Hybrid, Sensors, Established Reliability, Type III, (AC Undervoltage Sensor), Class B, 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)
MIL-R-28894/11	-	Relays, Hybrid, Sensors, Established Reliability, Type III, (AC Undervoltage Sensor), Class B, 4PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)
MIL-R-28894/12	-	Relays, Hybrid, Sensors, Established Reliability, Type III, (AC Overvoltage Sensor), Class B, 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)
MIL-R-28894/13	-	Relays, Hybrid, Sensors, Established Reliability, Type III, (AC Overvoltage Sensor), Class B, 4PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:45Z
Check the source to verify that this is the current version before use.

MIL-R-28894/14 - Relays, Hybrid, Sensors, Established Reliability, Type IV, (Under/Over Frequency Sensor), Class B, 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)

MIL-R-28894/15 - Relays, Hybrid, Sensors, Established Reliability, Type IV, (Under/Over Frequency Sensor), Class B, 4PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)

MIL-R-28894/16 - Relays, Hybrid, Sensors, Established Reliability, Type V, (AC Phase Sequence Sensor), Class B, 2PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)

MIL-R-28894/17 - Relays, Hybrid, Sensors, Established Reliability, Type V, (AC Phase Sequence Sensor), Class B, 4PDT, Low Level to 10 Amperes, Hermetically Sealed (Potted)

MIL-R-28894/18 - Relays, Solid State, Sensors, Established Reliability, Type II, (DC Undervoltage Sensors), Class C, SPST (NO), Hermetically Sealed, Plug-In Terminals (Potted)

MIL-R-28894/19 - Relays, Solid State, Sensors, Established Reliability, Type II, (DC Voltage Sensor), Class C, SPST (NO), 250 Milliamperes Hermetically Sealed, Plug-In Terminals (Potted)

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0725-99)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:45Z
Check the source to verify that this is the current version before use.