FF-N-105a
Interim Amendment-2
April 7, 1964

Superseding
Interim Amendment-1
December 20, 1963

INTERIM AMENDMENT-2
TO
FEDERAL SPECIFICATION

NAILS, WIRE, BRADS, AND STAPLES

This Interim Amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C., 20407, based upon currently available technical information. It is authorized by General Services Administration for use in procurement as a part of Federal Specification FF-N-105a, dated July 26, 1963. It may be converted to a regular Amendment after further coordination.

Page 1, paragraph 1.2.1: Under Type II.- Nails, add "26.- Square Barbed Nails (table XXXIII)".

Page 4, paragraph 3.3: Delete and substitute the following:

"3.3 Altered Shapes.

3.3.1 Mechanically deformed shanks. Mechanically deformed shanks may be of either the screw type or the annular ring type.

3.3.2 Mechanically driven nails. Mechanically driven nails shall be T head or shall be either style 7 or style 10 nails as specified (see 6.1) with altered heads suitable for use in power nail drivers. The T head nails shall conform to table XI-d for dimensions (see 6.1). The style 7 or style 10 nails with altered heads shall be the sizes as specified (see 6.1) and shall otherwise conform to table VIII or table XI-b for dimensions.

Page 4, add paragraph 3.4.3.2: Delete all after "Power driven staples" and substitute the following: "Power driven staples shall conform to table XXIX and shall fit the make and model of staple gun specified (see 6.1).

"3.4.3.3 Electrician's staples. Electrician's staples shall be either insulated or uninsulated as specified (see 6.1). Electrician's staples shall conform to table XXX for dimensions".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

Page 13, Table XI-d. Delete and substitute the following: "Table XI-d. Nails, type II, T head, diamond point, aluminum-alloy, bright or galvanized steel (power driven).

Length	Diameter of Shank
1-1/4	.080
1-1/4	.086
1-1/4	.099
1-1/2	.080
1-1/2	.086
1-1/2	.097
1-1/2	.113
1-5/8	.080
1-5/8	.086
1-5/8	.097
1-3/4	.080
1-3/4	.086
1-3/4	.097
1-3/4	.113
1-7/8	.080
1-7/8	.086
1-7/8	.097
2	.080
2	.086
2	.097
2	.113
2	.148
2-1/4	.099
2-1/4	.113
2-1/2	.099
2-1/2	.113
2-1/2	.131

Page 29, table XXIX: Delete column headed "Inches between legs" dimensions on the 3/16, 1/2, 7/16, 3/4 and 1 inch crown staples.

Add as a part of table XXIX the following:

3/8 Inch Crown Width Staples 14 and 16 Gauge

Length
1-1/8
1-1/4
1-3/8
1-1/2
1-5/8
1-3/4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

Page 33. Add: Table XXXIII. Nails, Type II, Style 26, square, barbed, bright, steel:

Size	Length	Gauge	Diagonal	Flat Dim	Head	Approx Ct per lb
6d Common	2	11-1/2	.113	.079	1/4	201
8d Common	2-1/2	10-1/4	.131	.093	17/64	118
10d Common	3	9	.148	.105	9/32	84
16d Common	3-1/2	8	.162	.115	5/16	59
20d Common	4	6	.192	.136	3/8	39
6d Box	2	12-1/2	.099	.070	1/4	256
8d Box	2-1/2	11-1/2	.113	.080	17/64	152
6d Finish	2	13	.091	.064	.124	320
8d Finish	2-1/2	12-1/2	.099	.070	.131	235
1-1/2" Truss	1-1/2	10-1/4	.131	.093	9/32	191

Page 36, paragraph 6.1, add:

"(j) Whether insulated or uninsulated staples are required (see 3.4.3.3).

(k) Whether style 7 or style 10 are required (see 3.3.2).

(l) Approximate head width for T head nails.

(m) Make and model of gun to be used for power-driven nails or power-driven staples."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.