MIL-C-50797 (MU)
AMENDMENT 1

28 May 1975

MILITARY SPECIFICATION

CASE, CARTRIDGE, 20MM, M103A1

This amendment forms a part of Military Specification MIL-C-50797(MU), 25 May 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

Para 4.2.1, delete para 4.2.1 and substitute the following:

"4.2.1 Initial production sample.-At the beginning of regular production a sample shall be submitted in accordance with contract requirements and shall consist of 2300 cases. The sample shall be manufactured using the same equipment, processes and procedures as will be used in regular production. Sample shall be divided and tested as follows:

100 Cases -- Physical and dimensional examination and test
800 Cases -- Function and casualty test, ambient temperature, M61 gun
800 Cases -- Function and casualty test, ambient temperature, M39 gun
100 Cases -- Function and casualty test, -65°F, M61 gun
100 Cases -- Function and casualty test, -65°F, M39 gun
100 Cases -- Function and casualty test, +165°F, M61 gun
100 Cases -- Function and casualty test, +165°F, M39 gun
100 Cases -- Function and casualty test, ambient temperature, excess pressure, M61 gun
100 Cases -- Function and casualty test, ambient temperature, excess pressure, M39 gun

The acceptance criteria specified in Table II for the combined sample will be used and applied independently to each of the above phases of the function and casualty test. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. Identification shall be in accordance with MIL-STD-1168."

Para 4.3.3.1, under Major:

118. delete "2.664" and substitute "2.837"

125. add "Exterior" before the words, Protective finish.

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

Para 4.3.4 Tests, delete Table I only and substitute the following:

Table I

Test	Sample Size	Rqmt Para
Hardness	1/ 13	3.4
Cold shut	2/ 13	3.5
Corrosion resistance	3/ 13	3.6.3
Function and casualty	4/ 400	3.7

Para 4.3.4 Tests, Table I footnote 4/, delete the last sentence.

Para 4.3.4 Table II, after Function and Casualty Test add footnote symbol D/.

Para 4.3.4 Table II, add after footnote C/ the following:

"D/ The excess pressure, ambient, low and high temperature phases will be considered as separate tests when firing the Initial production sample.

Para 4.3.4 Table II, under Detached metal, delete the line "Neck shear--------". and substitute the following:

"Neck shear C/ 0 1 0 1 0 1 0 1"

Para 4.3.6 Inspection Equipment. In sixth line delete "B11057228" and substitute "B11075228".

Custodian:

Army - MU

Preparing Activity:

Army - MU

Review:

Army - MU

Project No. 1305-A782

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:38Z
Check the source to verify that this is the current version before use.

1c