MILITARY SPECIFICATION
EJECTOR, PARACHUTE, CARTRIDGE ACTUATED: XM7
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-E-50766(MU) dated 14 January 1972.

Paragraph 2.1 under DRAWINGS Delete drawing number "D9257364" and substitute "C9257364".

Paragraph 3.4, line 1 Delete the words "The outside tube" and substitute "The tubes".

Add the following new paragraph:

"3.9 Pull test.-The sear assembly shall withstand a tensile pull test of 75 ± 5 lbs. without slippage."

Paragraph 4.3.1.2, line 2: Delete "5000 ejectors maximum" and substitute "10000 ejector maximum".

Paragraph 4.3.2.1 Delete "Dwg. C10551446" and substitute "Dwg. C11743947".

Paragraph 4.3.2.2 Delete "Dwg. C10551454" and substitute "Dwg. C11743952".

Paragraph 4.3.2.5 Delete "Dwg. C10551448" and substitute "Dwg. C11743949".

Paragraph 4.3.2.6 Delete "Dwg. B10551453" and substitute "Dwg. B11743951".

Paragraph 4.3.2.7 Delete "Dwg. 10551451" and substitute "Dwg. D11743954".

Paragraph 4.3.2.9 Delete "Dwg. D10551449" and substitute "Dwg. D11743953".

Paragraph 4.3.2.13 Delete paragraph title and substitute:

"4.3.2.13 Metal Parts Assembly Dwg. F10551542, less all components except Washer B11743951, Pin Firing C11743949".

Add the following new paragraphs:

"4.3.3.5 Pull test.-Each partial assembly; consisting of sear 11743947, wire rope and sleeve cable 11743948, shall be subjected to a pull test. Failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.3.5 (Cont'd)

of any partial assembly to comply with the requirements of 3.9 shall be cause for rejection of the subassembly".

"4.4.5 Pull test.-The sear subassembly shall be secured in a fixture and subjected to a pull applied to the wire rope in a longitudinal direction in conjunction with the fixture which registers the amount of pull."

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A507

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.