MILITARY SPECIFICATION

IGNITION ELEMENT ELECTRICAL
LOADING ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-I-50867B (PA) dated 12 July 1976.

Page 2

Para. 3.3.1.2, Delete "cognizant ... review." and substitute "government."

Page 3

Para. 3.5.2, Delete "cracks,"

Page 7

Para. 4.4.2.2, Delete Major 101
Major 102, Delete "*"
Delete "*The ... 100%."

Page 8

Para. 4.4.2.3, Major 104, Delete "1.0%" and substitute "see note"
Add note as follows: "MIL-STD-105, AQL 0.65%, single sampling plan, normal inspection at General Inspection Level 1."

Page 13

Para. 4.5.5, Delete "100 ± 10 millicuries" and substitute "50 ± 10 millicuries"
Delete "± .01%" and substitute "± .01 seconds"
Delete ", adequate shielding ... measurement values." and substitute "and adequate shielding equipment."

Page 17

Delete para. 6.7 in its entirety.

Page 17

Para. 6.9, Delete "and gamma testing"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Page 18

Para. 6.13, Delete "One set ... paragraph 6.12."
Delete "Table IV" in its entirety and substitute:

"Table IV

	Min. Density	Max. Density
Potassium Chlorate, %	41.5	38.5
Lead Thiocyanate, %	30.0	34.0
Charcoal, %	19.5	16.5
Lacquer, %	9.0	11.0

Allowable weight tolerances are ± 1 milligram."

Delete "Calibration values ... (see 4.5.5)." and substitute "5 densitometer readings shall be taken and recorded for each of the high and low density standards. Acceptance limits shall be set by calculating the 3 sigma (standard deviation) limits about the high and low standard mean readings. The difference between high and low means must exceed three sigma for the standard deviation of both groups."

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project No. 1375-A227

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.