MILITARY SPECIFICATION

POWER SUPPLY, PP4812/VPS-2:10548440

This amendment forms a part of Military Specification MIL-R-50686A (AR) dated 30 October 1979, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

Table II, Classification of Defects, 102.. performance, test procedure: Delete "4.6.3" and substitute "4.6.3, 4.6.4, 4.6.5, 4.6.6"

PAGE 11

Table V, Test Equipment List, Item 3, Meter accuracy: Delete "± 5%" and substitute "± 2%"

PAGE 19

4.6.3.4, Load currents, CURRENT REQUIRED column: Delete and substitute: "CURRENT REQUIRED

10.0±0.2
0.75±0.20
0.375±0.100
0.500±0.100
0.500±0.100
1.45±0.10
1.2±0.2
1.2±0.2"

PAGE 20

4.6.3.5, Load currents, NOT LESS THAN and NOT MORE THAN columns; Delete and substitute:

"NOT LESS THAN	NOT MORE THAN
(Vdc)	(Vdc)
-14.9	+15.1
+14.9	+15.1
+6.3	+6.7
+6.3	+6.7

FSC 1285

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:33Z
Check the source to verify that this is the current version before use.

-14.9	-15.1
+14.9	+15.1
-32.9	-33.1
-32.9	-33.1
+32.9	+33.1
-22.9	-23.1
+22.9	+23.1"

PAGE 21

4.6.4.1, fourth and fifth lines: Delete "Connect the voltmeter to the elevation" and substitute "Connect the voltmeter, Item 2, to the elevation"

4.6.4.2:
Third and fourth lines: Delete "to obtain between -10.0 to -10.5V on" and substitute "to obtain -10.0 Vdc on"

Fifth line: Delete "reads between 9.2 and 14 mV" and substitute "reads between 16.6 and 26.2 mV"

4.6.4.3:
Second line: Delete "to obtain between -10.0 and -10.5 Vdc on" and substitute "to obtain -10.0 Vdc on"

Fourth line: Delete "between 117 and 176 mV." and substitute "between 179 and 397 mV."

4.6.4.6:
Fourth line: Delete "to produce -10.0 to -10.5 Vdc on" and substitute "to produce -10.0 Vdc on"

Sixth line: Delete "+0.67 and +1.00 Vdc." and substitute "286 and 446 mV."

PAGE 22

4.6.5.1, sixth line: Delete "between -10.0 and -10.5 volts on" and substitute "to obtain -10.0 Vdc on"

4.6.5.2, second line: Delete "between 9.2 and 14 mV." and substitute "16.6 and 26.2 mV."

4.6.5.3:
Second line: Delete "to obtain between -10.0 and 10.5 Vdc on" and substitute "to obtain -10.0 Vdc on"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:33Z
Check the source to verify that this is the current version before use.

Fourth line: Delete "between 117 and 176 millivolts (mV)." and substitute "between 179 and 397 mV."

4.6.5.6:
Fifth line: Delete "to produce -10.0 to 10.5 Vdc" and substitute "to produce -10.0 Vdc"

Seventh line: Delete "is between + 0.67 and + 1.00 Vdc." and substitute "is between 286 and 446 mV."

Custodian:
Army-AR

Preparing activity:
Army-AR
(Project 1285-A557)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:33Z
Check the source to verify that this is the current version before use.