[INCH-POUND]
A-A-55001/05
December 21, 1994

COMMERCIAL ITEM DESCRIPTION

DISK DRIVE UNIT, SEVEN DRIVE, SMALL COMPUTER SYSTEM INTERFACE (SCSI), HALF HEIGHT, EXTERNAL, CD-ROM, AND OTHER ACCESSORIES

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID covers the general requirements for a seven-drive, multimedia, half height, CD-ROM, disk drive unit with one controller card, cabinet, interface cables, seven cartridges, software programs and other accessories as specified. Disk drive units covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION. This CID uses a classification system which is included in the Part or Identification Number (PIN) (see 7.1). The PIN shall be AA55001/05-01.

3. SALIENT CHARACTERISTICS

3.1 Design and construction. Disk drive units supplied to this CID shall be as specified herein.

TABLE I. Characteristics.

AA55001/05-	Characteristics	CD-audio	Transfer rate	Access time	Interface	Bus architecture supported
01	CD-ROM Multimedia PC Marketing Council (MPC) level II compliant disk drive	Yes	300 kilobytes (kb) per second minimum	Less than or equal to 325 milliseconds (ms)	SCSI-2	Industry Standard Architecture (ISA) 16-bit
02	CD-ROM MPC level II compliant disk drive	Yes	300 kb per second minimum	Less than or equal to 325 ms	SCSI-2	Extended Industry Standard Architecture (EISA) 32-bit
03	CD-ROM MPC level II compliant disk drive	Yes	300 kb per second minimum	Less than or equal to 325 ms	SCSI-2	Micro Channel Architecture for IBM (MCA) 16-bit

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Electronics Supply Center, ATTN: DESC-ELDM, 1507 Wilmington Pike, Dayton, OH 45444-5765, or telephone (513) 296-6189, or facsimile (FAX) (513) 296-8868.

AMSC N/A
FSC 7025

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.2 Disk drive unit.

3.2.1 Weight. The weight of this disk drive unit shall not exceed 21 kilograms (46 pounds) as a complete unit.

3.2.2 Memory storage capacity. The memory storage capacity of this disk drive unit shall be a minimum of 4.2 gigabytes (GB).

3.2.3 Form factor. The external form factor of each drive shall be 130 millimeters (mm) (5.25 inches) half height.

3.2.4 Front loadable. This disk drive unit contains seven drives and shall be front loadable with seven cartridges (i.e., caddies). A cartridge is not required if the unit has a loading tray that does not require a cartridge.

3.2.5 Horizontal operations. This disk drive unit shall be able to operate in the horizontal position.

3.2.6 Multiple sectors. Each disk drive shall be able to read multiple sectors.

3.2.7 File structure compatibility. Each disk drive shall be ISO 9660 compatible.

3.2.8 Buffer memory capacity. The buffer memory capacity shall be a minimum of 64 kb.

3.2.9 Mean time between failures (MTBF). The MTBF shall be 50,000 hours minimum.

3.2.10 Operation temperature. The operation temperature shall be +5°C to +40°C (±2°C).

3.2.11 Seek error. The seek error shall be $10x10^{-6}$ or less.

3.2.12 Relative humidity (Rh). The Rh operating range shall be 30 to 70 percent Rh (±2 percent).

3.2.13 Operation vibration. This disk drive unit shall be able to withstand 0.1 G_{o-p} at 5 hertz (Hz) to 300 Hz in x, y, and z directions without the loss of data transmission.

3.2.14 Nonoperating vibration. The nonoperating vibration shall be 2.0 G_{o-p} at 5 Hz to 300 Hz.

3.2.15 Operational shock. This disk drive unit shall be able to withstand 0.4 G_{o-p} at 11 ms half-sine wave without the loss of data transmission.

3.2.16 Nonoperating shock. The nonoperating shock shall be 20 G_{o-p} at 11 ms half-sine wave.

3.2.17 CD-audio compatibility. This CD-ROM disk drive unit shall be capable of reproducing CD audio. A volume control and headphone stereo mini-jack for each disk drive shall be located in the front of the unit.

3.2.18 SCSI addressing. SCSI addressing shall be external and user selectable.

3.2.19 Self-cleaning mechanism. Each CD-ROM disk drive shall have a self-cleaning optical pickup mechanism unless the CD-ROM disk drive unit is a completely sealed unit.

3.2.20 Power, busy/in-use indicator light. This CD-ROM disk drive unit shall be supplied with at least one power-on indicator light and one busy/in-use indicator light for each disk drive.

3.2.21 Photo CD compatible. These CD-ROM multimedia disk drive units shall be multi-session photo CD compatible.

3.2.22 Federal Communications Commission (FCC) approval. This CD-ROM disk drive unit shall be certified to FCC class B computing devices pursuant to subpart J of part 15 of FCC rules. A CD-ROM disk drive unit consists of a number of connected CD-ROM drives within a single cabinet as a distinct fully integrated unit.

3.2.23 UL approval. The complete CD-ROM disk drive unit shall be listed to UL 1950 for electronic data processing (EDP) equipment. A CD-ROM disk drive unit consists of a number of connected CD-ROM drives within a single cabinet as a distinct fully integrated unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.3 Cabinet.

3.3.1 Cabinet dimensions. The cabinet dimensions shall be 53.4 cm (21 inches) in height maximum, 26.7 cm (10.5 inches) in width maximum, and 43.2 cm (17 inches) in length maximum and functionally able to accommodate seven drive units.

3.3.2 Power supply. A power supply shall be enclosed which will support auto sensing or manual switching from 100 volts minimum to 240 volts maximum.

3.3.3 Operating frequency. The operating frequency shall be 50/60 Hz.

3.3.4 Power dissipation. The power dissipation shall be no more that 85 watts.

3.3.5 Power switch. This unit shall be supplied with an external ON/OFF power switch.

3.3.6 Temperature maintaining cooling fan. This disk drive unit shall be supplied with a cooling fan that maintains the operational temperature range of the CD-ROM drives.

3.3.7 Input/output (I/O) port. This disk drive unit shall be supplied with at least one built-in I/O port. If more than one I/O port is built in, an external terminator plug must be supplied with each CD-ROM disk drive unit.

3.3.8 Cabinet material. The cabinet shall be constructed of a metal or a combination of metal and plastic materials.

3.4 SCSI controller card.

3.4.1 SCSI controller card characteristics. The controller card shall be 16-bit or 32-bit as specified in table I and shall be MS DOS compatible with IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer.

3.5 Cables.

3.5.1 Cables. This CD-ROM disk drive unit shall include the necessary cabling and power cords intelligence to run selected operations on IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer as specified as follows.

3.5.2 Interface cable. A compatible host to disk drive unit SCSI interface cable shall be provided.

3.5.3 Interface cable length. The interface cables length shall be 0.6 meter (2 feet) minimum.

3.5.4 Power cable. The power cable shall be a UL rated three prong power cable 1.5 meters (5 feet) in length.

3.6 Technical documentation. Disk drive units shall be provided with technical documentation including owner's manual, and related information on operation and use.

3.7 Software. Disk drive units shall be supplied with a copy of Microsoft Extension (MSCDEX) CD-ROM operating program and installation instructions on a 90 mm (3.50 inches) floppy disk.

3.8 Operating system software supported. This disk drive unit shall support Novell NetWare version 3.11 or higher, MS-DOS and PC-DOS version 3.30 or higher operating system software.

3.9 Software driver interface. This disk drive unit shall be compatible with Advanced SCSI Programming interface (ASPI); Novell NetWare driver with version 4.0 Media Manager interface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.10 Accessory kit. Each disk drive unit shall be provided with the following accessories.

a. SCSI controller card.

b. SCSI terminator (plug or switchable).

c. Cable (host to disk drive unit).

d. Instruction manual(s).

e. Software.

4. REGULATORY REQUIREMENTS. This section is not applicable to this CID.

5. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-55001.

6. PACKAGING. Packaging shall be as specified in A-A-55001.

7. NOTES

7.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See 2 for PIN format example.

7.2 Multimedia PC Marketing Council (MPC) level II minimum requirements. The following requirements are minimum requirements which a CD-ROM disk drive unit must meet to be compliant to MPC level II.

a. Double speed with CD-DA outputs (capable of sustained 300 kb/second transfer rate).

b. No more than 40 percent of the CPU bandwidth may be consumed when maintaining a sustained transfer rate of 150 kb/second.

c. Average seek time of 400 ms or less.

d. 10,000 hours MTBF.

e. CD-ROM XA ready (mode 1 capable, mode 2 form 1 capable, mode 2 form 2 capable).

f. Multisession capable.

g. MSCDEX 2.2 or higher driver or equivalent that implements extended audio APIs.

h. Subchannel Q support (P, R-W optional).

7.3 Source of documents.

Other Publications

INTERNATIONAL STANDARDS OFFICE (ISO)

ISO 9660 - Information Processing - Volume and File Structure of CD ROM for Information Interchange.

(Applications for copies should be addressed to the International Standards Organization, 3 Rue De Varembe' Geneve, Switzerland.)

UNDERWRITERS LABORATORIES, INCORPORATED (UL)

UL 1950 - Safety of Information Technology Equipment, Including Electrical Business Equipment.

(Applications for copies should be addressed to the Underwriters Laboratories, Incorporated, 333 Pfingsten Road, Northbrook, IL 60062-2096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

7.4 Government users. To acquire information on obtaining these disk drive units from the Government inventory system, contact Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5270, or telephone (513) 296-5307.

7.5 Ordering data. Ordering data shall be as specified in A-A-55001.

7.6 Suggested sources of supply. Suggested sources of supply are listed below. Additional sources will be added as they become available. The vendors listed have submitted a certificate of compliance to DESC-ELDM and meet requirements of this CID.

	CID dash number AA55001/05-		
	01	02	03
Vendor commercial PIN CAGE 0CPW7	0137100705 WITH 0105223048	0137120705 WITH 0105223048	0119110747 WITH 0105233046
Vendor commercial PIN CAGE 0YVS8	TCD-T4101-7/7-1542	TCD-T4101-7/7-2742	TCD-T4101-7/7-1640
Vendor commercial PIN CAGE 0ZAW7	AA55001/05-01	AA55001/05-02	AA55001/05-03
Vendor commercial PIN CAGE 2S373	1070TOWER7S & 2470STDKIT	1070TOWER7S & 2470PRMKIT	1070TOWER7S & 2470MCAKIT

0CPW7 Meridian Data, Incorporated
5615 Scotts Valley Drive
Scotts Valley, CA 95066
(408) 438-3100

0YVS8 Protégé Corporation
4165 East LaPalma Avenue
Anaheim, CA 92807
(800) 232-1347

0ZAW7 TAC Systems, Incorporated
1031 Putman Drive
Huntsville, AL 35816
(205) 721-1976

2S373 SMS Data Products Group, Incorporated
1501 Farm Credit Drive
McLean, VA 22102-5004
(703) 883-4396

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - KMR

PREPARING ACTIVITY:

DLA-ES

Project 7025-D034

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.