INCH-POUND

A-A-55098
04 December 1992

COMMERCIAL ITEM DESCRIPTION

CLOTHING, LEATHER, (APRONS, SLEEVES, AND JACKETS)

The General Services Administration has authorized the use of this Commercial Item Description in preference to KK-C-450

Abstract. This description covers the requirements for leather protective aprons, sleeves, and jackets. The leather clothing are intended for use by all Government agencies, for the protection of personnel from trade hazards.

Classification. The leather clothing shall be in the following types and classes:

Type I	- Aprons
Class 1	- Plain
Class 2	- Split leg
Type II	- Sleeves
Class 1	- Plain
Class 2	- Sleeve, cape and bib, welder's
Type III	- Jacket

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSD, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Salient Characteristics. The leather protective aprons, sleeves, and jackets construction shall conform to the following U.S. Army Natick Research, Development, and Engineering Center drawings listed:

2-1-521 - Clothing, leather, (Aprons, Sleeves, and Jackets) type III, Jacket

2-1-522 - Clothing, leather, (Aprons, Sleeves, and Jackets) Apron, Split Leg, type I, class 2

2-1-523 - Clothing, leather, (Aprons, Sleeves, and Jackets) type II, class 1 Sleeve. Type II, class 2 Sleeve, Cape and Bib, Welder's

2-1-524 - Clothing, leather, (Aprons, Sleeves, and Jackets) Plain Apron, type I, class 1

These drawings shall be obtained from the procuring activity or as directed by the contracting officer.

Material

Slide socket. The slide socket for type I, classes 1 and 2 aprons shall be as shown on Drawings 2-1-522 or 2-1-524. The socket component shall be capable of firmly engaging the stud component of the male snap fastener and shall be capable of unsnapping to effect separation.

Buttons and tacks. The buttons and tacks for the type II, class 2 clothing shall conform to MIL-B-286. The buttons shall be type I, black, size 27-line and the tacks type IX, black, size 17-line by 0.406 inch or size 14-line by 0.406 inch.

Buttonhole. The buttonholes in the leather attached to the elastic webbing shall be of the dimensions shown on Drawing 2-1-523. One end of the slit shall terminate in a round perforation and the surface edges of the slit shall be smooth and free of loose fibers.

Grommets. The grommets for the type II clothing shall be type III, class 3, size 1, conforming to MIL-G-16491. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Rivets, split. The split rivets shall be nominal 1/8 inch diameter, black oxide finish, conforming to type XI, class 1, grade E of FF-R-556 except that the rivet may have a standard straight slot. The length shall be such as to effect a minimum clinch of 1/8 inch after penetrating the leather parts being secured.

Staples. The staples used for stitching shall be formed of flat steel wire approximately 0.060 by 0.020 inch, and have a corrosion resistant finish. The crown length shall be approximately 1/2 inch and the leg length of the formed staple shall be such as to insure a clinch of 1/16 inch minimum and 1/8 inch maximum after the staple has penetrated the leather being sewed.

Thread. The thread shall be cotton or para-aramid. The thread shall be a dyed Khaki P-1, C.A. 66019 and shall conform to A-A-52094 and thread sizes below:

Thread sizes

	301 stitch		401 stitch		Bartack	
Thread	Needle	Bobbin	Needle	Bobbin	Needle	Bobbin
Cotton	12-4	12-4	12-4	24-4	24-4	24-4
Para-aramid	T-50	T-50	T-50	T-35	T-50	T-35

Leather. The leather for body, straps, and thongs shall conform to type IV, class 2 of KK-L-2004 except that minimum elongation shall be 10 percent and the maximum elongation shall be 45 percent. The color of the leather shall be natural. The leather body shall be 4/64 (-1/128 + 1/64) inch thick. The leather straps and thongs shall be 5/64 (-1/128 + 1/64) inch thick.

Webbing, elastic. The elastic webbing shall be unbleached, 3/4 inch, type I, class 3, conforming to JJ-W-155. A commercial type 3/4 inch wide elastic webbing meeting the initial tension requirement for the type I, class 3 webbing of JJ-W-155 may be used as an alternate.

Labeling. The identification marking shall be applied in the location shown on each drawing and shall conform to type IV, class 5 of DDD-L-20.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Fasteners, snap.

Type I clothing. The male snap fastener for the type I clothing, consisting of a stud and eyelet, shall be style 2A, finish 2 conforming to MIL-F-10884.

Type II and type III clothing. The snap fastener for the type II, classes 1 and 2 and type III clothing shall be style 2, finish 2 conforming to MIL-F-10884.

The snap fasteners, shall be located as shown on the drawings. If a hole is punched before inserting the barrel of the eyelet, it shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole. The fasteners shall be securely clinched without cutting the materials.

Bartacking. Bartacks shall be as specified on the applicable drawings. The stitches per bartack shall be 28 per bartack for the 1/2 inch and 42 per bartack for the 3/4 inch.

Piecing. The bib portion of type I, class 2 apron may be made of one or three pieces. When three pieces are used, joining seams shall be as shown on Drawing 2-1-522 and the center piece of the bib shall be not less than 12 inches girthwise.

Workmanship. After completion, the finished garment shall be thoroughly cleaned, and all loose thread, lint, and foreign matter removed.

Stitching. Type 401 or 301 stitching conforming to FED-STD-751 shall be used on double seams that are reinforced with staple stitching. All remaining stitching except staple stitching and bartacking shall conform to type 301 of FED-STD 751. All stitching except staple stitching and bartacking shall have 6-10 stitches per inch. When stitch type 401 is used, the chain shall be on the inside of the garment. Type 401 stitching shall have a 1/2 inch bartack placed across the ends of the stitches except when the ends are caught in other seams or stitching. Type 301 stitching shall be backstitched not less than 1/2 inch at the ends except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so there will be no loose stitching or excessively tight stitching resulting in puckering of the material sewn. All thread ends shall be trimmed to a length of not more than 1/4 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Repairs of Types 301 and 401 stitching. Repairs of stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/4 inch back of the end of stitching.

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 3/8 inch back of the defective area, continue over the defective area and continue a minimum of 3/8 inch beyond the defective area onto the existing stitching. loose or tight stitching without damaging the material and restitching in the required manner. 1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

Quality Assurance

Certification. The contractor shall certify that the product offered meets the salient characteristics and all other requirements listed in this document. and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract.

Examination. Lots of clothing, leather shall be inspected in accordance with "Sampling Procedures and Tables for Inspection by Attributes", ANSI/ASQC Z1.4, published by the American Society for Quality Control.

Visual Examination. The inspection level for visual examination shall be II and the AQL shall be 2.5. The sample unit shall be one apron sleeve, sleeve with cape and bib, or jacket.

Defects. The leather clothing shall be examined for the following defects: any hole, cut, tear, color not as specified; any spot or stain (outside), thread ends not removed; marking missing, incorrect, or illegible; measurement of item not as specified; sleeves not properly mated, e.g., not right and left of same size; not specified type or class; any variation not otherwise classified herein but at variance with the approved product demonstration model; any component missing, misplaced, any operation omitted or not performed as specified; any part fractured, ripped, punctured, or torn; grommet or snap fastener not clinched to a degree where it may become detached from assembly;

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Defects cont. rivet button or tack not set properly to a degree where it may become detached; slide socket or snap fastener reversed on assembly; more than the maximum number of stitches per inch specified, one or two stitches per inch less than the minimum specified; any metal component damaging leather, e.g., snap fastener too tightly clinched resulting in its periphery cutting in leather; any loose stitch tension resulting in a loosely secured seam; any row of stitching omitted; any missing staple, stress point not reinforced by a rivet or double stapling as show on drawings; collar corners not uniformly shaped or poorly shaped.

Dimensional Examination. The finished clothing, leather shall conform to the dimensions specified. Any dimension that is not within the established tolerance shall be classified as a defect. The sample unit shall be one apron, sleeve, sleeve with cape and bib or jacket; the inspection level shall be S-3 and the AQL shall be 2.5.

Packaging Examination. The fully packaged shipping containers shall be examined in accordance with defects listed below. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and AQL shall be 1.0.

Examination	Defect
Material	Missing, damaged, not as required.
Content	Number per bundle is more or less than required.
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Workmanship	Inadequate application of components such as incomplete closure of container flap, loose strapping, inadequate stapling, or improper taping. Bulged or distorted container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Palletization inspection. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL shall be 4.0.

Examination	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Load not bonded as specified.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

Responsibility for Inspection. The supplier is responsible for assuring the product conforms to the requirements. Leather clothing lots will be inspected to determine conformance with the Commercial Item Description and the successful offerer's technical proposal as negotiated. Acceptability of leather clothing lots will be determined by the use of "Sampling Procedures and Tables for Inspection by Attributes", ANSI Z1.4, published by the American Society for Quality Control. Sampling procedures will be designated by the Government at the time of award. The sample unit shall be one apron sleeve, sleeve with cape and bib, or jacket, as applicable. The leather clothing will be examined for commercial type defects only.

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

PACKAGING.

OVERSEAS.

Packaging. Each apron, pair of sleeves, or jacket shall be folded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

Packing. Six aprons, six pairs of sleeves, or six jackets shall be packed in a fiberboard box conforming to style RSC-L, grade 275 of PPP-B-636. The inside dimensions of the box shall approximately 17 inches in length, 14-3/4 inches in width and 7-3/4 inches in depth. The box shall be closed in accordance with the appendix of PPP-B-636.

NOTE: Approximate dimension are furnished as a guide only.

Palletization. Boxes shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D, or film bonding means F and G. The pallet pattern shall be number 6 in accordance with the appendix of MIL-STD 147.

Marking. Marking shall be in accordance with MIL-STD-129.

Domestic.

Packaging, packing, palletization, and marking. Packaging, packing, palletization, and marking shall be in accordance with ASTM-D 3951.

Source of Government Documents. Copies of Military and Federal documents are available from:

Standardization Documents Order desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source of Nongovernment Association Documents.

ANSI/ASQC Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Applications for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018-3308)

MILITARY INTERESTS:
Custodian:
Army - GL
Navy - NU
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:
GSA - FSS
FPI

Review Activity:
Army - MD, GL
Air Force - 45, 82

User Activity:
Navy - MC

Preparing Activity:
DLA - CT

Project No. 8415-0878

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-55098	2. DOCUMENT DATE (YYMMDD) 921204

3. DOCUMENT TITLE
CLOTHING, LEATHER, (APRONS, SLEEVES, AND JACKETS)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Defense Personnel Support Center ATTN: DPSC-FSSD (12-3-D)	b. TELEPHONE (Include Area Code) (1) Commercial: 215-737-8105 (2) AUTOVON: 444-8105
c. ADDRESS (Include Zip Code) 2800 South 20th Street P.O. Box 8419 Philadelphia, PA 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 — Previous editions are obsolete. — 198 290

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:42Z
Check the source to verify that this is the current version before use.