MIL-C-45573B(AR)
2 April 1985

SUPERSEDING
MIL-C-45573A(WC)
19 JULY 1972

MILITARY SPECIFICATION

CANNON, 165MM GUN: M135

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers Cannon, 165MM Gun: M135 consisting of a tube and breech mechanism assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-LCB-SAS, Watervliet, N.Y. 12189-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1025

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

MIL-G-10924 - Grease, Automotive and Artillery
MIL-C-13931 - Cannon, Mortars, Recoilless Rifles and Recoilless Guns: General Specification for
MIL-P-14232 - Parts, Equipment and Tools for Army Materiel, Packaging of
MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1189 - Standard Symbology for Marking Unit Packs, Outer Containers, and Selected Documents

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

U. S. Army Armament, Munitions and Chemical Command

EPL 8769436	- Engineering Parts for Cannon, 165MM Gun: M135
Master LQAP 8769436	- Master Index of Quality Assurance Provisions for Cannon, 165MM Gun: M135
DL 8769436	- Index of Inspection Equipment Lists for Cannon, 165MM Gun: M135
P8769436	- Special Packaging Instructions, Cannon, 165MM Gun: M135
LSPI 8769436	- List of Special Packaging Instructions, Cannon, 165MM Gun: M135
QAP-APPENDIX-WVA	- General Quality Assurance Provisions
11579818	- Obturator Shimming Instructions

PUBLICATION

DA Form 2408-4 - Weapon Record Data

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951 -Standard Practice for Commerical Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, drawing requirements shall have first order of precedence, followed by the text of this specification, then the other referenced specifications and standards.

3. REQUIREMENTS

3.1 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 6.2.1). No first article requirements shall be waived without review by the responsible Engineering Activity and approval by the responsible Product Assurance activity.

3.2 General requirements. Cannon and parts thereof shall conform to the Engineering Parts EPL 8769436 the requirements of this specification, and MIL-C-13931.

3.2.1 Marking. When specified, marking shall be in accordance with the requirement specified in MIL-C-13931.

3.3 Reliability, availability, maintainability, and durability (RAM-D). The specified performance and design requirements result in a cannon and parts thereof having inherent reliability, availability, maintainability, and durability.

3.4 Preparation for assembly.

3.4.1 Tube and breech ring. When assembling the tube to the breech ring grease conforming to MIL-G-10924 shall be used on the packing ring to reduce friction during assembly.

3.4.2 Lubrication. All surfaces of each leaf of the spring assembly, all bearing surfaces of the operating-shaft, the crank, the breech mechanism locking-key, the breechblock release crank, the adjustor, and sliding surfaces of the breechblock shall be coated with lubricant conforming to MIL-G-10924.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

3.5 Functioning. All parts shall function smoothly without interference, erratic movement or malfunction.

3.5.1 Breech opening. The operating handle, when unlatched and rotated rearward, shall rotate the operating shaft and the operating crank to lower the breechblock. The breechblock shall then be locked in the open position by the release crank.

WARNING: The operating handle shall be returned and latched to prevent damage or injury during closing.

3.5.2 Breech closing. A quick upward pull of the release lever shall unseat the cam of the release crank. The closing spring shall rotate the operating shaft and the operating crank to raise the breechblock which shall be locked in the fully-closed position by engagement of the locking key into the recess of the operating shaft. The fully-closed position is indicated by alignment of the breechblock firing contact and the operating crank firing contact and full engagement of the locking key into the cutout in the hub of the operating handle. Full closing shall be obtained with the spring adjustor set for minimum preload which is the extreme counterclockwise position of the adjustor. This requirement applies only to cannon at room temperature with new spring packs. After considerable use and use at subzero temperatures, it is usually necessary to increase the preload on the spring by rotating the adjustor clockwise.

3.5.3 Manual breech closing. Manual closing of the breech shall be accomplished by rotating the operating handle until the clutch can be manually engaged in the hole provided in the crank. While maintaining pressure on the clutch pin, rotation of the handle upward and forward shall move the breechblock into the closed position.

3.6 Firing pin and connector assemblies. The firing pin assembly and connector assembly shall be assembled to assure proper contact of current-carrying parts.

3.6.1 Firing pin position. The point of the firing pin shall be flush to 0.005 inch recessed in the boss on the obturating spindle.

3.6.2 Continuity. The firing circuit shall show continuity with an applied voltage not exceeding 24 volts dc.

3.6.3 Dielectric strength. The firing circuit shall show no evidence of breakdown when subjected to a potential of not less than 1000 volts, rms, ac, 60 cycles per second for 30 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

3.6.4 Insulation resistance. The firing circuit shall have a minimum insulation resistance of one megohm when a potential of 500 volts dc is applied for one minute.

3.7 Obturator assembly.

3.7.1 Bearing of the obturator. The obturator shall be free from any visual defects such as cuts and abrasions. The mating surface of the breech ring shall be free from burrs, nicks, and tool marks. When the breech is closed, the obturator shall make 360 degrees line contact with the breech ring mating surface, the breech block and operating crank firing contacts shall be aligned, and the locking key shall be completely engaged into the cut out in the operating handle hub. It is to be noted that an overshimmed obturator may hang-up in the breech. See drawing 11579818 for obturator shimming instructions.

3.8 Ammunition loading rollers. Both rollers shall roll freely when spun by hand.

3.9 Performance.

3.9.1 High pressure resistance. The cannon and repair tubes shall be capable of withstanding 5800 ± 200 pounds per square inch at 70° F when tested as specified in 4.6.5.2.1.

3.9.2 Bore enlargement. Bore diameters measured across the rifled lands, after proof firing no more than 10 rounds shall not exceed the before firing diameters by the amounts shown in TABLE I.

TABLE I. Bore enlargement.

Distance forward of commencement of rifling	0.10 inch	1 cal.	2 cals. to muzzle
Amount (in inches)	0.006	0.006	0.004

NOTE: Interpolate to determine the bore enlargement between distances given.

3.9.3 Material soundness. After testing all parts shall be free from cracks and fractures, and shall comply with any soundness requirements specified on the applicable drawings.

3.9.4 Obturator pad adjustment. After performance testing, the obturator pad shall be adjusted in accordance with 3.7.1.

3.10 Workmanship. Workmanship shall be as required in MIL-C-13931.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 The inspections set forth in the specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of his responsibility for assuring that all supplies and services submitted to the Govermment for acceptance conform to all requirements of the contract.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used in this specification are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection, (see 4.4).
b. First Article-Initial Production Test, FA-IPT, (see 4.5).
c. Quality conformance inspection, (see 4.6).

4.4 First Article inspection. Unless otherwise specified in the contract, (see 6.2.1), First Article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 8769436. First Article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First Article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.5 First Article-Initial Production Test (FA-IPT). Unless otherwise specified in the contract, (see 6.2.1), First Article Cannon shall be subjected to Initial Production Testing by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of this specification and any additional requirements listed in the contract.

4.5.1 Sample. Three First Article Cannon shall be randomly selected from the first ten cannon produced during quantity

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

production. First Article Cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.5.2 Inspection provisions. First Article Cannon shall be subjected to normal inspection per applicable item QAPs, and Quality conformance inspection (see 4.6) including performance testing (see 4.6.5.2).

4.5.2.1 Performance testing. First Article Cannon shall have successfully passed performance testing (see 4.6.5.2) prior to commencement of First Article-Initial Production Testing.

4.5.2.2 FA-IPT tests. Unless otherwise specified in the contract, (see 6.2.1), cannon tests shall be performed in COMBAT ENGINEER VEHICLE, FULL TRACKED, M728, or in a test facility mount, as applicable. All tests shall be conducted by the Government or any agency specified by the Government and may be conducted at a Government facility.

4.5.2.2.1 Ambient temperature firing test. This test shall be conducted on three cannon using the test method of 4.7.2. If the requirements are not complied with, acceptance shall be deferred and 4.8 applies.

4.5.2.2.2 Elevated temperature firing test. This test shall be conducted on three cannon using the test method of 4.7.3. If the requirements are not complied with, acceptance shall be deferred and 4.8 applies.

4.5.2.2.3 Cold temperature firing test. This test shall be conducted on three cannon using the test method of 4.7.4. If the requirements are not complied with, acceptance shall be deferred and 4.8 applies.

4.6 Quality conformance inspection. Quality conformance inspection is listed in TABLE II.

4.6.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance with the requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 8769436, and QAP-APPENDIX-WVA.

4.6.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.6.3 Inspection equipment. Data lists containing equipment used in the inspection of parts, subassemblies, and assemblies are listed in DL 8769436.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.6.3.1 Acquistion, maintenance, and disposition. Unless otherwise specified (see 6.2.1), responsibility for acquisition, maintenance, and disposition of acceptance inspection and test equipment referenced in the List of Inspection Equipment DL 8769436, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, shall be in accordance with MIL-I-45607, (see 6.4).

4.6.3.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

TABLE II. Quality conformance inspection.

Catagories/Characteristics	Requirement Paragraph	Inspection/Test-Method Paragraph
Examinations		4.6.4
Assembly	3.4.1	4.6.4.1
Lubrication	3.4.2	4.6.4.2
Functioning	3.5, 3.5.1, 3.5.2	4.6.4.3
Firing pin position	3.6.1	4.6.4.4
Bearing of the obturator	3.7.1	4.6.4.5
Ammunition loading rollers	3.8	4.6.4.6
Workmanship	3.10	4.6,4.7
Packaging inspection	5.	4.6.4.8
Tests		4.6.5
Firing mechanism electrical tests		4.6.5.1
Continuity	3.6.2	4.6.5.1.1
Dielectric strength	3.6.3	4.6.5.1.2
Insulation resistance	3.6.4	4.6.5.1.3
Performance testing	3.9	4.6.5.2
Proof firing tests	3.9.1	4.6.5.2.1
Obturator pad adjustment	3.9.4, 3.7.1	4.6.5.2.2
Functioning	3.5, 3.5.1, 3.5.2	4.6.5.2.3
Material soundness	3.9.3	4.6.5.2.4
Bore enlargement	3.9.2	4.6.5.2.5

4.6.4 Examinations.

4.6.4.1 Assembly. When assembling the tube to the breech ring the application of the specified grease shall be observed to determine conformance with 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.6.4.2 Lubrication. When lubricating the breech ring assembly, the application and locations of application of the specified lubricant shall be observed to determine confommance with 3.4.2.

4.6.4.3 Functioning. After shimming of the obturator pad, manually operate the breech mechanism of each assembled cannon for a minimum of two complete cycles. Failure to comply with 3.5, 3.5.1 and 3.5.2 shall be cause for rejection.

4.6.4.4 Firing pin position, This measurement shall be made prior to assembly of the breechblock into the breech ring. After assembly of the firing circuit into the breechblock, the position of the firing pin shall be measured with a depth gage or an approved equivalent. Failure to comply with 3.6.1 shall be cause for rejection.

4.6.4.5 Bearing of the obturator. Visually examine the obturator for cuts, abrasions, and similar visual defects. Coat the seating surface in the breech ring with a thin coat of red lead, then close and open the breech, and examine the obturator for 360-degree line contact. Failure to meet the requirements of 3.7.1 shall be cause for rejection.

4.6.4.6 Ammunition loading rollers. Manually operate and visually examine the rollers to determine conformance with 3.8. Failure to meet the requirements shall be cause for rejection.

4.6.4.7 Workmanship. Workmanship shall be examined visually in accordance with MIL-C-13931.

4.6.4.8 Packaging inspection. Packaging inspection for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232. Packages failing to comply with the packaging requirements shall be rejected.

4.6.5 Tests

4.6.5.1 Firing mechanism electrical tests. Firing mechanism electrical tests shall be conducted on each cannon with approved test equipment. Tests shall consist of continuity, dielectric strength, and insulation resistance and shall be performed with the cannon breech in the closed position.

4.6.5.1.1 Continuity. Continuity of the firing circuit shall be determined by placing a circuit tester (11576610 or approved equivalent) into the breech end of the tube and pushing the tester forward until it stops at the raised diameter. After closing the breech mechanism, connect a dc power supply not exceeding 24 volts to the firing circuit. Continuity of the circuit will be indicated by the sounding of the buzzer of the tester. Failure to achieve an indication of continuity shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.6.5.1.2 Dielectric strength. After completion of the continuity test, an appropriate high potential tester shall be connected to the firing circuit and grounded on the breech ring or breechblock. A 60 cycles per second potential of 1000 volts rms shall be applied for 30 seconds. Any indication of breakdown shall be cause for rejection.

4.6.5.1.3 Insulation resistance. After completion of the dielectric strength test, a megohm bridge or other approved measuring instrument shall be connected to the firing circuit and grounded on the breech ring or breechblock. A potential of 500 volts dc shall be applied for one minute. Any firing mechanism failing to show minimum insulation resistance of one megohm shall be rejected.

4.6.5.2 Performance testing. Each cannon and repair tube shall be subject to performance testing to assure compliance with 3.9, by a Government activity in accordance with procedures specified by the Engineering and Product Assurance elements of the procuring activity.

4.6.5.2.1 Proof firing test. Each cannon and repair tube shall be subjected to proof firing tests by Government personnel at a proving ground designated by USATECOM. Proof firing shall consist of firing one round of ammunition producing 5800 $\pm$ 200 pounds per square inch at 70 degrees F.

4.6.5.2.2 Obturator pad adjustment. After firing, readjust the obturator in accordance with 3.7.1 and examine in accordance with 4.6.4.5.

4.6.5.2.3 Functioning. After performance testing, each cannon shall be tested for proper functioning in accordance with

4.6.4.3. Cannon failing to meet the requirements of 3.5 shall be cause for rejection.

4.6.5.2.4 Material soundness. After testing, each cannon and each repair tube shall be examined visually for freedom from cracks, fractures and other defects. Furthermore, breechblocks, breech rings and outer surfaces of tubes shall be magnetic particle inspected in accordance with applicable drawings and specifications. Inner surface of tubes shall be examined by means of a borescope. Any evidence of cracks or fractures shall be cause for rejection.

4.6.5.2.5 Bore enlargement. After firing no more than 10 rounds, the bore diameters across the lands of each cannon and each repair tube shall be measured with an air gage, electrical gage, or other approved gage. Measurements shall be recorded. Enlargement exceeding the limits specified in TABLE I shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.6.5.2.6 Records. Cannon and repair tubes that pass firing tests shall have applicable data entered on DA Form 2408-4, "Weapon Record Data" card by the proving ground.

4.7 FA-IPT test methods.

4.7.1 Firing schedule shall be as specified in TABLE III.

TABLE III. Firing schedule.

No. of rounds	Chamber pressure requirement, psi
2	5100
2	5800 ± 200
2	5100
2	5800 ± 200

4.7.2 Ambient temperature firing test. A ten round group, (TABLE III preceded by two warmer rounds), shall be fired at a vertical target located at a range of 600 meters with cannon and ammunition at ambient temperature. Measure chamber pressure and muzzle velocity. After firing, perform inspection prescribed in 4.6.5.1.1, 4.6.5.1.2, 4.6.5.1.3, 4.6.5.2.3, 4.6.5.2.4 and 4.6.5.2.5.

4.7.3 Elevated temperature firing test. A ten round group shall be fired with cannon and ammunition conditioned at +125 degrees F. (Ammunition may either be conditioned at +125 degrees F or powder increments added to simulate the pressure condition at the elevated temperature.) After firing, perform inspection prescribed in 4.6.5.1.1, 4.6.5.1.2, 4.6.5.1.3, 4.6.5.2.3, 4.6.5.2.4, and 4.6.5.2.5.

4.7.4 Cold temperature firing test. Ten round groups shall be fired at each of the following temperatures: -25 degrees F, -40 degrees F, and -50 degrees F. After firing at each of the preceding temperatures, perform inspection prescribed in 4.6.5.1.1, 4.6.5.1.2, 4.6.5.1.3, 4.6.5.2.3, 4.6.5.2.4, and 4.6.5.2.5.

4.8 Failure analysis. The contractor shall assist in failure analysis procedures by performing a dimensional, physical, and visual examination of the components which are suspected to have caused the failure. Results shall be submitted to the Government for a final cause determination. The Govermment reserves the right to participate in any of the above examinations and tests. If it is determined that failure occurred because of deviation from specified dimensions or physical properties or both, the contractor shall accomplish, as applicable, the following actions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

a. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect in future production.

b. Examine completely assembled cannon and partially assembled cannon and components to ensure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.

c. Submit the corrective actions taken to the Government for evaluation and approval to retest or continue the test.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Preservation, packaging and packing of the cannon shall be in accordance with Special Packaging Instructions P8769436 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts.

5.2.1 Levels A, B and C. Repair parts preservation, packaging and packing shall be in accordance with the applicable Special Packaging Instructions listed in the List of Special Packaging Instructions LSPI 8769436 for the level of protection specified in the contract (see 6.2).

5.2.2 Level X-Industrial packaging. Repair parts preservation, packaging, packing and marking shall be in accordance with ASTM D 3951 when Level X protection is specified in the contract (see 6.2).

5.3 Marking.

5.3.1 Levels A, B and C. Marking of unit packages and exterior shipping containers shall be in accordance with Packaging Data Sheet P8769436.

5.3.2 Level X - Industrial. Marking shall be in accordance with ASTM D 3951.

5.3.3 Bar code marking. When specified (see 6.2.1.m) bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

6. NOTES

6.1 Intended use. The cannon specified herein is intended to be used in the Combat Engineer Vehicle, Full Tracked, M728 System.

6.2 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

6.2.1 Acquisition requirements.

a. Title, number and date of this specification.
b. Requirements for and the number of assemblies to be submitted for first article by the contractor (see 3.1).
c. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.
d. All inspection and test data that is required.
e. At whose expense a retest may be performed.
f. Serial numbers for the cannon and tube assemblies.
g. List of inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.6.3.1).
h. Availability of inspection equipment from the Government.
i. Extent of supplier's responsibility for Government-furnished and for supplier-required final inspection equipment.
j. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.
k. When applicable, the sampling plan for the actual firing of tubes.
l. The levels of preservation, packaging, and packing required for cannon (see 5.1) and repair parts (see 5.2).
m. When applicable, bar code marking requirements (see 5.3).

6.2.2 Contract data requirements. Monthly reports of the results of final examination and performance testing shall be as specified for delivery on DD Form 1423 in the contract.

6.2.2.1 When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DOD FAR Supplement 52.227-7031 are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data Requirement Title	Applicable DID No.
3.1	First Article Inspection Report	DI-T-4902

(Data item descriptions related to this specification, and identified in Section 6 will be approved and listed as such in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

DoD 5000.19L., Volume II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the Contracting Officer).

6.3 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

6.4 Unless otherwise specified, the contract should specify the application of MIL-I-45607 and MIL-STD-45662.

6.5 Definition. Frequency of testing is defined as the proportion of the lot to be tested after initial 100 percent testing.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-AR

Preparing activity:

Army-AR

Project No. 1025-A159

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: SMCAR-LCB-SAS
Watervliet, NY 12189-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45573B (AR)	Cannon, 165MM Gun: M135

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.