INCH-POUND
MIL-C-45573C(AR)
14 November 1991
SUPERSEDING
MIL-C-45573B Amd 1 (AR)
29 August 1986

MILITARY SPECIFICATION

CANNON, 165MM Gun: M135

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 165MM Gun: M135 consisting of a tube and breech mechanism assembly. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SC, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1025

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-G-10924 - Grease, Automotive and Artillery

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Equipment and Tools for Army Materiel, Packaging of

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

MIL-STD-2073-1 - DOD Materiel Procedures for Development and Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.5)

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

EPL 8769436 - Engineering Parts for Cannon, 165MM Gun: M135

P8769436 - Special Packaging Instructions, Cannon, 165MM Gun: M135

11579818 - Obturator Shimming Instructions

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

DA Form 2408-4 - Weapon Record Data

Master LQAP 8769436 - Master Index of Quality Assurance Provisions for Cannon, 165MM Gun: M135

DL 8769436 - Index of Inspection Equipment Lists for Cannon, 165MM Gun: M135

QAP-APPENDIX-WVA - General Quality Assurance Provisions

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1137.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable drawings (EPL 8769436), this specification, MIL-C-13931, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.3 and 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.3).

3.3 Preparation for assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

3.3.1 Tube and breech ring. When assembling the tube to the breech ring, grease conforming to MIL-G-10924 shall be used on the packing ring to reduce friction during assembly.

3.3.2 Lubrication. All surfaces of each leaf of the spring assembly, all bearing surfaces of the operating-shaft, the crank, the breech mechanism locking-key, the breechblock release crank, the adjustor, and sliding surfaces of the breechblock shall be coated with lubricant conforming to MIL-G-10924.

3.4 Functioning. All parts shall function smoothly without interference, erratic movement or malfunction.

3.4.1 Breech opening. The operating handle, when unlatched and rotated rearward, shall rotate the operating shaft and the operating crank to lower the breechblock. The breechblock shall then be locked in the open position by the release crank.

WARNING: The operating handle shall be returned and latched to prevent damage or injury during closing.

3.4.2 Breech closing. A quick upward pull of the release lever shall unseat the cam of the release crank. The closing spring shall rotate the operating shaft and the operating crank to raise the breechblock which shall be locked in the fully-closed position by engagement of the locking key into the recess of the operating shaft. The fully-closed position is indicated by alignment of the breechblock firing contact and the operating crank firing contact and full engagement of the locking key into the cutout in the hub of the operating handle. Full closing shall be obtained with the spring adjustor set for minimum preload which is the extreme counterclockwise position of the adjustor. This requirement applies only to cannon at room temperature with new spring packs. After considerable use and use at subzero temperatures, it is usually necessary to increase the preload on the spring by rotating the adjustor clockwise.

3.4.3 Manual breech closing. Manual closing of the breech shall be accomplished by rotating the operating handle until the clutch can be manually engaged in the hole provided in the crank. While maintaining pressure on the clutch pin, rotation of the handle upward and forward shall move the breechblock into the closed position.

3.5 Firing pin and connector assemblies. The firing pin assembly and connector assembly shall be assembled to assure proper contact of current-carrying parts.

3.5.1 Firing pin position. The point of the firing pin shall be flush to 0.005 inch recessed in the boss on the obturating spindle.

3.5.2 Continuity. The firing circuit shall show continuity with an applied voltage not exceeding 24 volts dc.

3.5.3 Dielectric strength. The firing circuit shall show no evidence of breakdown when subjected to a potential of not less than 1000 volts, rms, ac, 60 cycles per second for 30 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

3.5.4 Insulation resistance. The firing circuit shall have a minimum insulation resistance of one megohm when a potential of 500 volts dc is applied for one minute.

3.6 Obturator assembly.

3.6.1 Bearing of the obturator. The obturator shall be free from any visual defects such as cuts and abrasions. The mating surface of the breech ring shall be free from burrs, nicks, and tool marks. When the breech is closed, the obturator shall make 360 degrees line contact with the breech ring mating surface, the breech block and operating crank firing contacts shall be aligned, and the locking key shall be completely engaged into the cut out in the operating handle hub. It is to be noted that an overshimmed obturator may hang-up in the breech. See drawing 11579818 for obturator shimming instructions.

3.7 Ammunition loading rollers. Both rollers shall roll freely when spun by hand.

3.8 Performance.

3.8.1 High pressure resistance. The cannon and repair tubes shall be capable of withstanding 5800 ± 200 pounds per square inch at 70° F when tested as specified in 4.5.5.2.1.

3.8.2 Bore enlargement. Bore diameters measured across the rifled lands, after proof firing or first article testing shall not exceed the before firing diameters by the amounts shown in TABLE I.

TABLE I. Bore enlargement.

Distance forward of commencement of rifling	0.10 inch	1 cal.	2 cals. to muzzle
Amount (in inches)	0.006	0.006	0.004

NOTE: Interpolate to determine the bore enlargement between distances given.

3.8.3 Material soundness. After testing all parts shall be free from cracks and fractures, and shall comply with any soundness requirements specified on the applicable drawings.

3.8.4 Obturator pad adjustment. After performance testing, the obturator pad shall be adjusted in accordance with 3.6.1.

3.9 Workmanship. Workmanship shall be as required in MIL-C-13931.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Production Qualitification Test (PQT) (see 4.4).

c. Quality conformance inspection (see 4.5).

4.3 First Article Inspection. Unless otherwise specified in the contract, (see 6.2.1), first article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 8769436. First article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.4 Production Qualification Test (PQT). When specified in the contract, (see 6.2.1), cannon shall be subjected to production qualification testing by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of this specification and any additional requirements listed in the contract.

4.4.1 Sample. Three cannon shall be randomly selected from the first ten cannon produced during quantity production. These cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.4.2 Inspection provisions. Cannon shall be subjected to normal inspection per applicable item QAPs, and quality conformance inspection (see 4.5) including performance testing (see 4.5.5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.4.2.1 PQT tests. Unless otherwise specified in the contract, (see 6.2.1), cannon tests shall be performed in a suitable test facility mount, as applicable. All tests shall be conducted by the Government or any agency specified by the Government and may be conducted at a Government facility.

4.4.2.1.1 Ambient temperature firing test. This test shall be conducted on three cannon using the test method of 4.6.2. If the requirements are not complied with, acceptance shall be deferred and 4.7 applies.

4.4.2.1.2 Elevated temperature firing test. This test shall be conducted on three cannon using the test method of 4.6.3. If the requirements are not complied with, acceptance shall be deferred and 4.7 applies.

4.4.2.1.3 Cold temperature firing test. This test shall be conducted on three cannon using the test method of 4.6.4. If the requirements are not complied with, acceptance shall be deferred and 4.7 applies.

4.5 Quality conformance inspection. Quality conformance inspection is listed in TABLE II.

4.5.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance with the requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 8769436, and QAP-APPENDIX-WVA.

4.5.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.5.3 Inspection equipment. Data lists containing equipment used in the inspection of parts, subassemblies, and assemblies are listed in DL 8769436.

4.5.3.1 Acquisition, maintenance, and disposition. Unless otherwise specified (see 6.2.1), responsibility for acquisition, maintenance, and disposition of acceptance inspection and test equipment referenced in the List of Inspection Equipment DL 8769436, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, shall be in accordance with MIL-I-45607, (see 6.4).

4.5.3.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

TABLE II. Quality Conformance Inspection

Catagories/Characteristics	Requirement Paragraph	Inspection/Test-Method Paragraph
Examinations		4.5.4
Assembly	3.3.1	4.5.4.1
Lubrication	3.3.2	4.5.4.2
Functioning	3.4, 3.4.1, 3.4.2	4.5.4.3
Firing pin position	3.5.1	4.5.4.4
Bearing of the obturator	3.6.1	4.5.4.5
Ammunition loading rollers	3.7	4.5.4.6
Workmanship	3.9	4.5.4.7
Packaging inspection	5.	4.5.4.8
Tests		4.5.5
Firing mechanism electrical tests		4.5.5.1
Continuity	3.5.2	4.5.5.1.1
Dielectric strength	3.5.3	4.5.5.1.2
Insulation resistance	3.5.4	4.5.5.1.3
Performance testing	3.8	4.5.5.2
Proof firing tests	3.8.1	4.5.5.2.1
Obturator pad adjustment	3.8.4, 3.7.1	4.5.5.2.2
Functioning	3.4, 3.4.1, 3.4.2	4.5.5.2.3
Material soundness	3.8.3	4.5.5.2.4
Bore enlargement	3.8.2	4.5.5.2.5

4.5.4 Examinations.

4.5.4.1 Assembly. When assembling the tube to the breech ring the application of the specified grease shall be observed to determine conformance with 3.3.1.

4.5.4.2 Lubrication. When lubricating the breech ring assembly, the application and locations of application of the specified lubricant shall be observed to determine confommance with 3.3.2.

4.5.4.3 Functioning. After shimming of the obturator pad, manually operate the breech mechanism of each assembled cannon for a minimum of two complete cycles. Failure to comply with 3.4, 3.4.1 and 3.4.2 shall be cause for rejection.

4.5.4.4 Firing pin position, This measurement shall be made prior to assembly of the breechblock into the breech ring. After assembly of the firing circuit into the breechblock, the position of the firing pin shall be measured with a depth gage or an approved equivalent. Failure to comply with 3.5.1 shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

4.5.4.5 Bearing of the obturator. Visually examine the obturator for cuts, abrasions, and similar visual defects. Coat the seating surface in the breech ring with a thin coat of red lead, then close and open the breech, and examine the obturator for 360-degree line contact. Failure to meet the requirements of 3.6.1 shall be cause for rejection.

4.5.4.6 Ammunition loading rollers. Manually operate and visually examine the rollers to determine conformance with 3.7. Failure to meet the requirements shall be cause for rejection.

4.5.4.7 Workmanship. Workmanship shall be examined visually in accordance with MIL-C-13931.

4.5.4.8 Packaging inspection. Packaging inspection for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232. Packages failing to comply with the packaging requirements shall be rejected.

4.5.5 Tests

4.5.5.1 Firing mechanism electrical tests. Firing mechanism electrical tests shall be conducted on each cannon with approved test equipment. Tests shall consist of continuity, dielectric strength, and insulation resistance and shall be performed with the cannon breech in the closed position.

4.5.5.1.1 Continuity. Continuity of the firing circuit shall be determined by placing a circuit tester (11576610 or approved equivalent) into the breech end of the tube and pushing the tester forward until it stops at the raised diameter. After closing the breech mechanism, connect a dc power supply not exceeding 24 volts to the firing circuit. Continuity of the circuit will be indicated by the sounding of the buzzer of the tester. Failure to achieve an indication of continuity shall be cause for rejection.

4.5.5.1.2 Dielectric strength. After completion of the continuity test, an appropriate high potential tester shall be connected to the firing circuit and grounded on the breech ring or breechblock. A 60 cycles per second potential of 1000 volts rms shall be applied for 30 seconds. Any indication of breakdown shall be cause for rejection.

4.5.5.1.3 Insulation resistance. After completion of the dielectric strength test, a megohm bridge or other approved measuring instrument shall be connected to the firing circuit and grounded on the breech ring or breechblock. A potential of 500 volts dc shall be applied for one minute. Any firing mechanism failing to show minimum insulation resistance of one megohm shall be rejected.

4.5.5.2 Performance testing. Each cannon and repair tube shall be subject to performance testing to assure compliance with 3.8, by a Government activity in accordance with procedures specified by the Engineering and Product Assurance elements of the procuring activity.

4.5.5.2.1 Firing test. Each cannon and repair tube shall be subjected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

proof firing tests by the Government at a proving ground designated by USATECOM. The first cannon or repair tube manufactured under a new contract shall be subjected to the firing schedule shown in Table III. Subsequent cannon or repair tubes shall be proof fired with one round at a pressure of 5800 ± 200 pounds per square inch (psi) and be subject to such production tests as prescribed by the responsible commodity arsenal to ascertain conformance to specifications and performance requirements (see 6.2).

TABLE III. Firing schedule.

No. of rounds	Chamber pressure requirement, psi
1	5100
1	5800 ± 200
1	5100
1	5800 ± 200

4.5.5.2.2 Obturator pad adjustment. After firing, readjust the obturator in accordance with 3.6.1 and examine in accordance with 4.5.4.5.

4.5.5.2.3 Functioning. After performance testing, each cannon shall be tested for proper functioning in accordance with 4.5.4.3. Cannon failing to meet the requirements of 3.4 shall be cause for rejection.

4.5.5.2.4 Material soundness. After testing, each cannon and each repair tube shall be examined visually for freedom from cracks, fractures and other defects. Furthermore, breechblocks, breech rings and outer surfaces of tubes shall be magnetic particle inspected in accordance with applicable drawings and specifications. Inner surface of tubes shall be examined by means of a borescope. Any evidence of cracks or fractures shall be cause for rejection.

4.5.5.2.5 Bore enlargement. After proof-firing or PQT tests, the bore diameters across the lands of each cannon and each repair tube shall be measured with an air gage, electrical gage, or other approved gage. Measurements shall be recorded. Enlargement exceeding the limits specified in TABLE I shall be cause for rejection.

4.5.5.2.6 Records. Cannon and repair tubes that pass firing tests shall have applicable data entered on DA Form 2408-4, "Weapon Record Data" card by the proving ground.

4.6 PQT test methods.

4.6.1 Firing procedure. Firing procedure shall be as specified in 4.6.2, 4.6.3, and 4.6.4.

4.6.2 Ambient temperature firing test. A ten round group, preceded by two warmer rounds), shall be fired at a vertical target located at a range of 600 meters with

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

cannon and ammunition at ambient temperature. Measure chamber pressure and muzzle velocity. After firing, perform inspection prescribed in 4.5.5.1.1, 4.5.5.1.2, 4.5.5.1.3, 4.5.5.2.3, 4.5.5.2.4 and 4.5.5.2.5.

4.6.3 Elevated temperature firing test. A ten round group shall be fired with cannon and ammunition conditioned at +125°F. (Ammunition may either be conditioned at +125°F or powder increments added to simulate the pressure condition at the elevated temperature.) After firing, perform inspection prescribed in 4.5.5.1.1, 4.5.5.1.2, 4.5.5.1.3, 4.5.5.2.3, 4.5.5.2.4, and 4.5.5.2.5.

4.6.4 Cold temperature firing test. Ten round groups shall be fired at each of the following temperatures: -25° F, -40° F, and -50°F. After firing at each of the preceding temperatures, perform inspection prescribed in 4.5.5.1.1, 4.5.5.1.2, 4.5.5.1.3, 4.5.5.2.3, 4.5.5.2.4, and 4.5.5.2.5.

4.7 Failure analysis. The contractor shall assist in failure analysis procedures by performing a dimensional, physical, and visual examination of the components which are suspected to have caused the failure. Results shall be submitted to the Government for a final cause determination. The Government reserves the right to participate in any of the above examinations and tests. If it is determined that failure occurred because of deviation from specified dimensions or physical properties or both, the contractor shall accomplish, as applicable, the following actions:

a. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect in future production.

b. Examine completely assembled cannon and partially assembled cannon and components to ensure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.

c. Submit the corrective actions taken to the Government for evaluation and approval to retest or continue the test.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Special Packaging Instruction (SPI) P8769436 and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts - Level A, B and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair part SPI and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2). When Level C requirements are not shown on the PDS/SPI, Level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level X - Industrial packaging. Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D 3951 when industrial packaging is specified in the contract (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

5.2.1.1 Quantity in unit package (QUP). When Level C packaging in accordance with MIL-STD-1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of packages.

5.3.1 Levels A, B and C. Marking (including bar code marking) of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129 (see 6.2).

5.3.2 Level X - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D 3951 (see 6.2). Bar code marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cannon specified herein is intended for use with the Combat Engineer Vehicle, Full Tracked, M728 System.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.2).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.5.3.1).

j. Availability of inspection equipment from the Government.

k. Extent of contractor's responsibility for Government furnished and for

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

contractor-required final inspection equipment.

l. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4.5.5.2.1).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

p. Marking and bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.4 First article. When first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot of production items, a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.3. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

6.6 Subject term (key word) listing.

Cannon, 165MM: M135

Gun, 165MM: M135

Weapon

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research, Development and Engineering Center" (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, Ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8. Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR
(Project 1025-0174)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-45573C (AR)	14 NOVEMBER 1991

3. DOCUMENT TITLE

CANNON, 165MM GUN: M135

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
US ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial (201) 724-6662	(2) AUTOVON 880-6662
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL,NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:26Z
Check the source to verify that this is the current version before use.