INCH-POUND
MIL-C-45579C(AR)
8 March 1989
SUPERSEDING
MIL-C-45579B(AR)
4 March 1985

MILITARY SPECIFICATION

CANNON, 105MM HOWITZER: M137A1

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 105MM Howitzer: M137A1, consisting of a tube and a breech mechanism. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2). "

SPECIFICATIONS

Military

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Equipment arid Tools for Army Materiel, Packaging of

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use In improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SAS, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1015

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1189 . Bar Code Symbology, Standard Department of Defense

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing, and Marking

MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-2073-1 - DoD Materiel Procedures for Development and Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.5)

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

EPL 11577648 - Engineering Parts for Cannon, 105MM Howitzer: M137Al

P11577648 - Packaging Data Sheet, Cannon, 105MM Howitzer: M137A1

PUBLICATIONS

DL 11577648 - Index of Inspection Equipment Lists for Cannon, 105MM Howitzer: M137Al

Master LQAP 11577648 - Master Index of Quality Assurance Provisions for Cannon, 105MM Howitzer: M137A1

QAP-APPENDIX W A - General Quality Assurance Provisions

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the Issues of the documents which are DOD adopted are those listed In the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the D0DISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

ASTMD 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1137.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable drawings denoted in Engineering Parts List EPL 11577648, the requirements of this specification, the applicable paragraphs of the General Cannon Specification - MIL-C-13931 as incorporated in this document, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.1.1 Marking. When specified, marking shall be in accordance with the requirements specified in MIL-C-13931.

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.3 and 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.3).

3.3 Functioning. All parts shall function smoothly without interference, erratic movement or malfunction.

3.3.1 Breech mechanism. When the operating-lever is unlatched and rotated rearward (clockwise) it shall rotate the breechblock crank rearward and downward, thereby dropping the breechblock to open the breech. The extractors shall eject the empty cartridge case from the breech chamber and latch the breechblock in the open position. When the extractors are tripped (normally by insertion of a round) rotation of the operating lever counterclockwise raises the breechblock to the closed position. Counterclockwise rotation of the adjustor increases the preload on the breech mechanism counterbalance spring.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

3.3.2 Firing mechanism group. During dropping of the breechblock, the cocking lever, forced by a camming surface on the breech ring, engages the retractor. This engagement forces the precession mechanism rearward thereby compressing the firing spring. During retraction, the sear which is subjected to a torsion load is rotated by the percussion mechanism as well. During overtravel, the sear rotates back to its assembly position, thereby arresting the percussion mechanism in the cocked (ready to fire) position. Rearward movement of the trigger plunger rotates the trigger which In turn rotates the sear, thereby releasing the percussion mechanism. The compressed firing spring drives the percussion mechanism forward and the firing pin strikes the cartridge case primer. Simultaneously, the firing pin retracting spring is driven in the compressed direction. The expanding retracting spring then withdraws the firing pin behind the front face of the breechblock.

3.3.3 Firing pin Protrusion. When fired. the Protrusion of the firing pin from the front of the breechblock shall be not-less than 0.10 inch nor more-than 0.16 inch.

3.3.4 Firing mechanism overtravel. Overtravel of the firing mechanism in cocking shall be not less than 0.050 inch.

3.3.5 Headspace. Headspace, the distance from the front face of the closed and locked breechblock and the rear face of the tube shall not be less than 0.188 inch nor more than 0.206 inch.

3.4 Performance.

3.4.1 High pressure resistance. The cannon and replacement tubes shall be capable of withstanding 44 100 + 1600 pounds per square inch at 70 degrees F when tested as specified in 4.4.6.1.1 and 4.4.6.1.2.

3.4.2 Material soundness. After testing, all parts shall be free from cracks and fractures, and shall comply with any soundness requirements on the applicable drawings.

3.4.3 Bore enlargement. Bore diameters measured across the rifled lands, after proof firing no more than 8 rounds, shall not exceed the before firing diameters by more than the amounts shown in TABLE I.

TABLE I. Bore enlargement.

Distance forward of commencement of rifling	0.10 inch	1 inch	1 cal.	2 cals. to muzzle
Amount (in inches)	0.003	0.003	0.002	0.002

NOTE : Interpolate to determine the amount between given distances.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor Is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the Inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5 The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to-ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does It commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. Unless otherwise specified in the contract, (see First article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 11577648. First article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.3.1 First Article - Initial Production Test (FA-IPT). When specified in the contract, (see 6.2), first article cannon shall be subjected to initial production-testing by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of thiss specification and any additional requirements listed in the contract. FA-IPT procedures and the sample size of first article cannon shall be as specified in the contract. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Quality conformance inspection is listed in Table II.

TABLE II. Qualitv conformance inspection.

Categories/Characteristics	Requirement Paragraph	Inspection Paragraph
Examinations		
Firing pin protrusion	3.3*3	4.4.4.1
Firing mechanism overtravel	3.3.4	4.4.4.2
Headspace	3.3.5	4.4.4.3
Material soundness	3.4.2	4.4.4.4
Packaging	5.	4.4.4.5
Functional inspection		
Breech mechanism	3.3.1	4.4.5.1
Tests		
Proof acceptance	3.4	4.4.6.1
Proof firing	3.4.1, 3.4.2 3.4.3	4.4.6.1.1
Proof pressure simulation	3.4.1, 3.4.2	4.4.6.1.2

4.4.1 Inspection **provisionS.** Cannon and parts shall be inspected for conformance with the requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 11577648, and QAP-APPENDIX-WVA.

4.4.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4..4.3 Inspection equipment. Data lists containing equipment used in the inspection of parts, subassemblies, and assemblies are listed in DL 11577648.

4.4.3.1 Acquistions, maintenance, and disposition. Unless otherwise specified (see 6.2), responsibility for acquisition, maintenance, and disposition of acceptance inspection and test equipment referenced in the List of Inspection Equipment DL 11577648, and for all other inspection equipment required to perform inspection prescribed by applicable specifications and QAPs, shall be in accordance with MIL-I-45607. (see 6.21.

4.4.3.2 Accuracy of commercial measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of ten percent of the total tolerance of the characteristic being inspected.

4.4.4 Examinations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

4.4.4.1 Firing pin protrusion. The protrusion of the firing pin from the front of each breechblock shall be gaged using Gage 7248891 (2 pieces) or approved equivalent before assembly of the breechblock into the breech recess. After assembly of the firing mechanism into the breechblock, push the firing pin fully forward and gage the protrusion by use of piece 2 of Gage 7248891. Failure to meet the requirements of 3.3.3 shall be cause for rejection.

4.4.4.2 Firing mechanism overtravel. Firing mechanism overtravel shall be determined on each breech mechanism using a depth gage as follows: With the breech mechanism assembled in the tube, remove the firing mechanism retainer from the block. Lower the breechblock slowly to the point where the cocking mechanism engages the firing mechanism, as indicated by an audible click. Holding the breechblock in this position, measure with a depth gage and record the distance from the rear face of the firing pin guide. Holding the depth gage in position against the breechblock, slowly lower the breechblock to the bottom of the travel. Movement of the breechblock will cause the firing pin guide to move backward. This firing pin guide movement will cause the depth gage reading to change. At some point, the depth gage reading will be a minimum. This point may or may not be at the bottom of the breechblock travel, due to the curved cam surface of the block plus tolerance build-up on components involved. Record the minimum depth gage reading. Subtract the second reading from the first reading to determine the overtravel of the firing mechanism. Failure to meet the requirements of 3.3.4 shall be cause for rejection.

4.4.4.3 Heads ace. Headspace shall remeasured on each cannon with gages 8773818 and 8773819 or approved equivalents. Failure to meet the requirements of 3.3.5 shall be cause for rejection.

4.4.4.4 Material soundness. All external and internal surfaces of each tube, breech ring, and breechblock shall be examined by magnetic partfcle inspection in accordance with the procedures and acceptance criteria of the applicable General Data Drawings.

4.4.4.5 Packaging inspection. Packaging inspect~on for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232. Packages failing to comply with the packaging requirements shall be rejected.

4.4.5 Functional inspections.

4.4.5.1 Functioning tests. The breech mechanism of each assembled cannon shall be operated manually for a minimum of two complete cycles of operation. Cocking action, trigger actuation, firing mechanism action, and breech mechanism operation tests shall be performed to ascertain proper functioning. With the cannon in a horizontal position, extraction shall be tested with an empty service cartridge case. Any evidence of binding, scraping, looseness or other malfunction of any part or failure to completely eject an empty service cartridge case shall be cause for rejection.

4.4.6 Tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

4.4.6.1 Proof acceptance. Cannon shall be proof accepted through proof firing, breech mechanism proof pressure simulation tests, or both. Cannon and replacement tubes to be proof-fired-shall be fired in accordance with 4.4.6.1.1. Failure to comply with the requirements of 3.4.1, 3.4.2, and 3.4.3 shall be cause for rejection. Breech mechanisms to be simulation proof tested shall be proof tested in accordance with 4.4.6.l.2. Failure to comply with the requirements of 3.4.1 and 3.4.2 shall be cause for rejection. Proof firing performed on a sampling basis shall be conducted as follows:

a. Using plan CSP-1 of MIL-STD-1235 the Product Assurance Directorate at Watervliet Arsenal shall designate the appropriate initial quantity (i) and sample frequency (f), in the contract (see 6.2).

b. The first "i" quantity of cannon or tubes produced in a particular buy shall be proof fired. When the "i" quantity has been satisfied, sampling shall be put into effect using the "f" sampling frequency. If a cannon is rejected, sampling shall be discontinued and the "i" quantity reinstated. All cannon not proof fired shall have the breech mechanisms simulation proof tested in the Product Assurance Weapon Test Facility at Watervliet Arsenal.

c. Successive production buys shall not require "i" quantities. However, if the time lag between two successive buys exceeds one year, or if a new cannon or tube contractor is utilized, a new "i" quantity shall be proof fi red.

d. Proof fired cannon and replacement tubes, and simulation proof tested breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data) as specified by Product Assurance Directorate at Watervliet Arsenal.

e. When specified in the contract (see 6.2), the weapon simulation test facility shall be qualified as follows: a sample of breech mechanisms of cannon to be sent to the Proving ground for proof firinq shall be subjected initially to simulation-proof testing at the weapon simulation test facility.

4.4.6.1.1 Proof firing Proof firing shall be conducted at a Government test site. The proce ure shall be as follows:

a. Each cannon or replacement tube shall be proof fired within the proof pressure range specified in 3.4.1. If the lower limit is not attained, additional rounds shall be fired until the minimum value is attained. The number of additional rounds shall not exceed five.

b. A facility mount may be used if necessary.

c. Chamber pressure shall be measured and recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

d. After proof firing:

(1) The bore of each tube shall be examined for bore enlargement using an air gage or other approved gages. Enlargements exceeding the limits specified in TABLE I shall be cause for rejection (see 3.4.3).

(2) Each tube shall be borescoped and magnetic particle inspected (see 4.4.4.4).

(3) Each breech mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5.1),

(4) Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4-4.4).

(5) Each breech mechanism shall be cleaned and reassembled. The breech mechanism shall then be functioned in accordance with 4.4.5.1.

e. Cannon found to be defective at the proving ground shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189-4050 and Benet Labs, Watervliet Arsenal, Watervliet, NY 12189-4050 within one working day. The test agency shall forward, a Test Incident Report (TIR), incident to the deficiency, within three working days.

4.4.6.1.2 Proof pressure simulation. All cannon not proof fired at a proving ground shall have the breech mechanism proof tested in accordance with the following procedure:

a. Each breech mechanism shall be tested by means of suitable hydraulic pressure testing equipment at a pressure within the proof pressure range specified in 3.4.1.

b. Cycle time to achieve test pressure and release shall not exceed three minutes. Test pressure shall be immediately released upon its attainment. Dwell time at test pressure shall not exceed three seconds.

(1) when difficulty is encountered in attaining test pressure, the number of attempts in which ten percent or less of the test pressure is attained shall not be counted. The number of attempts in which over ten percent of the test pressure is attained, shall not exceed five.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism shall be subjected to proof firing as part of a cannon (see 4.4.6.l.1). A notification of this condition shall be submitted with the breech mechanism to the proving ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

c. The peak pressure shall be recorded for each test and attached to inspection records identifiable with the specific breech mechanism undergoing test.

d. After the pressure test, each breech mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5.1).

e. Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be visually examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4.4.4).

f. Each breech mechanism shall be cleaned and reassembled. The breech mechanism shall then be functioned in accordance with 4.4.5.1.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Packaging Data Sheet (PDS) P11577648 and MIL-P-14232 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts - Level A, B and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be In accordance with the applicable repair part PDS and MIL-P-14232 or the applicable repair part SPI and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2). When Level C requirements are not shown on the PDS/SPI, Level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level X - Industrial packaging. Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D 3951 when industrial packaging is specified in the contract (see 6.2).

5.2.1.1 Quantity in Unit Package (QUP). When Level C packaging in accordance with MIL-STD-1190 or industrtal packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of packages.

5.3.1 Levels A, B and C. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

5.3.2 Level X - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D 3951. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cannon specified herein is intended for use in the Light Towed Howitzer, 105MM M102, System.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific Issue of Individual documents referenced (see 2.1.1).

c. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.2).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.4.3).

j. Availability of inspection equipment from the Government.

k. Extent of contractor's responsibility for Government furnished and for contractor-required final inspection equipment.

Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4.4.6.1).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

p. When applicable, bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3	DI-T-4902	First Article Inspection Report	

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 First article. When first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot of production items, a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.3. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide.that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at watervliet Arsenal.

6.6 Subject term (key word) listing.

Cannon, 105MM: M137A1

Howitzer, 105MM: M137AI

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

6,7 Drawing s. Drawings listed In Section 2 of this specification under the h e a d i n g Army Armament Research, Development **and Engineering Center"** (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, Ordnance **Corps,** Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Changes from previous issue. Marginal notations are **not used in this revision to** identity changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR .

Preparing activity:
Army-AR

(Project 1OI5-A32O)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45579C (AR)	Cannon, 105MM Howitzer: M137A1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF HE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

● CNALTV FOR ● RIVAW

BUSINESS REPLY MAIL

● ERMIT NO. 12= WA8H INGTON D. C.

POSTAGE WILL BEPA108Y THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemc ial Command
ATTN : SMC~-CCB-SAS
Watervliet, NY ~l~+g-hoso"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:27Z
Check the source to verify that this is the current version before use.